

Data sheet for household cooker hoods

In acc. with delegated regulation (EU) No. 65/2014 and regulation (EU) No. 66/2014

Miele					
Model name/identifier		DA 6708 D Aura Ed. 6000			
Annual Energy Consumption (AEC) (AEC _{rpm})	kWh/year	80,6			
Energy efficiency class		C			
Energy efficiency index (EEI) (EEI _{rpm})		83,3			
Fluid Dynamic Efficiency (FDE) (FDE _{rpm})		15,4			
Fluid Dynamic Efficiency class					
A (most efficient) to G (least efficient)		D			
Lighting Efficiency (LE) (LE _{rpm})	lx/W	60,0			
Lighting Efficiency class					
A (most efficient) to G (least efficient)		A			
Grease Filtering Efficiency	%	91,2			
Grease Filtering Efficiency class					
A (most efficient) to G (least efficient)		B			
Airflow at best efficiency point	m ³ /h	348,7			
Air flow (min. speed)	m ³ /h	250			
Air flow (max. speed)	m ³ /h	470			
Air flow (intensive or boost setting)	m ³ /h	620			
Max. air flow (Q) (Q _{max})	m ³ /h	620			
Air pressure at best efficiency point	Pa	216			
Airborne acoustical A-weighted sound power emissions (min. speed)	dB	54			
Airborne acoustical A-weighted sound power emissions (max. speed)	dB	67			
Airborne acoustical A-weighted sound power emissions (intensive or boost setting)	dB	74			
Electrical power input at best efficiency point	W	136,0			
Power consumption in off mode (P _o)	W				
Power consumption in standby mode (P _s)	W	0,35			
Nominal power of lighting system	W	12,0			
Average illumination of the lighting system on the cooking surface	lx	720			
Time increase factor		1,4			