Maximum temperature inside the treated textile <sup>(a)</sup> (°C)	Value 8.0 41.6 1.031		Miele Carl-Miele-Straße 29, 33332 Güter WWB380 WCS 125 Edition  Parameter  Dimensions in cm	sloh, DE  Value  Height  Width	85
Model identifier  General product parameters  Parameter  Rated capacity <sup>(a)</sup> (kg)  Energy efficiency index EEI <sub>w</sub> <sup>(a)</sup> Washing efficiency index <sup>(a)</sup> Energy consumption in kWh per cycle, based on the eco 40-60 programme at a combination of full and partial loads. Actual energy consumption will depend on how the appliance is used.  Maximum temperature inside the treated textile <sup>(a)</sup> (°C)	8.0		WWB380 WCS 125 Edition  Parameter	<b>Value</b> Height	85
General product parameters  Parameter  Rated capacity <sup>(a)</sup> (kg)  Energy efficiency index EEI <sub>w</sub> <sup>(a)</sup> Washing efficiency index <sup>(a)</sup> Energy consumption in kWh per cycle, based on the eco 40-60 programme at a combination of full and partial loads. Actual energy consumption will depend on how the appliance is used.  Maximum temperature inside the treated textile <sup>(a)</sup> (°C)	8.0		Parameter	Height	85
Parameter  Rated capacity <sup>(a)</sup> (kg)  Energy efficiency index EEI <sub>w</sub> <sup>(a)</sup> Washing efficiency index <sup>(a)</sup> Energy consumption in kWh per cycle, based on the eco 40-60 programme at a combination of full and partial loads. Actual energy consumption will depend on how the appliance is used.  Maximum temperature inside the treated textile <sup>(a)</sup> (°C)	8.0		_	Height	85
Rated capacity <sup>(a)</sup> (kg)  Energy efficiency index EEI <sub>w</sub> <sup>(a)</sup> Washing efficiency index <sup>(a)</sup> Energy consumption in kWh per cycle, based on the eco 40-60 programme at a combination of full and partial loads. Actual energy consumption will depend on how the appliance is used.  Maximum temperature inside the treated textile <sup>(a)</sup> (°C)	8.0		_	Height	85
Energy efficiency index EEI <sub>w</sub> <sup>(a)</sup> Washing efficiency index <sup>(a)</sup> Energy consumption in kWh per cycle, based on the eco 40-60 programme at a combination of full and partial loads. Actual energy consumption will depend on how the appliance is used.  Maximum temperature inside the treated textile <sup>(a)</sup> (°C)	41.6		Dimensions in cm	-	85
Energy efficiency index EEI <sub>w</sub> <sup>(a)</sup> Washing efficiency index <sup>(a)</sup> Energy consumption in kWh per cycle, based on the eco 40-60 programme at a combination of full and partial loads. Actual energy consumption will depend on how the appliance is used.  Maximum temperature inside the treated textile <sup>(a)</sup> (°C)	41.6		Dimensions in cm	Width	<b></b>
Washing efficiency index <sup>(a)</sup> Energy consumption in kWh per cycle, based on the eco 40-60 programme at a combination of full and partial loads. Actual energy consumption will depend on how the appliance is used.  Maximum temperature inside the treated textile <sup>(a)</sup> (°C)					60
Washing efficiency index <sup>(a)</sup> Energy consumption in kWh per cycle, based on the eco 40-60 programme at a combination of full and partial loads. Actual energy consumption will depend on how the appliance is used.  Maximum temperature inside the treated textile <sup>(a)</sup> (°C)				Depth	64
Energy consumption in kWh per cycle, based on the eco 40-60 programme at a combination of full and partial loads. Actual energy consumption will depend on how the appliance is used.  Maximum temperature inside the treated textile(a) (°C)	1.031		Energy efficiency class <sup>(a)</sup>	A	
kWh per cycle, based on the eco 40-60 programme at a combination of full and partial loads. Actual energy consumption will depend on how the appliance is used.  Maximum temperature inside the treated textile(a) (°C)			Rinsing effectiveness (g/kg) <sup>(a)</sup>	5.0	
Maximum temperature inside the treated textile <sup>(a)</sup> (°C)	0.378		Water consumption in litre per cycle, based on the eco 40-60 programme at a combination of full and partial loads. Actual water consumption will depend on how the appliance is used and on the hardness of the water.	48	
the treated textile <sup>(a)</sup> (°C)	Rated capacity	32			
F	Half 28		Weighted remaining moisture	53.5	
	Quarter	25	content <sup>(a)</sup> (%)		
	Rated capacity	1400		В	
Spin speed <sup>(a)</sup> (rpm)	Half	1400 Spin-drying efficiency class <sup>(a)</sup>	Spin-drying efficiency class <sup>(a)</sup>		
	Quarter	1400			
Programme duration <sup>(a)</sup> (h:min)	Rated capacity	3:39		Free-standing	
	Half	2:48	Design type		
	Quarter	2:29			
Airborne acoustical noise emission class <sup>(a)</sup> (spinning phase)	72		Airborne acoustical noise emission class <sup>(a)</sup> (spinning phase)	А	
Off-mode (W) (if applicable)	0.30		Standby mode (W) (if applicable)	-	
Delay start (W) (if applicable)	3.00		Networked standby (W) (if applicable)	0.60	
Minimum duration of the guarant	tee offered by the	supplier	24 months		
This product has been designed to the washing cycle	o release silver io	ns during	no		
Additional information					
Weblink to the supplier's website, w 9 of Annex II to Commission Regula found		•	https://www.miele.com/		