Data sheet for household cooker hoods
In acc. with delegated regulation (EU) No. 65/2014 and regulation (EU) No. 66/2014

Miele				
Model name/identifier		DA 2450-1		
Annual Energy Consumption (AEC)				
(AEC _{rpm})	kWh/year	52,6		
Energy efficiency class		Α		
Energy efficiency index (EEI) (EEI _{ppm})		54,7		
Fluid Dynamic Efficiency (FDE) (FDE _{rom})		29,5		
Fluid Dynamic Efficiency class				
A (most efficient) to G (least efficient)		Α		
Lighting Efficiency (LE) (LE _{rpm})	lx/W	55,0		
Lighting Efficiency class				
A (most efficient) to G (least efficient)		Α		
Grease Filtering Efficiency	%	94,6		
Grease Filtering Efficiency class				
A (most efficient) to G (least efficient)		В		
Airflow at best efficiency point	m³/h	340,1		
Air flow (min. speed)	m³/h	230		
Air flow (max. speed)	m³/h	590		
Air flow (intensive or boost setting)	m³/h			
Max. air flow (Q) (Q _{max})	m³/h	590		
Air pressure at best efficiency point	Pa	440		
Airborne acoustical A-weighted sound power emiss	sions			
(min. speed)	dB	47		
Airborne acoustical A-weighted sound power emiss				
(max. speed)	dB	66		
Airborne acoustical A-weighted sound power emiss				
(intensive or boost setting)	dB			
Electrical power input at best efficiency point	W	141,0		
Power consumption in off mode (P _o)	W	0,00		
Power consumption in standby mode (Ps)	W	0.0		
Nominal power of lighting system	W	6,0		
Average illumination of the lighting system on the c surface	оокing lx	330		
Time increase factor	IX	0,9		
Time morease racion		0,9		