Data sheet for household cooker hoods In acc. with delegated regulation (EU) No. 65/2014 and regulation (EU) No. 66/2014

Miele					
Model name / identifier		PUR 68 W			
Annual Energy Consumption (AEC)					
(AEC _{rpm})	kWh/year	47,0			
Energy efficiency class		А			
Energy efficiency index (EEI) (EEI _{rpm})		48,4			
Fluid Dynamic Efficiency (FDE) (FDE _{rpm})		32,8			
Fluid Dynamic Efficiency class		- ,-			
A (most efficient) to G (least efficient)		Α			
Lighting Efficiency (LE) (LE _{rpm})	lx/W	55,0			
Lighting Efficiency class					
A (most efficient) to G (least efficient)		Α			
Grease Filtering Efficiency	%	95,1			
Grease Filtering Efficiency class					
A (most efficient) to G (least efficient)		A			
Airflow at best efficiency point	m³/h	374,5			
Air flow (min. speed)	m³/h	265			
Air flow (max. speed)	m³/h	395			
Air flow (intensive or boost setting)	m³/h	650			
Max. air flow (Q) (Q _{max})	m³/h	650			
Air pressure at best efficiency point	Pa	450			
Airborne acoustical A-weighted sound power emis	sions				
(min. speed)	dB	47			
Airborne acoustical A-weighted sound power emis					
(max. speed)	dB	56			
Airborne acoustical A-weighted sound power emis					
(intensive or boost setting)	dB	67			
Electrical power input at best efficiency point	W	142,7			
Power consumption in off mode (P_o)	W				
Power consumption in standby mode (P _s)	W	0,20			
Nominal power of lighting system	W	6,0			
Average illumination of the lighting system on the	0	220			
surface Time increase factor	lx	330 0,8			
		0,0		 	