

Product information sheet

DELEGATED REGULATION (EU) 2019/2014

Supplier's name or trade mark Miele

Supplier's address Carl-Miele-Straße 29, 33332 Gütersloh, DE

Model identifier WTD165 WPM 8/5 kg

General product parameters

Parameter	Value		Parameter	Value	
Rated capacity (kg)	Rated capacity ^(b)	5.0	Dimensions in cm	Height	85
	Rated washing capacity ^(a)	8.0		Width	60
				Depth	64
Energy Efficiency Index	$EEI_W^{(a)}$	51.6	Energy efficiency class	$EEI_W^{(a)}$	A
	$EEI_{WD}^{(b)}$	66.9		$EEI_{WD}^{(b)}$	D
Washing efficiency index	$I_W^{(a)}$	1.045	Rinsing effectiveness (g/kg dry textile)	$I_R^{(a)}$	4.0
	$J_W^{(b)}$	1.036		$J_R^{(b)}$	4.0
Energy consumption in kWh per cycle, for the washing cycle of the household washer-dryer, using the eco 40-60 programme at a combination of full and partial loads. Actual energy consumption will depend on how the appliance is used	0.469		Energy consumption in kWh per cycle, for the wash and dry cycle of the household washer-dryer at a combination of full and half loads. Actual energy consumption will depend on how the appliance is used	2.658	
Water consumption in litre per cycle, for the eco 40-60 programme at a combination of full and partial loads. Actual water consumption will depend on how the appliance is used and on the hardness of the water	47		Water consumption in litre per cycle, for the wash and dry cycle of the household washer-dryer at a combination of full and half loads. Actual water consumption will depend on how the appliance is used and on the hardness of the water	68	
Maximum temperature inside the treated textile (°C) for the washing cycle of the household washer-dryer, using the eco 40-60 programme	Rated washing capacity	43	Maximum temperature inside the treated textile (°C) for the washing cycle of the household washer-dryer, using the wash and dry cycle.	Rated capacity	35
	Half	32		Half	28
	Quarter	25			
Spin speed ^(a) (rpm)	Rated washing capacity	1500	Weighted remaining moisture content ^(a) (%)	0.0	
	Half	1500			
	Quarter	1500			
Eco 40-60 programme duration (h:min)	Rated washing capacity	3:39	Spin-drying efficiency class ^(a)	B	
	Half	2:48			
	Quarter	2:48			

^(a) for the eco 40-60 programme

^(b) for the wash and dry cycle

Airborne acoustical noise emissions during the spinning phase for the eco 40-60 washing cycle at rated washing capacity (dB(A) re 1 pW)	71	wash and dry cycle duration (h:min)	Rated capacity	6:29
			Half	3:59
Design type	Free-standing	Airborne acoustical noise emission class for the spinning phase for the eco 40-60 programme at rated washing capacity	A	
Off-mode (W) (if applicable)	0.30	Standby mode (W) (if applicable)	-	
Delay start (W) (if applicable)	2.60	Networked standby (W) (if applicable)	0.70	
Minimum duration of the guarantee offered by the supplier	24 months			
This product has been designed to release silver ions during the washing cycle	no			
Additional information				
Weblink to the supplier's website, where the information in point 9 of Annex II to Regulation (EU) 2019/2023 is found	https://www.miele.com/			
^(a) for the eco 40-60 programme ^(b) for the wash and dry cycle				