Maximum temperature inside the treated textile ^(a) (°C)	9.0 41.6 1.031 0.396		Miele Carl-Miele-Straße 29, 33332 Güter WSD383 WCS PWash&Steam&9k Parameter Dimensions in cm Energy efficiency class ^(a) Rinsing effectiveness (g/kg) ^(a) Water consumption in litre per cycle, based on the eco 40-60 programme at a combination of full and partial loads. Actual water consumption will	Value Height Width Depth A 5.0	85 60 64
Model identifier General product parameters Parameter Rated capacity ^(a) (kg) Energy efficiency index EEI _w ^(a) Washing efficiency index ^(a) Energy consumption in kWh per cycle, based on the eco 40-60 programme at a combination of full and partial loads. Actual energy consumption will depend on how the appliance is used. Maximum temperature inside the treated textile ^(a) (°C)	9.0 41.6 1.031		Parameter Dimensions in cm Energy efficiency class ^(a) Rinsing effectiveness (g/kg) ^(a) Water consumption in litre per cycle, based on the eco 40-60 programme at a combination of full and partial loads. Actual water consumption will	Value Height Width Depth A 5.0	60
General product parameters Parameter Rated capacity ^(a) (kg) Energy efficiency index EEI _w ^(a) Washing efficiency index ^(a) Energy consumption in kWh per cycle, based on the eco 40-60 programme at a combination of full and partial loads. Actual energy consumption will depend on how the appliance is used. Maximum temperature inside the treated textile ^(a) (°C)	9.0 41.6 1.031		Parameter Dimensions in cm Energy efficiency class ^(a) Rinsing effectiveness (g/kg) ^(a) Water consumption in litre per cycle, based on the eco 40-60 programme at a combination of full and partial loads. Actual water consumption will	Value Height Width Depth A 5.0	60
Parameter Rated capacity ^(a) (kg) Energy efficiency index EEI _w ^(a) Washing efficiency index ^(a) Energy consumption in kWh per cycle, based on the eco 40-60 programme at a combination of full and partial loads. Actual energy consumption will depend on how the appliance is used. Maximum temperature inside the treated textile ^(a) (°C)	9.0 41.6 1.031		Dimensions in cm Energy efficiency class ^(a) Rinsing effectiveness (g/kg) ^(a) Water consumption in litre per cycle, based on the eco 40-60 programme at a combination of full and partial loads. Actual water consumption will	Height Width Depth A 5.0	60
Rated capacity ^(a) (kg) Energy efficiency index EEI _w ^(a) Washing efficiency index ^(a) Energy consumption in kWh per cycle, based on the eco 40-60 programme at a combination of full and partial loads. Actual energy consumption will depend on how the appliance is used. Maximum temperature inside the treated textile ^(a) (°C)	9.0 41.6 1.031		Dimensions in cm Energy efficiency class ^(a) Rinsing effectiveness (g/kg) ^(a) Water consumption in litre per cycle, based on the eco 40-60 programme at a combination of full and partial loads. Actual water consumption will	Height Width Depth A 5.0	60
Energy efficiency index EEI _w ^(a) Washing efficiency index ^(a) Energy consumption in kWh per cycle, based on the eco 40-60 programme at a combination of full and partial loads. Actual energy consumption will depend on how the appliance is used. Maximum temperature inside the treated textile ^(a) (°C)	41.6 1.031 0.396		Energy efficiency class ^(a) Rinsing effectiveness (g/kg) ^(a) Water consumption in litre per cycle, based on the eco 40-60 programme at a combination of full and partial loads. Actual water consumption will	Width Depth A 5.0	60
Energy efficiency index EEI _w (a) Washing efficiency index(a) Energy consumption in kWh per cycle, based on the eco 40-60 programme at a combination of full and partial loads. Actual energy consumption will depend on how the appliance is used. Maximum temperature inside the treated textile(a) (°C)	41.6 1.031 0.396		Energy efficiency class ^(a) Rinsing effectiveness (g/kg) ^(a) Water consumption in litre per cycle, based on the eco 40-60 programme at a combination of full and partial loads. Actual water consumption will	Depth A 5.0	
Washing efficiency index ^(a) Energy consumption in kWh per cycle, based on the eco 40-60 programme at a combination of full and partial loads. Actual energy consumption will depend on how the appliance is used. Maximum temperature inside the treated textile ^(a) (°C)	0.396		Rinsing effectiveness (g/kg) ^(a) Water consumption in litre per cycle, based on the eco 40-60 programme at a combination of full and partial loads. Actual water consumption will	5.0	64
Washing efficiency index ^(a) Energy consumption in kWh per cycle, based on the eco 40-60 programme at a combination of full and partial loads. Actual energy consumption will depend on how the appliance is used. Maximum temperature inside the treated textile ^(a) (°C)	0.396		Rinsing effectiveness (g/kg) ^(a) Water consumption in litre per cycle, based on the eco 40-60 programme at a combination of full and partial loads. Actual water consumption will	5.0	
Energy consumption in kWh per cycle, based on the eco 40-60 programme at a combination of full and partial loads. Actual energy consumption will depend on how the appliance is used. Maximum temperature inside the treated textile(a) (°C)	0.396		Water consumption in litre per cycle, based on the eco 40-60 programme at a combination of full and partial loads. Actual water consumption will		
kWh per cycle, based on the eco 40-60 programme at a combination of full and partial loads. Actual energy consumption will depend on how the appliance is used. Maximum temperature inside the treated textile(a) (°C)			cycle, based on the eco 40-60 programme at a combination of full and partial loads. Actual water consumption will	50	
Maximum temperature inside the treated textile ^(a) (°C)	Rated capacity		depend on how the appliance is used and on the hardness of the water.	50	
the treated textile ^(a) (°C)		ed capacity 33		53.9	
R	Half 32		Weighted remaining moisture		
	Quarter	25	content ^(a) (%)		
Spin speed ^(a) (rpm)	Rated capacity	1400			
	Half	1400	Spin-drying efficiency class ^(a)	В	
	Quarter	1400			
Programme duration ^(a) (h:min)	Rated capacity	3:49		Design type Free-standing	
	Half	2:54	Design type		
	Quarter	2:26			
Airborne acoustical noise emission class ^(a) (spinning phase)	72		Airborne acoustical noise emission class ^(a) (spinning phase)	А	
Off-mode (W) (if applicable)	0.30		Standby mode (W) (if applicable)	-	
Delay start (W) (if applicable)	3.00		Networked standby (W) (if applicable)	0.60	
Minimum duration of the guarante	ee offered by the	e supplier	24 months		
This product has been designed to the washing cycle	release silver io	ons during	no		
Additional information					
Weblink to the supplier's website, wl 9 of Annex II to Commission Regula found		•	https://www.miele.com/		