Data sheet for household cooker hoods
In acc. with delegated regulation (EU) No. 65/2014 and regulation (EU) No. 66/2014

Miele			 	
Model name / identifier		DAR 1135		
Annual Energy Consumption (AEC)				
(AEC _{rpm})	kWh/year	68,4		
Energy efficiency class		В		
Energy efficiency index (EEI) (EEI _{rpm})		65.3		
Fluid Dynamic Efficiency (FDE) (FDE _{rom})		24,9		
Fluid Dynamic Efficiency class		,-		
A (most efficient) to G (least efficient)		В		
Lighting Efficiency (LE) (LE _{rom})	lx/W	75,0		
Lighting Efficiency class				
A (most efficient) to G (least efficient)		Α		
Grease Filtering Efficiency	%	80,9		
Grease Filtering Efficiency class				
A (most efficient) to G (least efficient)		С		
Airflow at best efficiency point	m³/h	394,8		
Air flow (min. speed)	m³/h	200		
Air flow (max. speed)	m³/h	400		
Air flow (intensive or boost setting)	m³/h	650		
Max. air flow (Q) (Q _{max})	m³/h	650		
Air pressure at best efficiency point	Pa	349		
Airborne acoustical A-weighted sound power emiss	sions			
(min. speed)	dB	39		
Airborne acoustical A-weighted sound power emiss				
(max. speed)	dB	54		
Airborne acoustical A-weighted sound power emiss				
(intensive or boost setting)	dB	67		
Electrical power input at best efficiency point	W	153,7		
Power consumption in off mode (Po)	W	0,00		
Power consumption in standby mode (Ps)	W			
Nominal power of lighting system	W	9,0		
Average illumination of the lighting system on the c surface		675		
Time increase factor	lx	675 1,1		
Time increase factor		1,1	 	