

# Data sheet for household cooker hoods

In acc. with delegated regulation (EU) No. 65/2014 and regulation (EU) No. 66/2014

Miele	
Model identifier	DA 1260
Annual Energy Consumption (AEC <sub>hood</sub> )	kWh/year 91.6
Energy efficiency class	C
Energy efficiency index (EEI <sub>hood</sub> )	82.1
Fluid Dynamic Efficiency (FDE <sub>hood</sub> )	16.3
Fluid Dynamic Efficiency class	
A (most efficient) to G (least efficient)	D
Lighting Efficiency (LE <sub>hood</sub> )	lx/W 55.0
Lighting Efficiency class	
A (most efficient) to G (least efficient)	A
Grease Filtering Efficiency	% 95.1
Grease Filtering Efficiency class	
A (most efficient) to G (least efficient)	A
Airflow at best efficiency point	m <sup>3</sup> /h 317.1
Air flow (min. speed)	m <sup>3</sup> /h 275
Air flow (max. speed)	m <sup>3</sup> /h 355
Air flow (intensive or boost setting)	m <sup>3</sup> /h 545
Max. air flow (Q <sub>max</sub> )	m <sup>3</sup> /h 545.0
Air pressure at best efficiency point	Pa 313
Airborne acoustical A-weighted sound power emissions (min. speed)	dB 57
Airborne acoustical A-weighted sound power emissions (max. speed)	dB 64
Airborne acoustical A-weighted sound power emissions (intensive or boost setting)	dB 74
Electrical power input at best efficiency point	W 169.0
Nominal power of lighting system	W 6.0
Average illumination of the lighting system on the cooking surface	lx 330
Time increase factor	1.4