

PW 6080

18 lbs. / 8 kg



Electric Heating




FEATURES

- Profitronic L Vario select controls with shortcut buttons
- Pre-configured program packages for a very broad range of applications
- Patented Honeycomb drum
- Precise automatic load recognition: water and energy consumption are automatically adjusted for the load size
- Imbalance monitoring
- Designed for 30,000 operating hours
- Safe disinfection



Honeycomb Drum

The sculpted structure of the Miele Honeycomb drum allows garments to glide gently on a thin film of water.



Safe Disinfection

Disinfection programs ensure reliable levels of hygiene.



Customized User Guidance

Flexible solutions to suit a wide range of professional laundry care needs.



WetCare

Water instead of chemicals: Delicate textiles are cleaned perfectly using the wet cleaning process.

Mat. No.	Model	Heat Type	Electrical	Finish
9292310	PW 6080 Drain Pump	Electric Washer	2 AC 220-240 V, 60 Hz, 30A	Octoblue
9292330	PW 6080 Drain Valve	Electric Washer	2 AC 220-240 V, 60 Hz, 30A	Octoblue

PW 6080

18 lbs. / 8 kg

Model	PW 6080
Heated Option (EL)	Electric
Finish	Octoblue
Load Size	18 lbs. (8 kg)
Drum Capacity	2.83 cu.ft. / 80 liter
Tested for	30,000 Operating Hours
G-Force	520
Cold Water Connection	1 x cold water ½ in. hose with ¾ in. threaded union
Hot Water Connection	1 x hot water ½ in. hose with ¾ in. threaded union
Min. water flow pressure	14.5 psi
Max. water flow	145 psi
Max. throughput	2.9 gal./min.
Length of connection hose (supplied)	61 in. (1,550 mm)
Drain Valve	7/8 in. DN 22
Width	27 ^{9/16} in. (700 mm)
Depth	27 ^{5/8} in. (702 mm)
Height	40 ^{3/16} in. (1,020 mm)
Height to the bottom of the door	12 ^{13/16} in. (325 mm)
Door opening diameter	14 ^{9/16} in. (370 mm)
Door hinging	Right
Net Weight	309 lbs. (140 kg)
Shipping Width	29 ^{15/16} in. (760 mm)
Shipping Depth	32 ^{1/4} in. (820 mm)
Shipping Height	47 ^{13/16} in. (1,215 mm)
Shipping Weight	327 lbs. (148 kg)
Plug type	NEMA L6-30
Standard electrical connection	2 AC 208 / 220-240 V, 60 Hz
Possible voltage variant 1	2 AC 208 V 60 Hz
Heating Power	4.00 kW
Fuse	2 x 30 A