Maximum temperature inside the treated textile ^(a) (°C)	9.0 51.8 1.036		Miele Carl-Miele-Straße 29, 33332 Güter WER865 WPS PWash&TDos&9kg Parameter Dimensions in cm Energy efficiency class ^(a) Rinsing effectiveness (g/kg) ^(a) Water consumption in litre per cycle, based on the eco 40-60 programme at a combination		85 60 64	
Model identifier General product parameters Parameter Rated capacity ^(a) (kg) Energy efficiency index EEI _w ^(a) Washing efficiency index ^(a) Energy consumption in kWh per cycle, based on the eco 40-60 programme at a combination of full and partial loads. Actual energy consumption will depend on how the appliance is used. Maximum temperature inside the treated textile ^(a) (°C)	9.0 51.8 1.036		Parameter Dimensions in cm Energy efficiency class ^(a) Rinsing effectiveness (g/kg) ^(a) Water consumption in litre per cycle, based on the eco 40-60	Value Height Width Depth A	60	
General product parameters Parameter Rated capacity ^(a) (kg) Energy efficiency index EEI _w ^(a) Washing efficiency index ^(a) Energy consumption in kWh per cycle, based on the eco 40-60 programme at a combination of full and partial loads. Actual energy consumption will depend on how the appliance is used. Maximum temperature inside the treated textile ^(a) (°C)	9.0 51.8 1.036		Parameter Dimensions in cm Energy efficiency class ^(a) Rinsing effectiveness (g/kg) ^(a) Water consumption in litre per cycle, based on the eco 40-60	Value Height Width Depth A	60	
Parameter Rated capacity ^(a) (kg) Energy efficiency index EEI _w ^(a) Washing efficiency index ^(a) Energy consumption in kWh per cycle, based on the eco 40-60 programme at a combination of full and partial loads. Actual energy consumption will depend on how the appliance is used. Maximum temperature inside the treated textile ^(a) (°C)	9.0 51.8 1.036		Dimensions in cm Energy efficiency class ^(a) Rinsing effectiveness (g/kg) ^(a) Water consumption in litre per cycle, based on the eco 40-60	Height Width Depth	60	
Rated capacity ^(a) (kg) Energy efficiency index EEI _w ^(a) Washing efficiency index ^(a) Energy consumption in kWh per cycle, based on the eco 40-60 programme at a combination of full and partial loads. Actual energy consumption will depend on how the appliance is used. Maximum temperature inside the treated textile ^(a) (°C)	9.0 51.8 1.036		Dimensions in cm Energy efficiency class ^(a) Rinsing effectiveness (g/kg) ^(a) Water consumption in litre per cycle, based on the eco 40-60	Height Width Depth	60	
Energy efficiency index EEI _w (a) Washing efficiency index ^(a) Energy consumption in kWh per cycle, based on the eco 40-60 programme at a combination of full and partial loads. Actual energy consumption will depend on how the appliance is used. Maximum temperature inside the treated textile(a) (°C)	51.8 1.036		Energy efficiency class ^(a) Rinsing effectiveness (g/kg) ^(a) Water consumption in litre per cycle, based on the eco 40-60	Width Depth A	60	
Energy efficiency index EEI _w (a) Washing efficiency index ^(a) Energy consumption in kWh per cycle, based on the eco 40-60 programme at a combination of full and partial loads. Actual energy consumption will depend on how the appliance is used. Maximum temperature inside the treated textile(a) (°C)	51.8 1.036		Energy efficiency class ^(a) Rinsing effectiveness (g/kg) ^(a) Water consumption in litre per cycle, based on the eco 40-60	Depth A		
Washing efficiency index ^(a) Energy consumption in kWh per cycle, based on the eco 40-60 programme at a combination of full and partial loads. Actual energy consumption will depend on how the appliance is used. Maximum temperature inside the treated textile ^(a) (°C)	1.036		Rinsing effectiveness (g/kg) ^(a) Water consumption in litre per cycle, based on the eco 40-60	A	64	
Washing efficiency index ^(a) Energy consumption in kWh per cycle, based on the eco 40-60 programme at a combination of full and partial loads. Actual energy consumption will depend on how the appliance is used. Maximum temperature inside the treated textile ^(a) (°C)	1.036		Rinsing effectiveness (g/kg) ^(a) Water consumption in litre per cycle, based on the eco 40-60			
Energy consumption in kWh per cycle, based on the eco 40-60 programme at a combination of full and partial loads. Actual energy consumption will depend on how the appliance is used. Maximum temperature inside the treated textile(a) (°C)			Water consumption in litre per cycle, based on the eco 40-60	4.0		
kWh per cycle, based on the eco 40-60 programme at a combination of full and partial loads. Actual energy consumption will depend on how the appliance is used. Maximum temperature inside the treated textile(a) (°C)	0.493		cycle, based on the eco 40-60		4.0	
Maximum temperature inside the treated textile ^(a) (°C)			of full and partial loads. Actual water consumption will depend on how the appliance is used and on the hardness of the water.	48		
the treated textile ^(a) (°C)	Rated capacity	city 42		44.1 %		
F	Half 31		Weighted remaining moisture content ^(a) (%)			
<u> </u>	Quarter	25	Contone (70)			
Spin speed ^(a) (rpm)	Rated capacity	1600	Spin-drying efficiency class ^(a)			
	Half	1600		Α		
	Quarter	1600				
R	Rated capacity	3:19				
Programme duration ^(a) (h:min)	Half	2:39	Design type	Free-standing		
	Quarter	2:29				
Airborne acoustical noise emission class ^(a) (spinning phase)	68		Airborne acoustical noise emission class ^(a) (spinning phase)	А		
Off-mode (W) (if applicable)	0.30		Standby mode (W) (if applicable)	-		
Delay start (W) (if applicable)	2.40		Networked standby (W) (if applicable)	0.70		
Minimum duration of the guarante	ee offered by the	supplier	24 months			
This product has been designed to the washing cycle	release silver io	ns during	no			
Additional information						
Weblink to the supplier's website, w 9 of Annex II to Commission Regula found		•	https://www.miele.com/			