



Printing date 08.11.2023 Version number 1 Revision: 08.11.2023

# SECTION 1: Identification of the substance/mixture and of the company/undertaking

- · 1.1 Product identifier
- · Trade name: ProCare Tex 11 COL
- · UFI: W9P0-P0XF-W00F-VXVT
- · 1.2 Relevant identified uses of the substance or mixture and uses advised against

No further relevant information available.

- · Application of the substance / the mixture Detergents
- · 1.3 Details of the supplier of the safety data sheet
- · Manufacturer/Supplier:
- · Manufacturer

Chemische Fabrik Kreussler & Co. GmbH

Postfach 120454

D-65082 Wiesbaden

· Supplier

Miele & Cie. KG

Carl-Miele-Str. 29

33332 Gütersloh

Germany

Telefon-Nr. +49 5241 89 0

Fax-Nr. +49 5241 89 2090

Web: www.miele-professional.com

· Further information obtainable from:

Department T-PS

+49 (0) 611 9271-0

msds-tc@kreussler.com

· 1.4 Emergency telephone number:

Members of the public seeking specific information on poisons should contact:

In England and Wales: NHS 111 - dial 111

In Scotland: NHS 24 - dial 111

### **SECTION 2: Hazards identification**

- · 2.1 Classification of the substance or mixture
- · Classification according to Regulation (EC) No 1272/2008

Skin Irrit. 2 H315 Causes skin irritation.

Eye Dam. 1 H318 Causes serious eye damage.

- · 2.2 Label elements
- · Labelling according to Regulation (EC) No 1272/2008

The product is classified and labelled according to the GB CLP regulation.

Hazard pictograms



GHS05

- · Signal word Danger
- · Hazard-determining components of labelling:

disodium disilicate

Disodium Metasilicate

· Hazard statements

H315 Causes skin irritation.





Printing date 08.11.2023 Version number 1 Revision: 08.11.2023

Trade name: ProCare Tex 11 COL

(Contd. of page 1)

H318 Causes serious eye damage.

#### Precautionary statements

P280 Wear protective gloves / eye protection. P302+P352 IF ON SKIN: Wash with plenty of water.

P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if

present and easy to do. Continue rinsing.

P332+P313 If skin irritation occurs: Get medical advice/attention. P337+P313 If eye irritation persists: Get medical advice/attention.

P402 Store in a dry place.

#### · 2.3 Other hazards

The product does not contain any organic halogen compounds (AOX), nitrates, heavy metal compounds or formaldehydes.

- Results of PBT and vPvB assessment
- · PBT: Not applicable.
- · vPvB: Not applicable.

### **SECTION 3: Composition/information on ingredients**

- · 3.2 Mixtures
- · Description: Mixture of substances listed below with nonhazardous additions.

· Dangerous componer	nts:	
CAS: 497-19-8 EINECS: 207-838-8	sodium carbonate Eye Irrit. 2, H319	30-50%
CAS: 13870-28-5 EINECS: 237-623-4	disodium disilicate  Eye Dam. 1, H318  Specific concentration limits: Eye Dam. 1; H318: C ≥ 10 %  Eye Irrit. 2; H319: 1 % ≤ C < 10 %	30-50%
CAS: 157627-86-6 NLP: 500-337-8	Alcohols C13-C15 branched and linear,ethoxylated  Eye Dam. 1, H318; Acute Tox. 4, H302; Aquatic Chronic 3, H412  Specific concentration limits: Eye Dam. 1; H318: C ≥ 10 %  Eye Irrit. 2; H319: 10 % ≤ C < 10 %	5-15%
CAS: 10213-79-3 EINECS: 229-912-9	Disodium Metasilicate Met. Corr.1, H290; Skin Corr. 1B, H314; Eye Dam. 1, H318; STOT SE 3, H335	1-5%
CAS: 120313-48-6 EC number: 639-733-1	alcohols C12 – C15 ethoxylated, propoxylated Skin Irrit. 2, H315; Eye Irrit. 2, H319	1-5%

Ingredients according to detergent regulation EC 648/2004	
non-ionic surfactants	≥5 - <15%
phosphonates, perfumes, enzymes	<5%

· Additional information: For the wording of the listed hazard phrases refer to section 16.

### **SECTION 4: First aid measures**

- 4.1 Description of first aid measures
- General information: Immediately remove any clothing soiled by the product.
- · After inhalation: In case of unconsciousness place patient stably in side position for transportation.
- · After skin contact:

Rinse with warm water.

If skin irritation continues, consult a doctor.

Immediately wash with water and soap and rinse thoroughly.

- After eye contact: Rinse opened eye for several minutes under running water. Then consult a doctor.
- · After swallowing: If symptoms persist consult doctor.





Printing date 08.11.2023 Version number 1 Revision: 08.11.2023

Trade name: ProCare Tex 11 COL

(Contd. of page 2)

· 4.2 Most important symptoms and effects, both acute and delayed

No further relevant information available.

- · Hazards Danger of gastric perforation.
- 4.3 Indication of any immediate medical attention and special treatment needed

No further relevant information available.

### **SECTION 5: Firefighting measures**

- · 5.1 Extinguishing media
- · Suitable extinguishing agents: Use fire extinguishing methods suitable to surrounding conditions.
- · 5.2 Special hazards arising from the substance or mixture

In case of fire, the following can be released:

Carbon monoxide (CO)

- 5.3 Advice for firefighters
- · Protective equipment: Use normal protective clothing.
- · Additional information

Dispose of fire debris and contaminated fire fighting water in accordance with official regulations.

### **SECTION 6: Accidental release measures**

· 6.1 Personal precautions, protective equipment and emergency procedures

Avoid formation of dust.

Wear protective equipment. Keep unprotected persons away.

- 6.2 Environmental precautions: Do not allow to enter sewers/ surface or ground water.
- 6.3 Methods and material for containment and cleaning up: Pick up mechanically.
- · 6.4 Reference to other sections

No dangerous substances are released.

See Section 7 for information on safe handling.

See Section 8 for information on personal protection equipment.

See Section 13 for disposal information.

### **SECTION 7: Handling and storage**

- · 7.1 Precautions for safe handling Prevent formation of dust.
- · Information about fire and explosion protection: No special measures required.
- · 7.2 Conditions for safe storage, including any incompatibilities
- · Storage:
- · Requirements to be met by storerooms and receptacles:

Do not use light alloy receptacles.

Unsuitable material for receptacle: glass or ceramic.

Unsuitable material for receptacle: aluminium.

Suitable material for receptacles and pipes: Stainless steel.

- Information about storage in one common storage facility: Not required.
- · Further information about storage conditions: None.
- · Storage class: 13
- · 7.3 Specific end use(s) No further relevant information available.

(Contd. on page 4)





Printing date 08.11.2023 Version number 1 Revision: 08.11.2023

Trade name: ProCare Tex 11 COL

(Contd. of page 3)

### **SECTION 8: Exposure controls/personal protection**

- · 8.1 Control parameters
- · Ingredients with limit values that require monitoring at the workplace:

The product does not contain any relevant quantities of materials with critical values that have to be monitored at the workplace.

· DNELs		
13870-28-	5 disodium disilicate	
Oral	long term/systemic effects	1.59 mg/kg (general public)
Dermal	long term/systemic effects	159 mg/kg/Day (general public)
		318 mg/kg/Day (Workers)
Inhalative	long term/systemic effects	2.39 mg/m³ (general public)
		11.12 mg/m³ (Workers)
10213-79-	3 Disodium Metasilicate	
Oral	long term/systemic effects	0.74 mg/kg (Consumers)
Dermal	long term/systemic effects	0.74 mg/kg/Day (Consumers)
		1.49 mg/kg/Day (Workers)
Inhalative	long term/systemic effects	1.55 mg/m³ (Consumers)
		6.22 mg/m³ (Workers)
· PNECs		
13870-28-	5 disodium disilicate	
Aqua	7.5 mg/l (Marine water)	
	7.5 mg/l (freshwater)	
Sediment	29.4 mg/kg (Marine water)	
	29.4 mg/kg (freshwater)	
10213-79-	3 Disodium Metasilicate	
Aqua	1,000 mg/l (Sewage treatm	ent plant)
	1 mg/l (Marine water)	
	7.5 mg/l (Freshwater)	
	7.5 mg/l (intermittent release	se)

- Additional information: The lists valid during the making were used as basis.
- · 8.2 Exposure controls
- · Appropriate engineering controls No further data; see section 7.
- Individual protection measures, such as personal protective equipment
- General protective and hygienic measures:

Do not eat, drink, smoke or sniff while working.

Keep away from foodstuffs, beverages and food.

Immediately remove all soiled and contaminated clothing

Wash hands before breaks and at the end of work.

Avoid contact with the skin.

Avoid contact with the eyes and skin.

Respiratory protection:

In case of brief exposure or low pollution use respiratory filter device. In case of intensive or longer exposure use self-contained respiratory protective device.

(Contd. on page 5)





Printing date 08.11.2023 Version number 1 Revision: 08.11.2023

Trade name: ProCare Tex 11 COL

(Contd. of page 4)

#### · Hand protection



Protective gloves

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation.

Due to missing tests no recommendation to the glove material can be given for the product/ the preparation/ the chemical mixture.

Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation

### Material of gloves

PVC or PE gloves

Recommended thickness of the material: ≥ 0.4 mm

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.

#### · Penetration time of glove material

The exact break trough time has to be found out by the manufacturer of the protective gloves and has to be observed.

### · Not suitable are gloves made of the following materials:

Leather gloves

Strong material gloves

· Eye/face protection



Tightly sealed goggles

· Body protection: Protective work clothing

#### **SECTION 9: Physical and chemical properties**

· 9.1 Information on basic physical and chemical properties

· General Information

· Physical state Solid

Colour: White-blue powder
 Odour: Characteristic
 Odour threshold: Not determined.
 Melting point/freezing point: Undetermined.

· Boiling point or initial boiling point and boiling

range Undetermined. • Flammability Not determined.

· Lower and upper explosion limit

Lower: Not determined.
Upper: Not determined.
Flash point: Not applicable.
Decomposition temperature: Not determined.

• pH at 20 °C 11 (1%)

· Viscosity:

Kinematic viscosityDynamic:Not applicable.Not applicable.

(Contd. on page 6)





Printing date 08.11.2023 Version number 1 Revision: 08.11.2023

Trade name: ProCare Tex 11 COL

(Contd. of page 5)

	(Contd. of page 5)
· Solubility	
water:	Soluble.
· Partition coefficient n-octanol/water (log value)	Not determined.
· Vapour pressure:	Not applicable.
Density and/or relative density	• •
Density:	Not determined.
Relative density	Not determined.
· Bulk density:	830 kg/m³
· Vapour density	Not applicable.
· 9.2 Other information	
· Appearance:	
· Form:	Powder
Important information on protection of health	1
and environment, and on safety.	
Ignition temperature:	Product is not selfigniting.
Explosive properties:	Product does not present an explosion hazard.
Solvent content:	
· Organic solvents:	0.0 %
· Change in condition	
· Evaporation rate	Not applicable.
Information with regard to physical hazard	j
classes	
· Explosives	Void
· Flammable gases	Void
· Aerosols	Void
· Oxidising gases	Void
· Gases under pressure	Void
Flammable liquids	Void
Flammable solids	Void
Self-reactive substances and mixtures	Void
Pyrophoric liquids	Void
Pyrophoric solids	Void
Self-heating substances and mixtures	Void
Substances and mixtures, which emit flammable	
gases in contact with water	Void
Oxidising liquids	Void

Void

Void

Void

Void

## **SECTION 10: Stability and reactivity**

- 10.1 Reactivity No further relevant information available.
- · 10.2 Chemical stability

· Oxidising solids

Organic peroxides

· Corrosive to metals

· Desensitised explosives

· Thermal decomposition / conditions to be avoided:

No decomposition if used according to specifications.

No decomposition if used and stored according to specifications.

10.3 Possibility of hazardous reactions

Reacts with water and acids.

Reacts with light alloys in the presence of moisture to form hydrogen.

(Contd. on page 7)





Printing date 08.11.2023 Version number 1 Revision: 08.11.2023

Trade name: ProCare Tex 11 COL

(Contd. of page 6)

- 10.4 Conditions to avoid No further relevant information available.
- · 10.5 Incompatible materials: aluminum
- 10.6 Hazardous decomposition products: Hydrogen

## **SECTION 11: Toxicological information**

- · 11.1 Information on hazard classes as defined in Regulation (EC) No 1272/2008
- · Acute toxicity Based on available data, the classification criteria are not met.

· LD/LC50 v	/alues rele	vant for classification:	
ATE (Acut	te Toxicity	Estimates)	
Oral	LD-50	20,536 mg/kg (rat)	
497-19-8 s	sodium car	bonate	
Oral	LD-50	2,800 mg/kg (rat)	
Dermal	LD-50	>2,000 mg/kg (rabbit) (EPA 16 CFR 1500.40 (Studienreport 1978))	
Inhalative	LC-50/2 h	2,300 mg/m³ (rat)	
13870-28-	13870-28-5 disodium disilicate		
Oral	LD-50	2,507 mg/kg (rat) (OECD 401)	
Inhalative	LC-50/4 h	>3,510 mg/l (rat)	
157627-86	157627-86-6 Alcohols C13-C15 branched and linear,ethoxylated		
Oral	LD-50	1,150 mg/kg (rat)	
10213-79-	10213-79-3 Disodium Metasilicate		
Oral	LD-50	1,152-1,349 mg/kg (rat)	
120313-48	120313-48-6 alcohols C12 – C15 ethoxylated, propoxylated		
Oral	LD-50	>2,000 mg/kg (rat)	

- Skin corrosion/irritation Causes skin irritation.
- · Serious eye damage/irritation Causes serious eye damage.
- 11.2 Information on other hazards

· Endocrir	ne disrupting properties	
128-37-0	Butylated hydroxytoluene	List II

## **SECTION 12: Ecological information**

· 12.1 Toxicity

· Aquatic toxi	city:	
497-19-8 soc	497-19-8 sodium carbonate	
EC-50 48h	200-227 mg/l (Ceriodaphnia sp.) (Mobilität)	
	256 mg/l (Daphnia magna)	
LC-50 96h	300 mg/l (Blauer Sonnenbarsch)	
	740 mg/l (gam)	
	300 mg/l (Lepomis macrochirus) (Wirkungsgrundlage: Sterblichkeit)	
13870-28-5 c	lisodium disilicate	
LC-50 48 h	491 mg/L (Daphnia magna)	
EC-50 3 h	720 mg/l (Belebtschlamm)	
EC-50 48h	491 mg/l (Daphnia magna) (OECD 202)	
LC-50 96h	>500 mg/l (Brachydanio rerio)	

(Contd. on page 8)





Printing date 08.11.2023 Version number 1 Revision: 08.11.2023

Trade name: ProCare Tex 11 COL

	(Contd. of page 7)
NOEC (72 h)	18 mg/l (Scenedesmus subspicatus)
157627-86-6	Alcohols C13-C15 branched and linear,ethoxylated
EC-10	>1,000 mg/L (Belebtschlamm)
EC-50 48h	1-10 mg/l (Daphnia magna) (Literaturangabe)
EC-50 72h	1-10 mg/l (Scenedesmus subspicatus) (Literaturangabe)
LC-50 96h	1-10 mg/l (Brachydanio rerio)
10213-79-3 D	isodium Metasilicate
EC-50 48h	1,700 mg/l (Daphnia magna)
120313-48-6	alcohols C12 – C15 ethoxylated, propoxylated
EC-50 48h	>1-10 mg/l (Daphnia magna)
LC-50 96h	1-10 mg/l (Leuciscus idus)

- · 12.2 Persistence and degradability No further relevant information available.
- Other information: The product is biodegradable.
- 12.3 Bioaccumulative potential No further relevant information available.
- 12.4 Mobility in soil No further relevant information available.
- 12.5 Results of PBT and vPvB assessment
- · PBT: Not applicable.
- vPvB: Not applicable.
- 12.6 Endocrine disrupting properties For information on endocrine disrupting properties see section 11.
- · 12.7 Other adverse effects
- · Additional ecological information:
- · General notes:

The surfactant(s) contained in this preparation complies(comply) with the biodegradability criteria as laid down in Regulation (EC) No.648/2004 on detergents. Data to support this assertion are held at the disposal of the competent authorities of the Member States and will be made available to them, at their direct request or at the request of a detergent manufacturer.

Do not allow product to reach ground water, water course or sewage system.

The product may not be released into the environment without control.

### **SECTION 13: Disposal considerations**

- · 13.1 Waste treatment methods
- · Recommendation Dispose of in accordance with Local, State, and Federal Regulations.
- Uncleaned packaging:
- Recommendation: Disposal must be made according to official regulations.
- · Recommended cleansing agents: Water, if necessary together with cleansing agents.

SECTION 14: Transport information	on	
· 14.1 UN number or ID number · ADR, ADN, IMDG, IATA	Void	
· 14.2 UN proper shipping name · ADR, ADN, IMDG, IATA	Void	
· 14.3 Transport hazard class(es)		
· ADR, ADN, IMDG, IATA · Class	Void	

(Contd. on page 9)





Printing date 08.11.2023 Version number 1 Revision: 08.11.2023

Trade name: ProCare Tex 11 COL

(Contd. of page 8)

Void	
Volu	
No	
Not applicable.	
to IMO	
Not applicable.	
Void	
- -	Not applicable.  To IMO  Not applicable.

### **SECTION 15: Regulatory information**

- · 15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture
- **Poisons Act**
- · Regulated explosives precursors

None of the ingredients is listed.

- Regulated poisons
- None of the ingredients is listed.
- · Reportable explosives precursors

None of the ingredients is listed.

· Reportable poisons

None of the ingredients is listed.

- · Directive 2012/18/EU
- · Named dangerous substances ANNEX I None of the ingredients is listed.
- · 15.2 Chemical safety assessment: A Chemical Safety Assessment has not been carried out.

#### **SECTION 16: Other information**

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

The information of Items 4 through 8 and 10 through 12 partially refers not to the use and the proper application of the product (see Directions for Use/Product Information) but to the release of larger quantities in the case of accidents and irregularities.

The information exclusively describes the safety requirements of the product(s) and is based on the present state of our experience.

Non-ionic tensides can have varying characteristics and classifications despite same CAS-No.

#### Relevant phrases

- H290 May be corrosive to metals.
- H302 Harmful if swallowed.
- H314 Causes severe skin burns and eye damage.
- H315 Causes skin irritation.
- H318 Causes serious eye damage.
- H319 Causes serious eye irritation.
- H335 May cause respiratory irritation.
- H412 Harmful to aquatic life with long lasting effects.

#### Department issuing SDS:

Department T-PS

Herr Heiko Schmidt

+49 (0) 611/9271-0





Printing date 08.11.2023 Version number 1 Revision: 08.11.2023

Trade name: ProCare Tex 11 COL

(Contd. of page 9)

· Contact: Herr Heiko Schmidt

#### · Abbreviations and acronyms:

ADR: Accord relatif au transport international des marchandises dangereuses par route (European Agreement Concerning the International Carriage of Dangerous Goods by Road)

IMDG: International Maritime Code for Dangerous Goods

IATA: International Air Transport Association

GHS: Globally Harmonised System of Classification and Labelling of Chemicals EINECS: European Inventory of Existing Commercial Chemical Substances

ELINCS: European List of Notified Chemical Substances

CAS: Chemical Abstracts Service (division of the American Chemical Society)

DNEL: Derived No-Effect Level (UK REACH)

PNEC: Predicted No-Effect Concentration (ÚK REACH)

LC50: Lethal concentration, 50 percent

LD50: Lethal dose, 50 percent

PBT: Persistent, Bioaccumulative and Toxic vPvB: very Persistent and very Bioaccumulative Met. Corr.1: Corrosive to metals – Category 1 Acute Tox. 4: Acute toxicity – Category 4

Skin Corr. 1B: Skin corrosion/irritation – Category 1B Skin Irrit. 2: Skin corrosion/irritation – Category 2

Eye Dam. 1: Serious eye damage/eye irritation – Category 1
Eye Irrit. 2: Serious eye damage/eye irritation – Category 2

STOT SE 3: Specific target organ toxicity (single exposure) – Category 3

Aquatic Chronic 3: Hazardous to the aquatic environment - long-term aquatic hazard - Category 3

\* Data compared to the previous version altered.

GB —