

Data sheet for household cooker hoods

In acc. with delegated regulation (EU) No. 65/2014 and regulation (EU) No. 66/2014

Miele			
Model name / identifier		DA 2698 EXT	
Annual Energy Consumption (AEC) (AEC _{Haube})	kWh/year	8,8	
Energy efficiency class		A+	
Energy efficiency index (EEI) (EEI _{Haube})		40,0	
Fluid Dynamic Efficiency (FDE) (FDE _{Haube})			
Fluid Dynamic Efficiency class			
A (most efficient) to G (least efficient)		-	
Lighting Efficiency (LE) (LE _{Haube})	lx/W	54,2	
Lighting Efficiency class			
A (most efficient) to G (least efficient)		A	
Grease Filtering Efficiency	%		
Grease Filtering Efficiency class			
A (most efficient) to G (least efficient)		-	
Airflow at best efficiency point	m ³ /h		
Air flow (min. speed)	m ³ /h		
Air flow (max. speed)	m ³ /h		
Air flow (intensive or boost setting)	m ³ /h		
Max. air flow (Q) (Q _{max})	m ³ /h		
Air pressure at best efficiency point	Pa		
Airborne acoustical A-weighted sound power emissions (min. speed)	dB		
Airborne acoustical A-weighted sound power emissions (max. speed)	dB	0	
Airborne acoustical A-weighted sound power emissions (intensive or boost setting)	dB		
Electrical power input at best efficiency point	W		
Power consumption in off mode (P _o)	W		
Power consumption in standby mode (P _s)	W	0,35	
Nominal power of lighting system	W	12,0	
Average illumination of the lighting system on the cooking surface	lx	650	
Time increase factor			