Data sheet for household cooker hoods
In acc. with delegated regulation (EU) No. 65/2014 and regulation (EU) No. 66/2014

Miele				
Model name / identifier		DA 2628		
Annual Energy Consumption (AEC)				
(AEC <sub>rpm</sub> )	kWh/year	26,8		
Energy efficiency class		A+		
Energy efficiency index (EEI) (EEI <sub>mm</sub> )		37,7		
Fluid Dynamic Efficiency (FDE) (FDE <sub>rom</sub> )		40,9		
Fluid Dynamic Efficiency class		, .		
A (most efficient) to G (least efficient)		Α		
Lighting Efficiency (LE) (LE <sub>rom</sub> )	lx/W	51,9		
Lighting Efficiency class				
A (most efficient) to G (least efficient)		Α		
Grease Filtering Efficiency	%	95,2		
Grease Filtering Efficiency class				
A (most efficient) to G (least efficient)		Α		
Airflow at best efficiency point	m³/h	340,4		
Air flow (min. speed)	m³/h	200		
Air flow (max. speed)	m³/h	400		
Air flow (intensive or boost setting)	m³/h	640		
Max. air flow (Q) (Q <sub>max</sub> )	m³/h	640		
Air pressure at best efficiency point	Pa	380		
Airborne acoustical A-weighted sound power emission	ons			
(min. speed)	dB	36		
Airborne acoustical A-weighted sound power emission				
(max. speed)	dB	51		
Airborne acoustical A-weighted sound power emission		20		
(intensive or boost setting)	dB	62		
Electrical power input at best efficiency point	W	88,0		
Power consumption in off mode (P <sub>o</sub> )	W	0.05		
Power consumption in standby mode (P <sub>s</sub> )	W W	0,35		
Nominal power of lighting system		13,5		
Average illumination of the lighting system on the co surface	oking Ix	700		
Time increase factor	IX	0,5		