

Data sheet for household cooker hoods

In acc. with delegated regulation (EU) No. 65/2014 and regulation (EU) No. 66/2014

Miele			
Model name / identifier		DAR 1235	
Annual Energy Consumption (AEC) (AEC _{rpm})	kWh/year		68,4
Energy efficiency class			B
Energy efficiency index (EEI) (EEI _{rpm})			65,3
Fluid Dynamic Efficiency (FDE) (FDE _{rpm})			24,9
Fluid Dynamic Efficiency class			
A (most efficient) to G (least efficient)			B
Lighting Efficiency (LE) (LE _{rpm})	lx/W		75,0
Lighting Efficiency class			
A (most efficient) to G (least efficient)			A
Grease Filtering Efficiency	%		80,9
Grease Filtering Efficiency class			
A (most efficient) to G (least efficient)			C
Airflow at best efficiency point	m ³ /h		394,8
Air flow (min. speed)	m ³ /h		200
Air flow (max. speed)	m ³ /h		400
Air flow (intensive or boost setting)	m ³ /h		650
Max. air flow (Q) (Q _{max})	m ³ /h		650
Air pressure at best efficiency point	Pa		349
Airborne acoustical A-weighted sound power emissions (min. speed)	dB		39
Airborne acoustical A-weighted sound power emissions (max. speed)	dB		54
Airborne acoustical A-weighted sound power emissions (intensive or boost setting)	dB		67
Electrical power input at best efficiency point	W		153,7
Power consumption in off mode (P _o)	W		0,00
Power consumption in standby mode (P _s)	W		
Nominal power of lighting system	W		9,0
Average illumination of the lighting system on the cooking surface	lx		675
Time increase factor			1,1