## Data sheet for household cooker hoods In acc. with delegated regulation (EU) No. 65/2014 and regulation (EU) No. 66/2014

Miele				
Model name/identifier		DA 6698 D Purist. Ed.6000		
Annual Energy Consumption (AEC)				
(AEC <sub>rpm</sub> )	kWh/year	32,1		
Energy efficiency class		A++		
Energy efficiency index (EEI) (EEI <sub>rpm</sub> )		36,8		
Fluid Dynamic Efficiency (FDE) (FDE <sub>rpm</sub> )		40,6		
Fluid Dynamic Efficiency class				
A (most efficient) to G (least efficient)		А		
Lighting Efficiency (LE) (LE <sub>rpm</sub> )	lx/W	68,3		
Lighting Efficiency class				
A (most efficient) to G (least efficient)		Α		
Grease Filtering Efficiency	%	95,1		
Grease Filtering Efficiency class				
A (most efficient) to G (least efficient)		A		
Airflow at best efficiency point	m³/h	474,0		
Air flow (min. speed)	m³/h	200		
Air flow (max. speed)	m³/h	450		
Air flow (intensive or boost setting)	m³/h	730		
Max. air flow (Q) (Q <sub>max</sub> )	m³/h	730		
Air pressure at best efficiency point	Pa	367		
Airborne acoustical A-weighted sound power emit	ssions			
(min. speed)	dB	35		
Airborne acoustical A-weighted sound power emi				
(max. speed)	dB	53		
Airborne acoustical A-weighted sound power emit				
(intensive or boost setting)	dB	65		
Electrical power input at best efficiency point	W	119,0		
Power consumption in off mode (P <sub>o</sub> )	W			
Power consumption in standby mode (P <sub>s</sub> )	W	0,35		
Nominal power of lighting system	W	12,0		
Average illumination of the lighting system on the		000		
surface Time increase factor	lx	820		
I Ime increase factor		0,5		