


E 352 Injector nozzle For the optimum cleaning of the wash items.





- Suitable for use in a mobile injector unit
- Can be combined with clip E 354
- Ø 6 x 220 mm, screw connection

Product category	
Glassware Washers, laboratory	•
Large-capacity washer-disinfectors, laboratory	•
Machine affiliation	
G 7825	•
PG 8527	•
PG 8535	•
PG 8536	•
PG 8504	•
PG 8583	•
PG 8583 CD	•
PG 8593	•
Product category	
Injector nozzle	•
Product characteristics	
Material	Stainless steel
Colour	Stainless Steel
Application area	
Application area Reprocessing of laboratory glassware	•
	•
Reprocessing of laboratory glassware	0
Reprocessing of laboratory glassware Standard electrical connection	0 0
Reprocessing of laboratory glassware  Standard electrical connection  Number of phases	
Reprocessing of laboratory glassware  Standard electrical connection  Number of phases  Voltage in V	0
Reprocessing of laboratory glassware  Standard electrical connection  Number of phases  Voltage in V  Frequency in Hz	0 0
Reprocessing of laboratory glassware  Standard electrical connection  Number of phases  Voltage in V  Frequency in Hz  Total rated load in kW	0 0 0.00
Reprocessing of laboratory glassware  Standard electrical connection  Number of phases  Voltage in V  Frequency in Hz  Total rated load in kW  Fuse rating in A	0 0 0.00
Reprocessing of laboratory glassware  Standard electrical connection  Number of phases  Voltage in V  Frequency in Hz  Total rated load in kW  Fuse rating in A  Dimensions and weight	0 0 0.00 0
Reprocessing of laboratory glassware  Standard electrical connection  Number of phases  Voltage in V  Frequency in Hz  Total rated load in kW  Fuse rating in A  Dimensions and weight  External dimensions, net height in mm	0 0 0.00 0 8 11/16 (220) in (mm)
Reprocessing of laboratory glassware  Standard electrical connection  Number of phases  Voltage in V  Frequency in Hz  Total rated load in kW  Fuse rating in A  Dimensions and weight  External dimensions, net height in mm  External dimensions, net width in mm	0 0 0.00 0 8 11/16 (220) in (mm) 0 7/16 (10) in (mm)
Reprocessing of laboratory glassware  Standard electrical connection  Number of phases  Voltage in V  Frequency in Hz  Total rated load in kW  Fuse rating in A  Dimensions and weight  External dimensions, net height in mm  External dimensions, net width in mm  External dimensions, net depth in mm	0 0 0.00 0 8 11/16 (220) in (mm) 0 7/16 (10) in (mm) 0 7/16 (10) in (mm)
Reprocessing of laboratory glassware  Standard electrical connection  Number of phases  Voltage in V  Frequency in Hz  Total rated load in kW  Fuse rating in A  Dimensions and weight  External dimensions, net height in mm  External dimensions, net depth in mm  External dimensions, gross height in mm	0 0 0.00 0 8 11/16 (220) in (mm) 0 7/16 (10) in (mm) 0 7/16 (10) in (mm) 9 1/16 (230)
Reprocessing of laboratory glassware  Standard electrical connection  Number of phases  Voltage in V  Frequency in Hz  Total rated load in kW  Fuse rating in A  Dimensions and weight  External dimensions, net height in mm  External dimensions, net depth in mm  External dimensions, gross height in mm  External dimensions, gross height in mm	0 0 0.00 0 8 11/16 (220) in (mm) 0 7/16 (10) in (mm) 0 7/16 (10) in (mm) 9 1/16 (230) 0 13/16 (20)
Reprocessing of laboratory glassware  Standard electrical connection  Number of phases  Voltage in V  Frequency in Hz  Total rated load in kW  Fuse rating in A  Dimensions and weight  External dimensions, net height in mm  External dimensions, net depth in mm  External dimensions, gross height in mm  External dimensions, gross width in mm  External dimensions, gross width in mm  External dimensions, gross width in mm  External dimensions, gross depth in in (mm)	0 0 0.00 0 8 11/16 (220) in (mm) 0 7/16 (10) in (mm) 0 7/16 (10) in (mm) 9 1/16 (230) 0 13/16 (20) 1 3/16 (30)