

E 385 Mobile unit for the optimum loading of narrow necked glassware.





- equipped with 16 injector nozzles
- Equipped with connection for hot air drying
- Bracket for ML/2 for wash cart recognition / spray arm control

Product category	
Glassware Washers, laboratory	•
Machine affiliation	
PG 8535	•
PG 8536	•
Product category	
Mobile unit with connection for hot-air drying	•
Mobile unit for narrow necked glassware	•
Product characteristics	
Material	Stainless steel, Plastic
Colour	Stainless Steel, Black
Application area	
Reprocessing of laboratory glassware	•
Capacity	
Narrow necked glassware [number]	16
Standard electrical connection	
Number of phases	0
Voltage in V	0
Frequency in Hz	0
Total rated load in kW	0.00
Fuse rating in A	0
Dimensions and weight	
External dimensions, net height in in. (mm)	19 13/16 (502)
External dimensions, net width in in. (mm)	21 1/8 (535)
External dimensions, net depth in in. (mm)	20 3/8 (517)
External dimensions, gross height in in. (mm)	21 11/16 (550)
External dimensions, gross width in in. (mm)	21 5/16 (540)
External dimensions, gross depth in in (mm)	11 1/16 (280)
Net weight in lb (kg)	13 (5.70)
Gross weight in lb (kg)	15 (6.70)
Accessory pack	
E 351 injector nozzle, Ø 4 mm, length 160 mm [number]	7
E 352 injector nozzle, Ø 6 mm, length 220 mm [number]	9
E 353 clip for injector nozzle E 351 [number]	7
E 354 clip for injector nozzle E 352 [number]	9
Rinse nozzle for powder dispenser [number]	1