

PW 6080 Vario [EL LP]

Washing machine, electric heating

with suspended drum unit, shortest cycle time of 53 min and drain pump.



- Drum volume 2.83 (80) ft³ (l), load size 18 (8.0) lb (kg)
- Large program variety – application-specific wash programs
- Gentle laundry care thanks to the Miele honeycomb drum
- Particularly efficient – low water and energy consumption
- Perfect spinning results – residual moisture 44 %*, g-factor 520

* Residual moisture specification relates to a hot rinse during the last rinse cycle.

EAN: 4002515127315 / Material number: 09292310 / Old Material Number: 51608065USA

Construction type and design

Construction type	Front loader
Product line	Octoplus
Front	Octo blue
Load ratio	1:10
Load in lbs. (kg)	18 (8.0)
Drum volume in l	2.83 (80) ft³ (l)
Door opening [Ø] in in. (mm)	14 5/8 (370)
Door-opening angle in degrees	180
Door hinging	right
Maintenance-free motor with frequency converter	•
Honeycomb drum	•

Application

Suitable for hotels and restaurants	•
Suitable for retirement and care homes	•
Suitable for dry cleaners	•
Suitable for commercial laundromats	•
Suitable for small businesses	•
Suitable for fire departments and rescue services	•
Suitable for universities, schools, and kindergartens	•
Suitable for hospitals	•
Suitable for sports clubs	•
Suitable for beauty salons, spas, and fitness centres	•
Suitable for medical and dental practices	•

Performance data

Specific water consumption for hot water connection in l/kg	8.25
Specific energy consumption for hot water connection in kWh/kg	0.06
Program duration with cold water connection in minutes	57
Program duration with hot water connection in minutes	53
Residual moisture with cold rinse in %	49
Residual moisture with hot rinse in %	44
Spin speed in rpm	1300
g-factor	520
Tested operating hours	30000

Controls

Control type	Profitronic L Vario
Programmability	programmable
Max. delay start in h	24
Time left display	•
Program sequence indicator	•
Choice of display language	•

Standard / target grp programs

Basic programs	•
Programs for hotels and restaurants	•
Programs for retirement and care homes	•
Programs for laundromats	•
Programs for residential homes and apartments	•
Programs for dry cleaners	•

PW 6080 Vario [EL LP]

Washing machine, electric heating

with suspended drum unit, shortest cycle time of 53 min and drain pump.



EAN: 4002515127315 / Material number: 09292310 / Old Material Number: 51608065USA

Programs for commercial laundromats	•
Programs for small businesses	•
Programs for fire departments and rescue services	•
Programs for universities, kindergartens, and schools	•
Programs for hospitals	•
Programs for fast food restaurants	•
Programs for camp sites	•
Programs for sports clubs	•
Programs for salons, spas, and fitness centres	•
Programs for private households	•
Programs for medical and dental practices	•
Dispensing	
Detergent drawer	3 compartments
Patented liquid dispensing adapter	•
Maximum number of connections for liquid dispenser pumps [number]	6
Empty sensing	•
Standard electrical connection	
Heating type	Electric
Electrical connection	2 AC 220-240V 60HZ
Heater rating in kW	4.20-5.00
Total rated load in kW	4.40-5.20
Fuse rating in A	30
NEMA plug: Twist Lock L6-30	•
Possible voltage variant 1	
Electrical connection	2 AC 208V 60HZ
Heater rating in kW	3.80
Total rated load in kW	4.00
Fuse rating in A	30
Water connection/drainage	
Cold water [number]	1x 1/2" hose w/ 3/4" th. union
Hot water [number]	1x 1/2" hose w/ 3/4" th. union
Alternative water supply (optional) [number]	1 x 1/2" w/ 3/4" union
Drain pump	DN 22
Dimensions and weight	
External dimensions, net height in in. (mm)	40 3/16 (1020)
External dimensions, net width in in. (mm)	27 9/16 (700)
External dimensions, net depth in in. (mm)	28 5/8 (727)
External dimensions, gross height in in. (mm)	47 7/8 (1215)
External dimensions, gross width in in. (mm)	29 15/16 (760)
External dimensions, gross depth in in. (mm)	32 5/16 (820)
Net weight in lbs. (kg)	309 (140.0)
Gross weight in lbs. (kg)	327 (148)
Maximum floor load in N/m ²	2600
Emission values	
Emission sound pressure level in the workplace	<70 dB(A) re 20 µPa
Heat dissipation into the room in MJ/h	3.00
Features	
Imbalance monitoring	•

PW 6080 Vario [EL LP]

Washing machine, electric heating

with suspended drum unit, shortest cycle time of 53 min and drain pump.



EAN: 4002515127315 / Material number: 09292310 / Old Material Number: 51608065USA

Disinfection rinse	•
Temperature monitoring	•
Special heater element	•
Automatic load recognition	•
Volumetric flow meter	•
Communication slot	•
Machine-independent accessories	•
Efficiency and sustainability	
Recycling rate in %	95
Connection options	
Payment system	•
Optical interface for service access	•
Serial interface module RS 232 (optional)	•
Peak-load negotiation / energy management (optional)	•
Capacities	
Breathing masks [number]	4-5
Protective suits [number]	1
Protective coats [number]	1-2
Synthetic duvets [number]	1
Synthetic pillows [number]	1-2
Down comforters [number]	1
Down pillows [number]	1-2
Standards / certs / symbols	
Splash protection IPX4	•
Complies with Machinery Directive 2006/42/EC	•