


A 202 Mobile unit for the optimum loading of 4 DIN mesh trays.





- Suitable for 4 DIN mesh trays on 2 levels
- Insert frames: Removable for the reprocessing of tall wash items
- 6 additional connection options via Luer lock connection
- With integrated spray arm
- Loading volumes for the different levels differ from each other

Product category	
Glassware Washers, laboratory	•
Washer-disinfectors, medical	•
Machine affiliation	
PG 8562	•
PG 8582	•
PG 8582 CD	•
PG 8583	•
PG 8583 CD	•
PG 8592	•
PG 8593	•
Product category	
Mobile unit for inserts	•
Mobile unit for mesh trays	•
Product characteristics	
Material	Stainless steel, Plastic
Colour	Stainless Steel, Black
Application area	
Reprocessing of laboratory glassware	•
Reprocessing of surgical instruments	•
Capacity	
DIN mesh trays [number]	4
DIN mesh trays [number] Standard electrical connection	4
	0
Standard electrical connection	
Standard electrical connection Number of phases	0
Standard electrical connection  Number of phases  Voltage in V	0
Standard electrical connection  Number of phases  Voltage in V  Frequency in Hz	0 0 0
Standard electrical connection Number of phases Voltage in V Frequency in Hz Total rated load in kW	0 0 0 0 0.00
Standard electrical connection Number of phases Voltage in V Frequency in Hz Total rated load in kW Fuse rating in A	0 0 0 0 0.00
Standard electrical connection  Number of phases  Voltage in V  Frequency in Hz  Total rated load in kW  Fuse rating in A  Dimensions and weight	0 0 0 0 0.00
Standard electrical connection  Number of phases  Voltage in V  Frequency in Hz  Total rated load in kW  Fuse rating in A  Dimensions and weight  External dimensions, net height in in. (mm)	0 0 0 0.00 0 0 8 13/16 (223)
Standard electrical connection  Number of phases  Voltage in V  Frequency in Hz  Total rated load in kW  Fuse rating in A  Dimensions and weight  External dimensions, net height in in. (mm)  External dimensions, net width in in. (mm)	0 0 0 0.00 0 0 8 13/16 (223) 20 7/8 (529)
Standard electrical connection Number of phases Voltage in V Frequency in Hz Total rated load in kW Fuse rating in A Dimensions and weight External dimensions, net height in in. (mm) External dimensions, net depth in in. (mm)	0 0 0 0.00 0 8 13/16 (223) 20 7/8 (529) 21 3/8 (542)
Standard electrical connection Number of phases Voltage in V Frequency in Hz Total rated load in kW Fuse rating in A Dimensions and weight External dimensions, net height in in. (mm) External dimensions, net depth in in. (mm) External dimensions, net depth in in. (mm) External dimensions, gross height in in. (mm)	0 0 0 0.00 0 8 13/16 (223) 20 7/8 (529) 21 3/8 (542) 9 5/16 (235)
Standard electrical connection Number of phases Voltage in V Frequency in Hz Total rated load in kW Fuse rating in A Dimensions and weight External dimensions, net height in in. (mm) External dimensions, net depth in in. (mm) External dimensions, gross height in in. (mm) External dimensions, gross height in in. (mm)	0 0 0 0.00 0 8 13/16 (223) 20 7/8 (529) 21 3/8 (542) 9 5/16 (235) 21 11/16 (550)