

PLW 6111 [DP BO SC CL H14 PR UL]
 Lab washer with 3 wash levels in SlimLine design
 with steam condenser, boiler, printer, and chamber lighting



- Performance/cycle 126 narrow necked glassware or 121 pipettes – 7.416 (210) ft³ (l) usable capacity
- Ergonomic loading and unloading – telescopic runners
- Flexible – 4 different level positions
- Have everything in view thanks to the all-glass door
- High capacity – reprocessing of vessels up to 50 l (13 gal)

EAN: 8051160654147 / Material number: 10959290 / Old Material Number: 62611177US

Construction type and design	
Construction type	Freestanding appliance, 1 glass hinged door
Heating type	Electricity
Front / back	Stainless Steel
Side panels	Stainless steel
Slimline construction type	•
Number of wash levels	3
Loading and unloading with telescopic rails	•
Electric door lock	•
Buzzer, acoustic signal at end of program	•
Easy-to-service construction	•
Application	
Suitable for laboratories	•
Capacity	
Narrow necked glassware per cycle [number]	126
Test tubes per cycle [number]	468
Laboratory flasks per cycle [number]	84
Pipettes per cycle [number]	121
Performance data	
Circulation pump, Qmax in gal/min (l/min.)	184.94 (700)
Usable wash cabinet volume in cu.ft (L)	7.41 (210) ft ³ (l)
Controls	
Control type	MP.CON 3
Program selection	Touch on Glass
Programmability	Freely programmable
Programs [number]	18
Free program slots [number]	20
Automatic program restart	•
Time left display	•
Program sequence indicator	•
Choice of display language	•
Standard electrical connection	
Electrical connection	3 AC 208V 60HZ
Heater rating in kW	7.50
Total rated load in kW	8.25
Fuse rating in A	30
Length of power cord in m	7.87 (2.00)
Water connection/drainage	
Cold water [number]	1
Hot water [number]	1
Fully demineralized water [number]	1
Required flow pressure in kPa	100-800
Maximum water hardness (cold water / hot water) in mmol/l	4.09 (0.70)
Drain pump [DN]	22
Drying unit	
Drying unit heating type	Electricity
Air throughput in ft ³ (min) (m ³ /h)	88.29 (150) ft ³ /min (m ³ /h)
Time settings in 1-minute steps	0-120
HEPA filter class	H14

PLW 6111 [DP BO SC CL H14 PR UL]

Lab washer with 3 wash levels in SlimLine design
with steam condenser, boiler, printer, and chamber lighting



EAN: 8051160654147 / Material number: 10959290 / Old Material Number: 62611177US

HEPA-filter filtration efficiency (DIN EN 1822) in %	99.99
Electric heater rating in kW	4.00
Dimensions and weight	
External dimensions, net height in in. (mm)	73 5/8 (1870) in (mm)
External dimensions, net width in in. (mm)	25 5/8 (650) in (mm)
External dimensions, net depth in in. (mm)	27 1/16 (687) in (mm)
External dimensions, gross height in in. (mm)	83 1/8 (2110)
External dimensions, gross width in in. (mm)	37 1/4 (945)
External dimensions, gross depth in in. (mm)	33 1/8 (840)
Wash cabinet, height in in. (mm)	26 3/16 (665)
Wash cabinet, width in in. (mm)	21 5/16 (540)
Wash cabinet, depth in in. (mm)	23 1/16 (585)
Rack height above floor in in. (mm)	33 1/2 (850)
Net weight in lb (kg)	554 (251)
Gross weight in lb (kg)	574 (260)
Maximum floor load in N/m ²	4000
Emission values	
Sound pressure LpA in cleaning and drying according to DIN EN ISO 11201	<70 dB(A) re 20 µPa
Heat dissipation into the room in MJ/h	1.26
Programs	
Thermal disinfection	•
Laboratory glassware reprocessing	•
Plastics	•
Features	
2 integrated hose dispenser pumps for liquid media	•
Boiler for preheating fully demineralized water	•
Steam condenser	•
Volume flow control	•
Interface for process documentation	•
Multi-component filter system	•
Load carrier – direct coupling	•
Integrated hot-air drying	•
Integrated printer for process documentation	•
Wash cabinet made from high-quality stainless steel (1.4404 / 316L)	•
Base	•
Chamber lighting	•
Connection options	
RS 232 serial interface	•
USB interface	•
Standards / certs / symbols	
RoHS Directive 2011/65/EU	•
c CSA us	•