

A 860 Holding frames For injector modules A 300/2 and A 300/3

EAN: 4002516087663 / Material number: 11056800 / Old Material Number: 69686000D



- Arrangement: 2 x 4 fields
- For use on A 300/2 and A 300/3 injector modules
- For the optimum positioning of laboratory glassware
- Part of SimpleLoad system

Glassware Washers, laboratory Large-capacity washer-disinfectors, laboratory Machine affiliation PG 8504 PG 8583 PG 8583 PG 8583 Product category Other inserts / other modules Product characteristics Material Colour Stainless steel, Plastic Colour Stainless Steel, Black Number of compartments 8 Compartment width in mm 4 1/2 (114) Compartment length in mm 4 1/2 (114) Part of SimpleLoad system Application area Reprocessing of laboratory glassware Standard electrical connection Number of phases Voltage in V Prequency in Hz Total rated load in kW 0.00-0.00 Fuse rating in A 0-0 Dimensions and weight External dimensions, net height in in. (mm) External dimensions, net depth in in. (mm) External dimensions, gross height in in. (mm) External dimensions, gross sedepth in in. (mm) External dimensions, gross depth in in. (mm) External dimensions, gross depth in in. (mm) External dimensions, gross depth in in. (mm) External dimensions, gross depth in in. (mm) External dimensions, gross depth in in. (mm) External dimensions, gross depth in in. (mm) External dimensions, gross depth in in. (mm) External dimensions, gross depth in in. (mm) External dimensions, gross depth in in. (mm) External dimensions, gross depth in in. (mm) External dimensions, gross depth in in. (mm) External dimensions, gross depth in in. (mm) External dimensions, gross depth in in. (mm)	Product category	
Large-capacity washer-disinfectors, laboratory Machine affiliation PG 8504 PG 8583 PG 8583 PG 8583 Product category Other inserts / other modules Product characteristics Material Stainless steel, Plastic Colour Stainless Steel, Black Number of compartments 8 Compartment width in mm 4 1/2 (114) Compartment length in mm 4 1/2 (114) Part of SimpleLoad system Application area Reprocessing of laboratory glassware Standard electrical connection Number of phases Voltage in V Prequency in Hz Total rated load in kW Dimensions and weight External dimensions, net height in in. (mm) External dimensions, net width in in. (mm) External dimensions, gross height in in. (mm) External dimensions, gross width in in. (mm) External dimensions, gross depth in in. (mm) External dimensions, gross depth in in. (mm) External dimensions, gross depth in in. (mm) External dimensions, gross depth in in. (mm) External dimensions, gross depth in in. (mm) External dimensions, gross depth in in. (mm) External dimensions, gross depth in in. (mm) External dimensions, gross depth in in. (mm) External dimensions, gross depth in in. (mm) External dimensions, gross depth in in. (mm) External dimensions, gross depth in in. (mm) External dimensions, gross depth in in. (mm) External dimensions, gross depth in in. (mm) External dimensions, gross depth in in. (mm) External dimensions, gross depth in in. (mm) External dimensions, gross depth in in. (mm)	0 ,	•
Machine affiliation • PG 8504 • PG 8583 • PG 8593 • Product category • Other inserts / other modules • Product characteristics • Material Stainless steel, Plastic Colour Stainless Steel, Black Number of compartments 8 Compartment width in mm 4 1/2 (114) Compartment length in mm 4 1/2 (114) Part of SimpleLoad system • Application area • Reprocessing of laboratory glassware • Standard electrical connection • Number of phases 0 Voltage in V 0-0 Frequency in Hz 0-0 Total rated load in kW 0.00-0.00 Fuse rating in A 0 Dimensions and weight External dimensions, net height in in. (mm) 1 3/16 (30) External dimensions, net depth in in. (mm) 13 13/16 (350) External dimensions, gross height in in. (mm) 1 7/16 (35) External dimensions, g		•
PG 8504 PG 8583 PG 8583 CD PG 8593 Product category Other inserts / other modules Product characteristics Material Colour Stainless steel, Plastic Colour Stainless Steel, Black Number of compartments Compartment width in mm 4 1/2 (114) Compartment length in mm 4 1/2 (114) Part of SimpleLoad system Application area Reprocessing of laboratory glassware Standard electrical connection Number of phases Voltage in V Frequency in Hz Total rated load in kW Dimensions and weight External dimensions, net height in in. (mm) External dimensions, gross height in in. (mm) External dimensions, gross width in in. (mm) External dimensions, gross width in in. (mm) External dimensions, gross depth in in. (mm) External dimensions		
PG 8583 PG 8583 Product category Other inserts / other modules Product characteristics Material Stainless steel, Plastic Colour Stainless Steel, Black Number of compartments 8 Compartment width in mm 4 1/2 (114) Compartment length in mm 4 1/2 (114) Part of SimpleLoad system Application area Reprocessing of laboratory glassware Standard electrical connection Number of phases Voltage in V Frequency in Hz Total rated load in kW 0.00-0.00 Fruse rating in A Dimensions and weight External dimensions, net height in in. (mm) External dimensions, gross height in in. (mm) External dimensions, gross width in in. (mm) External dimensions, gross depth in in. (mm) External dimensions		•
PG 8593 Product category Other inserts / other modules Product characteristics Material Stainless steel, Plastic Colour Stainless Steel, Black Number of compartments 8 Compartment width in mm 4 1/2 (114) Compartment length in mm 4 1/2 (114) Part of SimpleLoad system Application area Reprocessing of laboratory glassware Standard electrical connection Number of phases Oolous Voltage in V Oolouse rating in A Dimensions and weight External dimensions, net height in in. (mm) External dimensions, gross height in in. (mm) External dimensions, gross depth in in. (mm) Distail 13/16 (300) External dimensions, gross depth in in. (mm) Distail 13/16 (300) External dimensions, gross depth in in. (mm) External dimensions, gross depth in in. (mm) Distail 13/16 (300) External dimensions, gross depth in in. (mm) Distail 13/16 (300) External dimensions, gross depth in in. (mm) Distail 13/16 (300) External dimensions, gross depth in in. (mm) Distail 13/16 (300) External dimensions, gross depth in in. (mm) Distail 13/16 (300) External dimensions, gross depth in in. (mm) Distail 13/16 (300) External dimensions, gross depth in in. (mm) Distail 13/16 (300) Distail 13/16 (PG 8583	•
Product category Other inserts / other modules Product characteristics Material Stainless steel, Plastic Colour Stainless Steel, Black Number of compartments 8 Compartment width in mm 4 1/2 (114) Compartment length in mm 4 1/2 (114) Part of SimpleLoad system Application area Reprocessing of laboratory glassware Standard electrical connection Number of phases Oolour Voltage in V Oolour Frequency in Hz Total rated load in kW Ooloo-0.00 Fuse rating in A Dimensions and weight External dimensions, net height in in. (mm) External dimensions, net depth in in. (mm) External dimensions, gross height in in. (mm) External dimensions, gross width in in. (mm) External dimensions, gross width in in. (mm) External dimensions, gross depth in in. (mm) Discount of the initial control of the	PG 8583 CD	•
Other inserts / other modules Product characteristics Material Stainless steel, Plastic Colour Stainless Steel, Black Number of compartments Compartment width in mm 4 1/2 (114) Compartment length in mm 4 1/2 (114) Part of SimpleLoad system Application area Reprocessing of laboratory glassware Standard electrical connection Number of phases O-O Frequency in Hz Total rated load in kW Dimensions and weight External dimensions, net height in in. (mm) External dimensions, net width in in. (mm) External dimensions, gross height in in. (mm) External dimensions, gross width in in. (mm) External dimensions, gross width in in. (mm) External dimensions, gross depth in in. (mm)	PG 8593	•
Other inserts / other modules Product characteristics Material Stainless steel, Plastic Colour Stainless Steel, Black Number of compartments Compartment width in mm 4 1/2 (114) Compartment length in mm 4 1/2 (114) Part of SimpleLoad system Application area Reprocessing of laboratory glassware Standard electrical connection Number of phases O-O Frequency in Hz Total rated load in kW Dimensions and weight External dimensions, net height in in. (mm) External dimensions, net width in in. (mm) External dimensions, gross height in in. (mm) External dimensions, gross width in in. (mm) External dimensions, gross width in in. (mm) External dimensions, gross depth in in. (mm)	Product category	
Material Stainless steel, Plastic Colour Stainless Steel, Black Number of compartments 8 Compartment width in mm 4 1/2 (114) Compartment length in mm 4 1/2 (114) Part of SimpleLoad system Application area Reprocessing of laboratory glassware Standard electrical connection Number of phases O Voltage in V O-O Frequency in Hz O-O Total rated load in kW O.00-0.00 Fuse rating in A Dimensions and weight External dimensions, net height in in. (mm) External dimensions, net depth in in. (mm) External dimensions, gross height in in. (mm) External dimensions, gross width in in. (mm) External dimensions, gross depth in in. (mm) External dimensions, gross depth in in. (mm) External dimensions, gross depth in in. (mm) External dimensions, gross depth in in. (mm) External dimensions, gross depth in in. (mm) External dimensions, gross depth in in. (mm) External dimensions, gross depth in in. (mm) External dimensions, gross depth in in. (mm) External dimensions, gross depth in in. (mm)	Other inserts / other modules	•
Colour Number of compartments Compartment width in mm A 1/2 (114) Compartment length in mm 4 1/2 (114) Part of SimpleLoad system Application area Reprocessing of laboratory glassware Standard electrical connection Number of phases Voltage in V Co-0 Frequency in Hz Total rated load in kW Dimensions and weight External dimensions, net height in in. (mm) External dimensions, net depth in in. (mm) External dimensions, gross height in in. (mm) External dimensions, gross width in in. (mm) External dimensions, gross depth in in. (mm) 1 1 3/16 (300) External dimensions, gross depth in in. (mm) 1 1 13/16 (300) External dimensions, gross depth in in. (mm) 1 5 3/4 (400) Net weight in lb (kg)	Product characteristics	
Colour Number of compartments Compartment width in mm Compartment length in mm 4 1/2 (114) Part of SimpleLoad system Application area Reprocessing of laboratory glassware Standard electrical connection Number of phases Voltage in V Total rated load in kW Condumensions and weight External dimensions, net height in in. (mm) External dimensions, net depth in in. (mm) External dimensions, gross height in in. (mm) External dimensions, gross depth in in. (mm) Discovery and the steel, Black 8 8 8 Compartment width in mm 4 1/2 (114) 6 0 0 0 0 1 1 1 1 1 1 1 1 1	Material	Stainless steel, Plastic
Compartment width in mm Compartment length in mm A 1/2 (114) Part of SimpleLoad system Application area Reprocessing of laboratory glassware Standard electrical connection Number of phases Voltage in V Frequency in Hz Total rated load in kW Do-0 Fuse rating in A Dimensions and weight External dimensions, net height in in. (mm) External dimensions, net depth in in. (mm) External dimensions, gross height in in. (mm) External dimensions, gross width in in. (mm) External dimensions, gross width in in. (mm) External dimensions, gross depth in in. (mm) External dimensions, gross depth in in. (mm) Discovery and the state of the state	Colour	
Compartment length in mm Application area Reprocessing of laboratory glassware Standard electrical connection Number of phases Voltage in V Total rated load in kW Co-0 Total rated load in kW External dimensions, net height in in. (mm) External dimensions, net depth in in. (mm) External dimensions, gross height in in. (mm) External dimensions, gross width in in. (mm) External dimensions, gross depth in in. (mm)	Number of compartments	8
Part of SimpleLoad system Application area Reprocessing of laboratory glassware Standard electrical connection Number of phases O-0 Voltage in V Total rated load in kW O-00 Fuse rating in A Dimensions and weight External dimensions, net height in in. (mm) External dimensions, net width in in. (mm) External dimensions, gross height in in. (mm) External dimensions, gross width in in. (mm) External dimensions, gross depth in in. (mm) 15 3/4 (400) Net weight in lb (kg)	Compartment width in mm	4 1/2 (114)
Application area Reprocessing of laboratory glassware Standard electrical connection Number of phases O-0 Voltage in V Total rated load in kW Dimensions and weight External dimensions, net height in in. (mm) External dimensions, net depth in in. (mm) External dimensions, gross height in in. (mm) External dimensions, gross width in in. (mm) Total rated load in kW Dimensions and weight External dimensions, net width in in. (mm) External dimensions, net width in in. (mm) External dimensions, gross height in in. (mm) External dimensions, gross width in in. (mm) External dimensions, gross width in in. (mm) External dimensions, gross depth in in. (mm) Total rated load in kW D-0 D-0 D-0 D-0 D-0 D-0 D-0 D-	Compartment length in mm	4 1/2 (114)
Reprocessing of laboratory glassware Standard electrical connection Number of phases O Voltage in V O-0 Frequency in Hz Total rated load in kW O.00-0.00 Fuse rating in A O-0 Dimensions and weight External dimensions, net height in in. (mm) External dimensions, net width in in. (mm) External dimensions, net depth in in. (mm) External dimensions, gross height in in. (mm) External dimensions, gross width in in. (mm) 1 3/16 (350) External dimensions, gross width in in. (mm) 1 7/16 (35) External dimensions, gross depth in in. (mm) External dimensions, gross depth in in. (mm) Discovery and the standard of the standa	Part of SimpleLoad system	•
Standard electrical connection 0 Number of phases 0 Voltage in V 0-0 Frequency in Hz 0-0 Total rated load in kW 0.00-0.00 Fuse rating in A 0-0 Dimensions and weight 2 External dimensions, net height in in. (mm) 1 3/16 (30) External dimensions, net width in in. (mm) 9 7/8 (250) External dimensions, net depth in in. (mm) 13 13/16 (350) External dimensions, gross height in in. (mm) 1 7/16 (35) External dimensions, gross width in in. (mm) 11 13/16 (300) External dimensions, gross depth in in. (mm) 15 3/4 (400) Net weight in lb (kg) 1 (0.10)	Application area	
Number of phases 0 Voltage in V 0-0 Frequency in Hz 0-0 Total rated load in kW 0.00-0.00 Fuse rating in A 0-0 Dimensions and weight 1 3/16 (30) External dimensions, net height in in. (mm) 9 7/8 (250) External dimensions, net depth in in. (mm) 13 13/16 (350) External dimensions, gross height in in. (mm) 1 7/16 (35) External dimensions, gross width in in. (mm) 11 13/16 (300) External dimensions, gross depth in in. (mm) 15 3/4 (400) Net weight in lb (kg) 1 (0.10)	Reprocessing of laboratory glassware	•
Voltage in V 0-0 Frequency in Hz 0-0 Total rated load in kW 0.00-0.00 Fuse rating in A 0-0 Dimensions and weight 8 External dimensions, net height in in. (mm) 1 3/16 (30) External dimensions, net width in in. (mm) 9 7/8 (250) External dimensions, net depth in in. (mm) 13 13/16 (350) External dimensions, gross height in in. (mm) 1 7/16 (35) External dimensions, gross width in in. (mm) 11 13/16 (300) External dimensions, gross depth in in. (mm) 15 3/4 (400) Net weight in lb (kg) 1 (0.10)	Standard electrical connection	
Frequency in Hz Total rated load in kW 0.00-0.00 Fuse rating in A 0-0 Dimensions and weight External dimensions, net height in in. (mm) 1 3/16 (30) External dimensions, net width in in. (mm) 9 7/8 (250) External dimensions, net depth in in. (mm) 13 13/16 (350) External dimensions, gross height in in. (mm) 1 7/16 (35) External dimensions, gross width in in. (mm) 11 13/16 (300) External dimensions, gross depth in in. (mm) 15 3/4 (400) Net weight in lb (kg) 1 (0.10)	Number of phases	0
Total rated load in kW O.00-0.00 Fuse rating in A O-0 Dimensions and weight External dimensions, net height in in. (mm) External dimensions, net width in in. (mm) 9 7/8 (250) External dimensions, net depth in in. (mm) 13 13/16 (350) External dimensions, gross height in in. (mm) 1 7/16 (35) External dimensions, gross width in in. (mm) 1 1 13/16 (300) External dimensions, gross depth in in. (mm) 15 3/4 (400) Net weight in lb (kg) 1 (0.10)	Voltage in V	0-0
Fuse rating in A Dimensions and weight External dimensions, net height in in. (mm) External dimensions, net width in in. (mm) External dimensions, net depth in in. (mm) External dimensions, gross height in in. (mm) External dimensions, gross width in in. (mm) External dimensions, gross width in in. (mm) External dimensions, gross depth in in. (mm) Det weight in lb (kg) 1 (0.10)	Frequency in Hz	0-0
Dimensions and weight External dimensions, net height in in. (mm) External dimensions, net width in in. (mm) External dimensions, net depth in in. (mm) External dimensions, net depth in in. (mm) External dimensions, gross height in in. (mm) External dimensions, gross width in in. (mm) External dimensions, gross width in in. (mm) External dimensions, gross depth in in. (mm) External dimensions, gross depth in in. (mm) External dimensions, gross depth in in. (mm) 15 3/4 (400) Net weight in lb (kg)	Total rated load in kW	0.00-0.00
External dimensions, net height in in. (mm) External dimensions, net width in in. (mm) 9 7/8 (250) External dimensions, net depth in in. (mm) 13 13/16 (350) External dimensions, gross height in in. (mm) 1 7/16 (35) External dimensions, gross width in in. (mm) 11 13/16 (300) External dimensions, gross depth in in. (mm) 15 3/4 (400) Net weight in lb (kg) 1 (0.10)	Fuse rating in A	0-0
External dimensions, net width in in. (mm) 9 7/8 (250) External dimensions, net depth in in. (mm) 13 13/16 (350) External dimensions, gross height in in. (mm) 1 7/16 (35) External dimensions, gross width in in. (mm) 11 13/16 (300) External dimensions, gross depth in in. (mm) 15 3/4 (400) Net weight in lb (kg) 1 (0.10)	Dimensions and weight	
External dimensions, net depth in in. (mm) External dimensions, gross height in in. (mm) 1 7/16 (35) External dimensions, gross width in in. (mm) 1 1 13/16 (300) External dimensions, gross depth in in. (mm) 15 3/4 (400) Net weight in lb (kg) 1 (0.10)	External dimensions, net height in in. (mm)	1 3/16 (30)
External dimensions, gross height in in. (mm) 1 7/16 (35) External dimensions, gross width in in. (mm) 11 13/16 (300) External dimensions, gross depth in in. (mm) 15 3/4 (400) Net weight in lb (kg) 1 (0.10)	External dimensions, net width in in. (mm)	9 7/8 (250)
External dimensions, gross width in in. (mm) 11 13/16 (300) External dimensions, gross depth in in. (mm) 15 3/4 (400) Net weight in lb (kg) 1 (0.10)	External dimensions, net depth in in. (mm)	13 13/16 (350)
External dimensions, gross depth in in. (mm) 15 3/4 (400) Net weight in lb (kg) 1 (0.10)	External dimensions, gross height in in. (mm)	1 7/16 (35)
Net weight in lb (kg) 1 (0.10)	External dimensions, gross width in in. (mm)	11 13/16 (300)
	External dimensions, gross depth in in. (mm)	15 3/4 (400)
Gross weight in lb (kg) 1 (0.18)	Net weight in lb (kg)	1 (0.10)
	Gross weight in lb (kg)	1 (0.18)