

PLW 8616 [EL CT]

Lab washer, electrically heated

– double door with combined tank, 900 mm wide, 12.395 (351) ft³ (l) usable capacity.



- Performance/cycle, e.g., 216 laboratory bottles, 588 vials, or 294 pipettes
- Flexible use of the combined tank as recycling/pre-heating tank
- Up to 60% less water consumption based on the load *
- Flexible and simple – modular load carriers & SimpleLoad system
- Efficient – powerful pump performance with variable-speed pump
- Reliable results – spray arm monitoring and conductivity meter

* e.g., 60% saving with 100 ml laboratory bottles in Universal Max program compared to Lab Universal program for PG 8527

EAN: 4002516148166 / Material number: 11179580 / Old Material Number: 62861602USA

Construction type and design	
Construction type	Freestanding appliance, throughfeed, 2 glass lifting doors
Heating type	Electricity
Front / back	Stainless Steel
Side panels	Stainless steel
Single / multiple installations	•
Loading with mobile units	•
Electric door lock	•
Buzzer, acoustic signal at end of program	•
Easy-to-service construction	•
Application	
Suitable for laboratories	•
Suitable for industrial applications	•
Capacity	
Narrow necked glassware per cycle [number]	216
Test tubes per cycle [number]	588
Laboratory flasks per cycle [number]	216
Pipettes per cycle [number]	294
Performance data	
Circulation pump, Qmax in gal/min (l/min.)	105.68 (400)
Additional circulation pump for load carriers – direct coupling, Qmax in l/min.	600
Variable-speed pump	•
Usable wash cabinet volume in cu.ft (L)	12.39 (351) ft ³ (l)
Tested operating hours	15000
Service life in wash cycles	20000
Controls	
Control type	PST 20
Program selection	Full-touch colour display
Programmability	programmable
Programs [number]	30
Free program slots [number]	170
Automatic program restart	•
Time left display	•
Program sequence indicator	•
Status display via chamber lighting	•
Choice of display language	•
Standard electrical connection	
Electrical connection	3 AC 208V 60HZ
Heater rating in kW	18.00
Total rated load in kW	21.00
Fuse rating in A	60
Water connection/drainage	
Cold water [number]	2
Hot water [number]	1
Fully demineralized water [number]	2
Required flow pressure in kPa	200-1000
Maximum water hardness (cold water / hot water) in mmol/l	4.15 (0.71)
Drain valve [DN]	50

PLW 8616 [EL CT]

Lab washer, electrically heated

– double door with combined tank, 900 mm wide, 12.395 (351) ft³ (l) usable capacity.



EAN: 4002516148166 / Material number: 11179580 / Old Material Number: 62861602USA

Drain pump (optional)	•
Compressed air connection	
Compressed air connection, technical [number]	1
Required compressed air, technical in kPa	600-800
Drying unit	
Drying unit heating type	Electricity
Air throughput in ft ³ (min) (m ³ /h)	147.15 (250) ft ³ /min (m ³ /h)
Time settings in 1-minute steps	1-240
HEPA filter class	H13
HEPA-filter filtration efficiency (DIN EN 1822) in %	99.95
Electric heater rating in kW	8.00
Dimensions and weight	
External dimensions, net height in in. (mm)	65 3/4 (1670) in (mm)
External dimensions, net width in in. (mm)	35 7/16 (900) in (mm)
External dimensions, net depth in in. (mm)	39 (990) in (mm)
External dimensions incl. base / floor tray and top-box panelling, height in mm	98 1/4 (2495)
External dimensions, gross height in in. (mm)	77 3/16 (1960)
External dimensions, gross width in in. (mm)	39 3/8 (1000)
External dimensions, gross depth in in. (mm)	44 1/2 (1130)
Wash cabinet, height in in. (mm)	26 5/8 (675)
Wash cabinet, width in in. (mm)	25 5/8 (650)
Wash cabinet, depth in in. (mm)	31 1/2 (800)
Rack height above floor in in. (mm)	33 1/2 (850)
Net weight in lb (kg)	896 (406)
Gross weight in lb (kg)	918 (416)
Maximum floor load in N/m ²	8000
Emission values	
Sound pressure LpA in cleaning and drying according to DIN EN ISO 11201	<65 dB(A) re 20 µPa
Programs	
Thermal disinfection	•
Laboratory glassware reprocessing	•
Plastics	•
Oil soiling	•
Industrial parts cleaning	•
Features	
2 integrated diaphragm dispenser pumps for liquid media	•
Additional integrated dispenser pumps	4
Combined tank	•
Steam condenser (optional)	•
Volume flow control	•
Spray arm monitoring	•
Conductivity monitoring	•
Interface for process documentation	•
Multi-component filter system	•
Micro-fine filter	•
Load carrier – direct coupling	•
Integrated hot-air drying (optional)	•
Integrated printer for process documentation (optional)	•
Heater elements outside wash cabinet	•

PLW 8616 [EL CT]

Lab washer, electrically heated

– double door with combined tank, 900 mm wide, 12.395 (351) ft³ (l) usable capacity.



EAN: 4002516148166 / Material number: 11179580 / Old Material Number: 62861602USA

SimpleLoad	•
Storage options for process chemicals (4 x 5 l or 2 x 5 l + 1 x 10 l)	•
Wash cabinet made from high-quality stainless steel (1.4404 / 316L)	•
Base (optional)	•
Drain water cooling (optional)	•
Coloured chamber lighting	•
Modular basket design	•
Option of using existing load carriers	•
Connection options	
Ethernet interface	•
External dispenser modules	•
USB interface	•
Central dispensing	•
Peak-load negotiation / energy management	•
Standards / certs / symbols	
CE	•
VDE (electrical safety)	•
EN 61010-2-040	•
Machinery Directive 2006/42/EC	•