

## PDR 908 HP [EL]

Professional heat-pump dryer (208/240V)

with very low energy consumption and short cycle times.



- Drum volume 4.59 (130.00) ft<sup>3</sup> (l), load size 18 (8.0) lb (kg)
- Tested for intensive use – unique Miele quality
- Maximum user comfort with touch colour display – M Touch Flex
- Precision drying of all fabrics – PerfectDry
- Future-proof networking via #WiFi#Z

EAN: 4002516195917 / Material number: 11204480 /  
Old Material Number: 52908159NAM

Construction type and design	
Construction type	Front-loader, stackable
Product line	Performance Plus
Front	Lotus white
Control panel colour	Stainless steel
Load in lbs. (kg)	18 (8.0)
Drum volume in l	4.59 (130.00) ft <sup>3</sup> (l)
Drying system	Heat pump
Door opening [Ø] in in. (mm)	14 5/8 (370)
Door-opening angle in degrees	167
Door hinging	left
Stainless steel honeycomb drum	Yes
Application	
Suitable for hotels and restaurants	•
Suitable for retirement and care homes	•
Suitable for facility management	•
Suitable for laundromats	•
Suitable for dry cleaners	•
Suitable for commercial laundromats	•
Suitable for small businesses	•
Suitable for universities, schools, and kindergartens	•
Suitable for hospitals	•
Suitable for camp sites	•
Suitable for sports clubs	•
Suitable for beauty salons, spas, and fitness centres	•
Suitable for medical and dental practices	•
Suitable for the petrochemical industry	•
Suitable for the food-processing industry	•
Suitable for amusement parks and holiday resorts	•
Suitable for public / community facilities	•
Performance data	
Maximum evaporation capacity in l/hour	3 (3) gal (US)/min (l)
Specific energy consumption in kWh/kg	0.20
Specific energy consumption of Cottons / Normal, residual moisture 48% in kWh/kg	0.20
Specific energy consumption of mixed blends / Normal, residual moisture 40% in kWh/kg	0.17
Program duration in minutes	88
Program duration for Cottons / Normal, residual moisture 48% in minutes	88
Program duration for mixed blends / Normal, residual moisture 40% in minutes	76
Controls	
Control type	M Touch Flex
Programmability	programmable
Program controls	Residual moisture controlled
Max. delay start in h	24
Time left display	•

## PDR 908 HP [EL]

Professional heat-pump dryer (208/240V)

with very low energy consumption and short cycle times.



EAN: 4002516195917 / Material number: 11204480 /  
Old Material Number: 52908159NAM

Program sequence indicator	•
Language can be selected easily at any time	•
<b>Standard electrical connection</b>	
Heating type	Heat pump
Electrical connection	2 AC 208-240V 60HZ
Total rated load in kW	1.20
Fuse rating in A	30
NEMA plug: Twist Lock L6-30	•
<b>Dimensions and weight of dryer</b>	
External dimensions, net height in in. (mm)	33 1/2 (850)
External dimensions, net width in in. (mm)	23 1/2 (596)
External dimensions, net depth in in. (mm)	30 5/8 (777)
External dimensions, gross height in in. (mm)	37 1/16 (940)
External dimensions, gross width in in. (mm)	26 (660)
External dimensions, gross depth in in. (mm)	32 5/16 (820)
Net weight in lbs. (kg)	157 (71.0)
Gross weight in lbs. (kg)	170 (77)
Maximum floor load in N	920
<b>Emission values</b>	
Emission sound pressure level in the workplace	<70 dB(A) re 20 µPa
Heat dissipation into the room in MJ/h	3.60
<b>Features</b>	
Intelligent drum reversal	•
Axial airflow	•
Lint filter in the door	•
Low-maintenance heat exchanger filter system	•
PerfectDry	•
SoftLift drum ribs	•
Gentle tumble function	•
Condensed water drainage	•
Communication slot	•
Dryer basket (optional)	•
Drum lighting	•
Machine-independent accessories	•
<b>Efficiency and sustainability</b>	
Recycling rate in %	95
Contains fluorinated greenhouse gases	•
Hermetically sealed system	•
Refrigerant	R134a
Refrigerant quantity in kg	0.59
Refrigerant global warming potential in kg CO <sub>2</sub> e	1430
Machine global warming potential in kg CO <sub>2</sub> e	844.00
<b>Connection options</b>	
Payment system (optional)	•
Optical interface for service access	•
<b>Standards / certs / symbols</b>	
WEEE	•
c ETL US	•