

PDR 908 HP [EL]
Professional heat-pump dryer (208/240V)
with very low energy consumption and short cycle times.



- Drum volume 4.59 (130.00) ft³ (l), load size 18 (8.0) lb (kg)
- Tested for intensive use – unique Miele quality
- Maximum user comfort with touch colour display – M Touch Flex
- Precision drying of all fabrics – PerfectDry
- Future-proof networking via #WiFi#

EAN: 4002516195924 / Material number: 11204490 / Old Material Number: 52908259NAM

| Construction type and design | |
|---|-----------------------------------|
| Construction type | Front-loader, stackable |
| Product line | Performance Plus |
| Front | Stainless steel |
| Control panel colour | Stainless steel |
| Load in lbs. (kg) | 18 (8.0) |
| Drum volume in l | 4.59 (130.00) ft ³ (l) |
| Drying system | Heat pump |
| Door opening [Ø] in in. (mm) | 14 5/8 (370) |
| Door-opening angle in degrees | 167 |
| Door hinging | left |
| Stainless steel honeycomb drum | Yes |
| Application | |
| Suitable for hotels and restaurants | • |
| Suitable for retirement and care homes | • |
| Suitable for facility management | • |
| Suitable for laundromats | • |
| Suitable for dry cleaners | • |
| Suitable for commercial laundromats | • |
| Suitable for small businesses | • |
| Suitable for universities, schools, and kindergartens | • |
| Suitable for hospitals | • |
| Suitable for camp sites | • |
| Suitable for sports clubs | • |
| Suitable for beauty salons, spas, and fitness centres | • |
| Suitable for medical and dental practices | • |
| Suitable for the petrochemical industry | • |
| Suitable for the food-processing industry | • |
| Suitable for amusement parks and holiday resorts | • |
| Suitable for public / community facilities | • |
| Performance data | |
| Maximum evaporation capacity in l/hour | 3 (3) gal (US)/min (l) |
| Specific energy consumption in kWh/kg | 0.20 |
| Specific energy consumption of Cottons / Normal, residual moisture 48% in kWh/kg | 0.20 |
| Specific energy consumption of mixed blends / Normal, residual moisture 40% in kWh/kg | 0.17 |
| Program duration in minutes | 88 |
| Program duration for Cottons / Normal, residual moisture 48% in minutes | 88 |
| Program duration for mixed blends / Normal, residual moisture 40% in minutes | 76 |
| Controls | |
| Control type | M Touch Flex |
| Programmability | programmable |
| Program controls | Residual moisture controlled |
| Max. delay start in h | 24 |
| Time left display | • |
| Program sequence indicator | • |
| Language can be selected easily at any time | • |

PDR 908 HP [EL]
Professional heat-pump dryer (208/240V)
with very low energy consumption and short cycle times.



EAN: 4002516195924 / Material number: 11204490 / Old Material Number: 52908259NAM

| Standard electrical connection | |
|--|---------------------|
| Heating type | Heat pump |
| Electrical connection | 2 AC 208-240V 60HZ |
| Total rated load in kW | 1.20 |
| Fuse rating in A | 30 |
| NEMA plug: Twist Lock L6-30 | • |
| Dimensions and weight of dryer | |
| External dimensions, net height in in. (mm) | 33 1/2 (850) |
| External dimensions, net width in in. (mm) | 23 7/8 (605) |
| External dimensions, net depth in in. (mm) | 30 5/8 (777) |
| External dimensions, gross height in in. (mm) | 37 1/16 (940) |
| External dimensions, gross width in in. (mm) | 26 (660) |
| External dimensions, gross depth in in. (mm) | 32 5/16 (820) |
| Net weight in lbs. (kg) | 159 (72.0) |
| Gross weight in lbs. (kg) | 172 (78) |
| Maximum floor load in N/m ² | 920 |
| Emission values | |
| Emission sound pressure level in the workplace | <70 dB(A) re 20 µPa |
| Heat dissipation into the room in MJ/h | 3.60 |
| Features | |
| Intelligent drum reversal | • |
| Axial airflow | • |
| Lint filter in the door | • |
| Low-maintenance heat exchanger filter system | • |
| PerfectDry | • |
| SoftLift drum ribs | • |
| Gentle tumble function | • |
| Condensed water drainage | • |
| Communication slot | • |
| Dryer basket (optional) | • |
| Drum lighting | • |
| Machine-independent accessories | • |
| Efficiency and sustainability | |
| Contains fluorinated greenhouse gases | • |
| Hermetically sealed system | • |
| Refrigerant | R134a |
| Refrigerant quantity in kg | 0.59 |
| Refrigerant global warming potential in kg CO ₂ e | 1430 |
| Machine global warming potential in kg CO ₂ e | 844.00 |
| Connection options | |
| Payment system (optional) | • |
| Optical interface for service access | • |
| Standards / certs / symbols | |
| WEEE | • |
| c ETL US | • |