Miele

PWM 912 [EL DV DD]

Professional washing machine, electric heating with detergent drawer, M Touch Pro Plus – freely programmable.



- Drum volume 3.88 (110) ft³ (l) I, load size 25 (11.0) lb (kg)
- Top cleaning & consumption values – innovative Miele technology
- Ideal operation thanks to touch colour display M Touch Pro Plus
- Simple and safe operation thanks to automatic door lock
- Connected for the future using LAN and Wi-Fi

Occasional transfer and discharge	
Construction type and design	
Construction type	Front loader
Product line	Performance Plus
Front	Stainless steel
Control panel colour	Stainless steel
Maximum load with a load ratio of 1:9 in lbs (kg)	27 (12.0)
Load ratio	1:9
Load in lbs. (kg)	25 (11.0)
Drum volume in I	3.88 (110) ft ³ (l)
Door opening [Ø] in in. (mm)	16 3/8 (415)
Door-opening angle in degrees	180
Door hinging	right
Automatic door lock	•
Innovative suds container	•
Maintenance-free motor with frequency converter	•
Patented honeycomb drum 2.0	•
Application	
Suitable for hotels and restaurants	•
Suitable for retirement and care homes	•
Suitable for facility management	•
Suitable for dry cleaners	•
Suitable for commercial laundromats	•
Suitable for small businesses	•
Suitable for fire departments and rescue services	•
Suitable for stud farms and stables	•
Suitable for universities, schools, and kindergartens	•
Suitable for hospitals	•
Suitable for camp sites	•
Suitable for sports clubs	•
Suitable for beauty salons, spas, and fitness centres	•
Suitable for the petrochemical industry	•
Suitable for amusement parks and holiday resorts	•
Suitable for public / community facilities	•
Performance data	
Tested virucidal efficacy	•
Proven hygiene	•
Specific water consumption for cold water connection in I/	6.20
kg	
Specific energy consumption for cold water connection in	0.14
kWh/kg	
Specific water consumption for hot water connection in I/kg	5.90
Specific energy consumption for hot water connection in kWh/kg	0.06
Water consumption with cold water connection in I	74.4
Energy consumption with cold water connection in kWh	1.68
Energy consumption for cold water connection in Mops	2.41
standard 60°C program in kWh	40
Program duration with cold water connection in minutes	49
Water consumption with hot water connection in I	70.8
Water consumption for hot water connection in Mops standard 60°C program in I	133.6



PWM 912 [EL DV DD]

Professional washing machine, electric heating with detergent drawer, M Touch Pro Plus – freely programmable.



Energy consumption with hot water connection in kWh	0.72
Energy consumption for hot water connection in Mops standard 60°C program in kWh	1.00
Program duration with hot water connection in minutes	42
Water consumption in Economy program with cold water connection in I	69.6
Energy consumption in Economy program with cold water connection in kWh	1.20
Program duration with cold water connection in Economy program in minutes	34
Water consumption in Economy program with hot water connection in I	68.4
Energy consumption in Economy program with hot water connection in kWh	0.36
Program duration with hot water connection in Economy program in minutes	31
Program cycle time in minutes for Mops standard 60°C program with cold water connection	53
Program cycle time in minutes for Mops standard 60°C program with hot water connection	45
Residual moisture with cold rinse in %	48
Residual moisture with hot rinse in %	44
Residual moisture when reprocessing wiping cloths in %	25
Spin speed in rpm	1150
g-factor	458
Tested operating hours	30000
Controls	
Control type	M Touch Pro Plus
Programmability	Freely programmable
Max. delay start in h	Can be selected freely
Max. delay start in h Time left display	Can be selected freely •
	-
Time left display	•
Time left display Program sequence indicator	•
Time left display Program sequence indicator Choice of display language	•
Time left display Program sequence indicator Choice of display language Option to enter weight prior to start of program	•
Time left display Program sequence indicator Choice of display language Option to enter weight prior to start of program Standard / target grp programs	•
Time left display Program sequence indicator Choice of display language Option to enter weight prior to start of program Standard / target grp programs Basic programs	•
Time left display Program sequence indicator Choice of display language Option to enter weight prior to start of program Standard / target grp programs Basic programs Dispensing	•
Time left display Program sequence indicator Choice of display language Option to enter weight prior to start of program Standard / target grp programs Basic programs Dispensing Detergent drawer Maximum number of connections for liquid dispenser	• • • • • 3 compartments
Time left display Program sequence indicator Choice of display language Option to enter weight prior to start of program Standard / target grp programs Basic programs Dispensing Detergent drawer Maximum number of connections for liquid dispenser pumps [number]	• • • • • 3 compartments 12
Time left display Program sequence indicator Choice of display language Option to enter weight prior to start of program Standard / target grp programs Basic programs Dispensing Detergent drawer Maximum number of connections for liquid dispenser pumps [number] Empty sensing	• • • • • 3 compartments 12
Time left display Program sequence indicator Choice of display language Option to enter weight prior to start of program Standard / target grp programs Basic programs Dispensing Detergent drawer Maximum number of connections for liquid dispenser pumps [number] Empty sensing Standard electrical connection	• • • • • 3 compartments 12
Time left display Program sequence indicator Choice of display language Option to enter weight prior to start of program Standard / target grp programs Basic programs Dispensing Detergent drawer Maximum number of connections for liquid dispenser pumps [number] Empty sensing Standard electrical connection Heating type	• • • • • 3 compartments 12 • Electric
Time left display Program sequence indicator Choice of display language Option to enter weight prior to start of program Standard / target grp programs Basic programs Dispensing Detergent drawer Maximum number of connections for liquid dispenser pumps [number] Empty sensing Standard electrical connection Heating type Electrical connection	• • • • • • • • • • • • • • • • • • •
Time left display Program sequence indicator Choice of display language Option to enter weight prior to start of program Standard / target grp programs Basic programs Dispensing Detergent drawer Maximum number of connections for liquid dispenser pumps [number] Empty sensing Standard electrical connection Heating type Electrical connection Heater rating in kW	• • • • • • • • • • • • • • • • • • •
Time left display Program sequence indicator Choice of display language Option to enter weight prior to start of program Standard / target grp programs Basic programs Dispensing Detergent drawer Maximum number of connections for liquid dispenser pumps [number] Empty sensing Standard electrical connection Heating type Electrical connection Heater rating in kW Total rated load in kW	• • • • • • • • • • • • • • • • • • •
Time left display Program sequence indicator Choice of display language Option to enter weight prior to start of program Standard / target grp programs Basic programs Dispensing Detergent drawer Maximum number of connections for liquid dispenser pumps [number] Empty sensing Standard electrical connection Heating type Electrical connection Heater rating in kW Total rated load in kW Fuse rating in A	• • • • • • • • • • • • • • • • • • •
Time left display Program sequence indicator Choice of display language Option to enter weight prior to start of program Standard / target grp programs Basic programs Dispensing Detergent drawer Maximum number of connections for liquid dispenser pumps [number] Empty sensing Standard electrical connection Heating type Electrical connection Heater rating in kW Total rated load in kW Fuse rating in A Water connection/drainage	• • • • • • • • • • • • • • • • • • •



PWM 912 [EL DV DD]

Professional washing machine, electric heating with detergent drawer, M Touch Pro Plus – freely programmable.

Drain valve	DN 70
Dimensions and weight	
External dimensions, net height in in. (mm)	53 3/16 (1350)
External dimensions, net width in in. (mm)	31 1/2 (799)
External dimensions, net depth in in. (mm)	40 3/8 (1024)
External dimensions, gross height in in. (mm)	58 5/16 (1480)
External dimensions, gross width in in. (mm)	47 11/16 (1210)
External dimensions, gross depth in in. (mm)	44 1/2 (1130)
Net weight in lbs. (kg)	669 (303.0)
Gross weight in lbs. (kg)	719 (326)
Maximum floor load in N/m ²	4716
Emission values	
Emission sound pressure level in the workplace	65 dB(A) re 20 µPa
Heat dissipation into the room in MJ/h	6.48
Features	
Patented pre-spin	•
Cloths treatment	•
3-dimensional imbalance monitoring	•
Disinfection rinse	•
Efficient scoop ribs	•
EcoSpeed	•
Spring-in-spring system	•
Temperature monitoring	•
Special heater element	•
Automatic load recognition+	•
Volumetric flow meter (optional)	•
Weighing base (optional)	•
Adding laundry	•
Program selection via colour frame	•
Emergency shut-off	•
Machine-independent accessories	•
Efficiency and sustainability	
Recycling rate in %	91
Connection options	
Payment system (optional)	•
Optical interface for service access	•
Peak-load negotiation / energy management (optional)	•
Water recovery (optional)	•
LAN	•
Wi-Fi	•
Connector Box	•
Capacities	
Breathing masks [number]	10
Helmets [number]	3
Protective suits [number]	2
Protective coats [number]	3
Chemical protection suits [number]	
Synthetic duvets [number]	
Synthetic pillows [number]	2
Down comforters [number]	
Down pillows [number]	2
Some provide [narribot]	



PWM 912 [EL DV DD]

Professional washing machine, electric heating with detergent drawer, M Touch Pro Plus – freely programmable.



Cleaning cloths, 22 g [number]	289
Cotton mops, 40 cm / 190 g [number]	64
Cotton mops, 50 cm / 220 g [number]	56
Microfibre mops, 40 cm / 120 g [number]	102
Microfibre mops, 50 cm / 170 g [number]	72
Mops, office, 100 g [number]	120
Mops, stairway, 150 g [number]	80
Horse summer blankets [number]	2
Standards / certs / symbols	
Splash protection IPX4	•
c ETL US	•
Complies with Machinery Directive 2006/42/FC	•