

PDR 522 ROP [G]

Professional vented dryer, gas heating

with M Select ROP residual moisture control for perfect drying results.



- Drum volume 14.13 (400.00) ft³ (l), load size 36 (16.0) lb (kg) – 49 (22.0) lb (kg)
- Unique, gentle fabric care – honeycomb drum
- Greatest energy efficiency thanks to Air Recycling
- Precision drying of all fabrics – PerfectDry
- Connected for the future using LAN and Wi-Fi

EAN: 4002516546467 / Material number: 12012250 / Old Material Number: 52522015NAM

Construction type and design	
Construction type	Front loader
Product line	Performance
Front	Stainless steel
Load size with a load ratio of 1:25	36 (16.0)
Load size with a load ratio of 1:18	50 (22.5)
Drum volume in l	14.13 (400.00) ft ³ (l)
Drying system	Vented system
Door opening [Ø] in in. (mm)	20 1/2 (520)
Door-opening angle in degrees	180
Door hinging	left
Convertible hinging	•
Stainless steel honeycomb drum	Yes
Application	
Suitable for hotels and restaurants	•
Suitable for retirement and care homes	•
Suitable for facility management	•
Suitable for commercial laundromats	•
Suitable for small businesses	•
Suitable for stud farms and stables	•
Suitable for universities, schools, and kindergartens	•
Suitable for hospitals	•
Suitable for sports clubs	•
Suitable for beauty salons, spas, and fitness centres	•
Suitable for amusement parks and holiday resorts	•
Suitable for public / community facilities	•
Performance data	
Maximum evaporation capacity in l/hour	21 (21) gal (US)/min (l)
Specific energy consumption in kWh/kg	0.55
Program duration in minutes	25
Tested operating hours	20000
Controls	
Control type	M Select Benchmark
Programmability	Setting of defined parameters
Program controls	Residual moisture controlled
Max. delay start in h	24
Time left display	•
Panel with easy-to-understand icons	•
Standard electrical connection	
Heating type	Gas
Electrical connection	208/240 V 60 HZ 2 PH
Electric heater rating in kW	0.00
Gas heater rating in kW	21.50
Total rated load in kW	1.00
Fuse rating in A	15
Dimensions and weight of dryer	
External dimensions, net height in in. (mm)	55 1/8 (1400)
External dimensions, net width in in. (mm)	35 11/16 (906)

PDR 522 ROP [G]

Professional vented dryer, gas heating

with M Select ROP residual moisture control for perfect drying results.



EAN: 4002516546467 / Material number: 12012250 / Old Material Number: 52522015NAM

External dimensions, net depth in in. (mm)	45 3/4 (1162)
External dimensions, gross height in in. (mm)	60 1/8 (1526)
External dimensions, gross width in in. (mm)	42 15/16 (1090)
External dimensions, gross depth in in. (mm)	49 3/8 (1254)
Net weight in lbs. (kg)	450 (203.9)
Gross weight in lbs. (kg)	481 (218)
Maximum floor load in N/m ²	2570
Emission values	
Emission sound pressure level in the workplace	61 dB(A) re 20 µPa
Heat dissipation into the room in MJ/h	2.60
Features	
Intelligent drum reversal	•
Axial airflow	•
Large-surface lint filter	•
PerfectDry	•
SoftLift drum ribs	•
AirRecycling	•
Communication slot	•
Emergency shut-off	•
Machine-independent accessories	•
Connection options	
Payment system (optional)	•
Optical interface for service access	•
Peak-load negotiation / energy management (optional)	•
Wi-Fi dryer	•
Connector Box	•
LAN module (optional)	•
Capacities	
Cleaning cloths, 22 g [number]	364
Horse summer blankets [number]	3
Standards / certs / symbols	
Splash protection IPX4	•
c ETL US	•
Complies with Machinery Directive 2006/42/EC	•