

## PDR 944 [HW] Professional vented dryer, heated with hot water with programmable M Touch Pro controls for the maximum in flexibility.



- Drum volume 28.25 (800.00) ft<sup>3</sup> (l)
  I, load size53 (24.0) lb (kg) kg 71 (32.0) lb (kg) kg
- Unique, gentle fabric care honeycomb drum
- Greatest energy efficiency thanks to Air Recycling Plus
- Precision drying of all fabrics –
  PerfectDry
- Connected for the future using LAN and Wi-Fi

EAN: 4002516546665 / Material number: 12012440 / Old Material Number: 52944025NAM

Construction type and design	
Construction type	Front loader
Product line	Performance Plus
Front	Stainless steel
Load size with a load ratio of 1:32	53 (24.0) lb (kg)
Load size with a load ratio of 1:25	71 (32.0)
Load size with a load ratio of 1:18	100 (45.0)
Drum volume in I	28.25 (800.00) ft <sup>3</sup> (l)
Drying system	Hot water
Door opening [Ø] in in. (mm)	20 1/2 (520)
Door-opening angle in degrees	180
Door hinging	left
Convertible hinging	•
Stainless steel honeycomb drum	Yes
Application	165
Suitable for hotels and restaurants	•
	•
Suitable for retirement and care homes	
Suitable for facility management	
Suitable for dry cleaners	
Suitable for commercial laundromats	• •
Suitable for fire departments and rescue services	•
Suitable for stud farms and stables	•
Suitable for universities, schools, and kindergartens	•
Suitable for hospitals	•
Suitable for sports clubs	•
Suitable for beauty salons, spas, and fitness centres	•
Suitable for medical and dental practices	•
Suitable for the petrochemical industry	•
Suitable for the food-processing industry	•
Suitable for amusement parks and holiday resorts	•
Suitable for public / community facilities	•
Performance data	
Maximum evaporation capacity in l/hour	11 (11) gal (US)/min (l)
Specific energy consumption in kWh/kg	0.56
Program duration in minutes	64
Tested operating hours	20000
Controls	
Control type	M Touch Pro
Programmability	programmable
Program controls	Residual moisture
	controlled
Max. delay start in h	24
Time left display	•
Program sequence indicator	•
Choice of display language	•
Standard electrical connection	
Heating type	Hot water
Electrical connection	208/240 V 60 HZ 3 PH
Electric heater rating in kW	0.00
Hot water heater rating in kW	12.50



## PDR 944 [HW] Professional vented dryer, heated with hot water with programmable M Touch Pro controls for the maximum in flexibility.



Total rated load in kW 1.70 Fuse rating in A 15 Maximum water intake temperature in °C 90 Dimensions and weight of dryer External dimensions, net height in in. (mm) 64 5/8 (1640) External dimensions, net width in in. (mm) 47 1/2 (1206) External dimensions, net depth in in. (mm) 54 9/16 (1385) External dimensions, gross height in in. (mm) 69 9/16 (1766) External dimensions, gross width in in. (mm) 54 3/4 (1390) External dimensions, gross depth in in. (mm) 58 1/16 (1474) Net weight in lbs. (kg) 720 (326.3) Gross weight in lbs. (kg) 759 (344) Maximum floor load in N/m<sup>2</sup> 4094 Emission values 63 dB(A) re 20 µPa Emission sound pressure level in the workplace 4.00 Heat dissipation into the room in MJ/h Features Intelligent drum reversal • Axial airflow • Large-surface lint filter • PerfectDry • SoftLift drum ribs • AirRecycling • Communication slot • Program selection via colour frame • Emergency shut-off • Machine-independent accessories • **Connection options** Payment system (optional) • Optical interface for service access • Peak-load negotiation / energy management (optional) • Wi-Fi dryer • Connector Box • LAN module (optional) • Capacities 16 Breathing masks [number] Protective suits [number] 6 Protective coats [number] 9 Synthetic duvets [number] 4 Synthetic pillows [number] 8 Down comforters [number] 4 Down pillows [number] 8 Cleaning cloths, 22 g [number] 727 Cotton mops, 40 cm [number] 95 Cotton mops, 50 cm [number] 82 Microfibre mops, 40 cm [number] 150 Microfibre mops, 50 cm [number] 131 Horse summer blankets [number] 5 Standards / certs / symbols Splash protection IPX4 ٠ c ETL US •

EAN: 4002516546665 / Material number: 12012440 / Old Material Number: 52944025NAM



PDR 944 [HW] Professional vented dryer, heated with hot water with programmable M Touch Pro controls for the maximum in flexibility.



EAN: 4002516546665 / Material number: 12012440 / Old Material Number: 52944025NAM

•

Complies with Machinery Directive 2006/42/EC