Miele

PW 6241 [SI MF]

Washing machine, steam heating (indirect)

With liquid dispenser and individually programmable controls.



- Drum volume 8.48 (240) ft³ (I) I, load size 55 (24.5) lb (kg)
- Large program variety application-specific wash programs
- Gentle laundry care thanks to the Miele honeycomb drum
- Particularly efficient low water and energy consumption
- Perfect spinning results residual moisture 43 %*, g-factor541

EAN: 4002516584810 / Material number: 12088640 / Old Material Number: 51624187NAM

Construction type and design	
Construction type	Front loader
Product line	Professional
Front	Stainless steel
Control panel colour	Stainless steel
Load ratio	1:10
Load in lbs. (kg)	55 (24.5)
Drum volume in I	8.48 (240) ft ³ (l)
Door opening [Ø] in in. (mm)	16 15/16 (430)
Door-opening angle in degrees	180
Door hinging	right
Maintenance-free motor with frequency converter	•
Honeycomb drum	•
Application	
Suitable for hotels and restaurants	•
Suitable for retirement and care homes	•
Suitable for facility management	•
Suitable for dry cleaners	•
Suitable for commercial laundromats	•
Suitable for fire departments and rescue services	•
Suitable for stud farms and stables	•
Suitable for universities, schools, and kindergartens	•
Suitable for hospitals	•
Suitable for sports clubs	•
Suitable for beauty salons, spas, and fitness centres	•
Suitable for the petrochemical industry	•
Performance data	
Tested virucidal efficacy	•
Proven hygiene	•
Specific water consumption for cold water connection in I/	9.00
kg	
Specific energy consumption for cold water connection in kWh/kg	0.26
Specific water consumption for hot water connection in I/kg	8.80
Specific energy consumption for hot water connection in kWh/kg	0.10
Water consumption with cold water connection in I	216.0
Energy consumption with cold water connection in kWh	6.24
Energy consumption for cold water connection in Mops standard 60°C program in kWh	6.56
Program duration with cold water connection in minutes	55
Water consumption with hot water connection in I	211.0
Water consumption for hot water connection in Mops	276.1
standard 60°C program in I	
Energy consumption with hot water connection in kWh	2.40
Energy consumption for hot water connection in Mops standard 60°C program in kWh	1.66
Program duration with hot water connection in minutes	47
Water consumption in Economy program with cold water connection in I	212.3

^{*} Residual moisture specification relates to a hot rinse during the last rinse cycle.

Miele

PW 6241 [SI MF]

Washing machine, steam heating (indirect)

With liquid dispenser and individually programmable controls.



EAN: 4002516584810 / Material number: 12088640 / Old Material Number: 51624187NAM

Energy consumption in Economy program with cold water connection in kWh	5.04
Program duration with cold water connection in Economy program in minutes	46
Water consumption in Economy program with hot water connection in I	212.5
Energy consumption in Economy program with hot water connection in kWh	1.44
Program duration with hot water connection in Economy program in minutes	36
Program cycle time in minutes for Mops standard 60°C program with cold water connection	70
Program cycle time in minutes for Mops standard 60°C program with hot water connection	53
Residual moisture with cold rinse in %	46
Residual moisture with	43
hot rinse in %	
Residual moisture when reprocessing wiping cloths in %	25
Spin speed in rpm	1100
g-factor	541
Tested operating hours	30000
Controls	
Control type	Profitronic M
Programmability	Freely programmable
Max. delay start in h	Can be selected freely
Time left display	•
Program sequence indicator	•
Choice of display language	•
Option to enter weight prior to start of program	•
Option to enter weight phor to start or program	
Standard / target grp programs	
	•
Standard / target grp programs	•
Standard / target grp programs Basic programs	• 3 compartments
Standard / target grp programs Basic programs Dispensing	3 compartments
Standard / target grp programs Basic programs Dispensing Detergent drawer	3 compartments 12
Standard / target grp programs Basic programs Dispensing Detergent drawer Liquid dispensing module Maximum number of connections for liquid dispenser	•
Standard / target grp programs Basic programs Dispensing Detergent drawer Liquid dispensing module Maximum number of connections for liquid dispenser pumps [number]	•
Standard / target grp programs Basic programs Dispensing Detergent drawer Liquid dispensing module Maximum number of connections for liquid dispenser pumps [number] Empty sensing	•
Standard / target grp programs Basic programs Dispensing Detergent drawer Liquid dispensing module Maximum number of connections for liquid dispenser pumps [number] Empty sensing Standard electrical connection	12
Standard / target grp programs Basic programs Dispensing Detergent drawer Liquid dispensing module Maximum number of connections for liquid dispenser pumps [number] Empty sensing Standard electrical connection Heating type	• 12 • Indirect steam
Standard / target grp programs Basic programs Dispensing Detergent drawer Liquid dispensing module Maximum number of connections for liquid dispenser pumps [number] Empty sensing Standard electrical connection Heating type Electrical connection Steam heater rating in kW	• 12 • Indirect steam 208/240 V 60 HZ 3 PH
Standard / target grp programs Basic programs Dispensing Detergent drawer Liquid dispensing module Maximum number of connections for liquid dispenser pumps [number] Empty sensing Standard electrical connection Heating type Electrical connection Steam heater rating in kW Total rated load in kW	• 12 • Indirect steam 208/240 V 60 HZ 3 PH 50.00 4.40
Standard / target grp programs Basic programs Dispensing Detergent drawer Liquid dispensing module Maximum number of connections for liquid dispenser pumps [number] Empty sensing Standard electrical connection Heating type Electrical connection Steam heater rating in kW Total rated load in kW Fuse rating in A	• 12 • Indirect steam 208/240 V 60 HZ 3 PH 50.00
Standard / target grp programs Basic programs Dispensing Detergent drawer Liquid dispensing module Maximum number of connections for liquid dispenser pumps [number] Empty sensing Standard electrical connection Heating type Electrical connection Steam heater rating in kW Total rated load in kW Fuse rating in A Water connection/drainage	• 12 • Indirect steam 208/240 V 60 HZ 3 PH 50.00 4.40 15
Standard / target grp programs Basic programs Dispensing Detergent drawer Liquid dispensing module Maximum number of connections for liquid dispenser pumps [number] Empty sensing Standard electrical connection Heating type Electrical connection Steam heater rating in kW Total rated load in kW Fuse rating in A Water connection/drainage Cold water [number]	• 12 • Indirect steam 208/240 V 60 HZ 3 PH 50.00 4.40
Standard / target grp programs Basic programs Dispensing Detergent drawer Liquid dispensing module Maximum number of connections for liquid dispenser pumps [number] Empty sensing Standard electrical connection Heating type Electrical connection Steam heater rating in kW Total rated load in kW Fuse rating in A Water connection/drainage	• 12 • Indirect steam 208/240 V 60 HZ 3 PH 50.00 4.40 15 3 x 1/2" hose w/ 3/4" union
Standard / target grp programs Basic programs Dispensing Detergent drawer Liquid dispensing module Maximum number of connections for liquid dispenser pumps [number] Empty sensing Standard electrical connection Heating type Electrical connection Steam heater rating in kW Total rated load in kW Fuse rating in A Water connection/drainage Cold water [number]	• 12 • Indirect steam 208/240 V 60 HZ 3 PH 50.00 4.40 15 3 x 1/2" hose w/ 3/4" union 1x 1/2" hose w/ 3/4" th.
Standard / target grp programs Basic programs Dispensing Detergent drawer Liquid dispensing module Maximum number of connections for liquid dispenser pumps [number] Empty sensing Standard electrical connection Heating type Electrical connection Steam heater rating in kW Total rated load in kW Fuse rating in A Water connection/drainage Cold water [number]	Indirect steam 208/240 V 60 HZ 3 PH 50.00 4.40 15 3 x 1/2" hose w/ 3/4" union 1x 1/2" hose w/ 3/4" th. union
Standard / target grp programs Basic programs Dispensing Detergent drawer Liquid dispensing module Maximum number of connections for liquid dispenser pumps [number] Empty sensing Standard electrical connection Heating type Electrical connection Steam heater rating in kW Total rated load in kW Fuse rating in A Water connection/drainage Cold water [number] Hot water [number]	Indirect steam 208/240 V 60 HZ 3 PH 50.00 4.40 15 3 x 1/2" hose w/ 3/4" union 1x 1/2" hose w/ 3/4" th. union
Standard / target grp programs Basic programs Dispensing Detergent drawer Liquid dispensing module Maximum number of connections for liquid dispenser pumps [number] Empty sensing Standard electrical connection Heating type Electrical connection Steam heater rating in kW Total rated load in kW Fuse rating in A Water connection/drainage Cold water [number] Hot water [number] Drain valve Steam connection	Indirect steam 208/240 V 60 HZ 3 PH 50.00 4.40 15 3 x 1/2" hose w/ 3/4" union 1x 1/2" hose w/ 3/4" th. union DN 70
Standard / target grp programs Basic programs Dispensing Detergent drawer Liquid dispensing module Maximum number of connections for liquid dispenser pumps [number] Empty sensing Standard electrical connection Heating type Electrical connection Steam heater rating in kW Total rated load in kW Fuse rating in A Water connection/drainage Cold water [number] Hot water [number] Drain valve Steam connection Steam connection	Indirect steam 208/240 V 60 HZ 3 PH 50.00 4.40 15 3 x 1/2" hose w/ 3/4" union 1x 1/2" hose w/ 3/4" th. union DN 70



PW 6241 [SI MF]

Washing machine, steam heating (indirect)

With liquid dispenser and individually programmable controls.

EAN: 4002516584810 / Material number: 12088640 / Old Material Number: 51624187NAM

	40.7/0 (4000)
External dimensions, net width in in. (mm)	42 7/8 (1089)
External dimensions, net depth in in. (mm)	51 9/16 (1309)
External dimensions, gross height in in. (mm)	67 3/8 (1710)
External dimensions, gross width in in. (mm)	49 11/16 (1262)
External dimensions, gross depth in in. (mm)	58 (1472)
Net weight in lbs. (kg)	1522 (690.0)
Gross weight in lbs. (kg)	1634 (741)
Maximum floor load in N/m ²	9343
Emission values	
Emission sound pressure level in the workplace	73 dB(A) re 20 μPa
Heat dissipation into the room in MJ/h	4.70
Features	
Patented pre-spin	
Cloths treatment	
Imbalance monitoring	
Temperature monitoring	
Automatic load recognition+	
Volumetric flow meter (optional)	<u> </u>
Communication slot	
Emergency shut-off	•
Machine-independent accessories	<u>•</u>
Efficiency and sustainability	
Recycling rate in %	96
Connection options	
Payment system (optional)	•
Optical interface for service access	<u>•</u>
Serial interface module RS 232 (optional)	<u>•</u>
Peak-load negotiation / energy management (optional)	
Operating data logging	<u> </u>
Water recovery (optional)	<u> </u>
Capacities	
Breathing masks [number]	20
Helmets [number]	6
Protective suits [number]	4
Protective coats [number]	6
Chemical protection suits [number]	2
Synthetic duvets [number]	2
Synthetic pillows [number]	4
Down comforters [number]	2
Down pillows [number]	4
Cleaning cloths, 22 g [number]	578
Cotton mops, 40 cm / 190 g [number]	126
Cotton mops, 50 cm / 220 g [number]	112
Microfibre mops, 40 cm / 120 g [number]	223
Microfibre mops, 50 cm / 170 g [number]	146
Mops, office, 100 g [number]	233
Mops, stairway, 150 g [number]	155
Horse summer blankets [number]	4
Standards / certs / symbols	
Splash protection IPX4	•
c ETL US	•
	-

Miele

PW 6241 [SI MF]

Washing machine, steam heating (indirect)
With liquid dispenser and individually programmable controls.



EAN: 4002516584810 / Material number: 12088640 / Old Material Number: 51624187NAM

Complies with Machinery Directive 2006/42/EC