Miele

PW 6241 [EL] Washing machine, electric heating With liquid dispenser and individually programmable controls.



- Drum volume 8.48 (240) ft³ (I) I, load size 55 (24.5) lb (kg)
- Large program variety application-specific wash programs
- Gentle laundry care thanks to the Miele honeycomb drum
- Particularly efficient low water and energy consumption
- Perfect spinning results residual moisture 43 %*, g-factor541

Construction type and design	
Construction type and design	Front loader
Product line	Professional
Front	Stainless steel
Control panel colour	Stainless steel 1:10
Load ratio	
Load in lbs. (kg)	55 (24.5)
Drum volume in I	8.48 (240) ft ³ (l)
Door opening [Ø] in in. (mm)	16 15/16 (430)
Door-opening angle in degrees	180
Door hinging	right
Maintenance-free motor with frequency converter	•
Honeycomb drum	•
Application	
Suitable for hotels and restaurants	•
Suitable for retirement and care homes	•
Suitable for facility management	•
Suitable for dry cleaners	•
Suitable for commercial laundromats	•
Suitable for fire departments and rescue services	•
Suitable for stud farms and stables	•
Suitable for universities, schools, and kindergartens	•
Suitable for hospitals	•
Suitable for sports clubs	•
Suitable for beauty salons, spas, and fitness centres	•
Performance data	
Tested virucidal efficacy	•
Proven hygiene	•
Specific water consumption for cold water connection in I/	9.00
kg	
Specific energy consumption for cold water connection in kWh/kg	0.26
Specific water consumption for hot water connection in I/kg	8.80
Specific energy consumption for hot water connection in kWh/kg	0.10
Water consumption with cold water connection in I	216.0
Energy consumption with cold water connection in kWh	6.24
Energy consumption for cold water connection in Mops standard 60°C program in kWh	6.56
Program duration with cold water connection in minutes	60
Water consumption with hot water connection in I	211.0
Water consumption for hot water connection in Mops standard 60°C program in I	276.1
Energy consumption with hot water connection in kWh	2.40
Energy consumption for hot water connection in Mops standard 60°C program in kWh	1.66
Program duration with hot water connection in minutes	49
Program duration with hot water connection in minutes Water consumption in Economy program with cold water connection in I	49 212.3
-	

Residual moisture specification relates to a hot rinse during the last rinse cycle.



PW 6241 [EL] Washing machine, electric heating With liquid dispenser and individually programmable controls.



Program duration with cold water connection in Economy program in minutes	46
Water consumption in Economy program with hot water connection in I	212.5
Energy consumption in Economy program with hot water connection in kWh	1.44
Program duration with hot water connection in Economy program in minutes	36
Program cycle time in minutes for Mops standard 60°C program with cold water connection	74
Program cycle time in minutes for Mops standard 60°C program with hot water connection	57
Residual moisture with cold rinse in %	46
Residual moisture with	43
hot rinse in %	
Residual moisture when reprocessing wiping cloths in %	25
Spin speed in rpm	1100
g-factor	541
Tested operating hours	30000
Controls	
Control type	Profitronic M
Programmability	Freely programmable
Max. delay start in h	Can be selected freely
Time left display	
Program sequence indicator	
Choice of display language	•
Standard / target grp programs	
Basic programs	
Programs for hotels and restaurants	•
Programs for retirement and care homes	
Programs for facility management	
Programs for dry cleaners	
Programs for small businesses	
Programs for fire departments and rescue services	
Programs for stud farms / riding schools / stables	
Programs for hospitals	
Programs for sports clubs	
Programs for salons, spas, and fitness centres	•
Dispensing	
Detergent drawer	3 compartments
Liquid dispensing module	
Maximum number of connections for liquid dispenser pumps [number]	12
Empty sensing	•
Standard electrical connection	
Heating type	Electric
Electrical connection	440/480 V 60 HZ 3 PH
Heater rating in kW	22.60
Total rated load in kW	25.30
Fuse rating in A	35
Water connection/drainage	0 4/0 1 / 2/1
Cold water [number]	3 x 1/2" hose w/ 3/4" union



PW 6241 [EL]
Washing machine, electric heating
With liquid dispenser and individually programmable controls.

Hot water [number]	1x 1/2" hose w/ 3/4" th.
	union
Drain valve	DN 70
Dimensions and weight	
External dimensions, net height in in. (mm)	64 13/16 (1646)
External dimensions, net width in in. (mm)	42 7/8 (1089)
External dimensions, net depth in in. (mm)	49 5/16 (1252)
External dimensions, gross height in in. (mm)	67 3/8 (1710)
External dimensions, gross width in in. (mm)	49 11/16 (1262)
External dimensions, gross depth in in. (mm)	58 (1472)
Net weight in lbs. (kg)	1447 (656.0)
Gross weight in lbs. (kg)	1559 (707)
Maximum floor load in N/m ²	9010
Emission values	
Emission sound pressure level in the workplace	73 dB(A) re 20 µPa
Heat dissipation into the room in MJ/h	4.70
Features	
Patented pre-spin	•
Cloths treatment	•
Imbalance monitoring	•
Temperature monitoring	•
Special heater element	•
Automatic load recognition+	•
Volumetric flow meter (optional)	•
Communication slot	•
Emergency shut-off	•
Machine-independent accessories	•
Efficiency and sustainability	
Recycling rate in %	96
Connection options	
Payment system (optional)	•
Optical interface for service access	•
Serial interface module RS 232 (optional)	•
Peak-load negotiation / energy management (optional)	•
Operating data logging	•
Water recovery (optional)	•
Capacities	
Breathing masks [number]	20
Helmets [number]	6
Protective suits [number]	4
Protective coats [number]	6
Chemical protection suits [number]	2
Synthetic duvets [number]	2
, ,	4
Synthetic pillows [number] Down comforters [number]	2
. ,	
Down pillows [number]	<u>4</u>
Cleaning cloths, 22 g [number]	578
Cotton mops, 40 cm / 190 g [number]	126
Cotton mops, 50 cm / 220 g [number]	112
Microfibre mops, 50 cm / 170 g [number]	146
Mops, office, 100 g [number]	233



PW 6241 [EL] Washing machine, electric heating With liquid dispenser and individually programmable controls.



Mops, stairway, 150 g [number]	155
Horse summer blankets [number]	4
Standards / certs / symbols	
Splash protection IPX4	•
c ETL US	•
Complies with Machinery Directive 2006/42/EC	•