



- Drum volume 8.48 (240) ft³ (I) I, load size 55 (24.5) lb (kg)
- Large program variety application-specific wash programs
- Gentle laundry care thanks to the Miele honeycomb drum
- Particularly efficient low water and energy consumption
- Perfect spinning results residual moisture 43 %^{*}, g-factor541

Residual moisture specification relates to a hot rinse during the last rinse cycle.

Construction type and design	
Construction type and design	Front looder
Construction type	Front loader Professional
Product line	· · · · · · · · · · · · · · · · · · ·
Front	Iron grey
Control panel colour	Stainless steel
Load ratio	1:10
Load in lbs. (kg)	55 (24.5)
Drum volume in I	8.48 (240) ft ³ (l)
Door opening [Ø] in in. (mm)	16 15/16 (430)
Door-opening angle in degrees	180
Door hinging	right
Maintenance-free motor with frequency converter	•
Honeycomb drum	•
Application	
Suitable for hotels and restaurants	•
Suitable for retirement and care homes	•
Suitable for facility management	•
Suitable for dry cleaners	•
Suitable for commercial laundromats	•
Suitable for fire departments and rescue services	•
Suitable for stud farms and stables	•
Suitable for universities, schools, and kindergartens	•
Suitable for hospitals	•
Suitable for sports clubs	•
Suitable for beauty salons, spas, and fitness centres	•
· · ·	
Performance data	
Performance data Tested virucidal efficacy	•
Tested virucidal efficacy	•
Tested virucidal efficacy Proven hygiene	•
Tested virucidal efficacy	• • 9.00
Tested virucidal efficacy Proven hygiene Specific water consumption for cold water connection in l/ kg	•
Tested virucidal efficacy Proven hygiene Specific water consumption for cold water connection in l/	• 9.00
Tested virucidal efficacy Proven hygiene Specific water consumption for cold water connection in l/ kg Specific energy consumption for cold water connection in	• 9.00
Tested virucidal efficacy Proven hygiene Specific water consumption for cold water connection in I/ kg Specific energy consumption for cold water connection in kWh/kg	• 9.00 0.26
Tested virucidal efficacy Proven hygiene Specific water consumption for cold water connection in l/ kg Specific energy consumption for cold water connection in kWh/kg Specific water consumption for hot water connection in l/kg	• 9.00 0.26 8.80
Tested virucidal efficacy Proven hygiene Specific water consumption for cold water connection in I/ kg Specific energy consumption for cold water connection in kWh/kg Specific water consumption for hot water connection in I/kg Specific energy consumption for hot water connection in	• 9.00 0.26 8.80
Tested virucidal efficacy Proven hygiene Specific water consumption for cold water connection in l/ kg Specific energy consumption for cold water connection in kWh/kg Specific energy consumption for hot water connection in l/kg Specific energy consumption for hot water connection in kWh/kg	• 9.00 0.26 8.80 0.10
Tested virucidal efficacy Proven hygiene Specific water consumption for cold water connection in I/ kg Specific energy consumption for cold water connection in kWh/kg Specific energy consumption for hot water connection in kWh/kg Water consumption with cold water connection in I	• 9.00 0.26 8.80 0.10 216.0
Tested virucidal efficacy Proven hygiene Specific water consumption for cold water connection in I/ kg Specific energy consumption for cold water connection in kWh/kg Specific energy consumption for hot water connection in kWh/kg Water consumption with cold water connection in I Energy consumption with cold water connection in kWh Energy consumption for cold water connection in Mops standard 60°C program in kWh	• 9.00 0.26 8.80 0.10 216.0 6.24
Tested virucidal efficacy Proven hygiene Specific water consumption for cold water connection in I/ kg Specific energy consumption for cold water connection in kWh/kg Specific energy consumption for hot water connection in I/kg Specific energy consumption for hot water connection in kWh/kg Water consumption with cold water connection in I Energy consumption with cold water connection in kWh Energy consumption for cold water connection in Mops	• 9.00 0.26 8.80 0.10 216.0 6.24
Tested virucidal efficacy Proven hygiene Specific water consumption for cold water connection in I/ kg Specific energy consumption for cold water connection in kWh/kg Specific energy consumption for hot water connection in kWh/kg Water consumption with cold water connection in I Energy consumption with cold water connection in kWh Energy consumption for cold water connection in Mops standard 60°C program in kWh	• 9.00 0.26 8.80 0.10 216.0 6.24 6.56
Tested virucidal efficacy Proven hygiene Specific water consumption for cold water connection in I/ kg Specific energy consumption for cold water connection in kWh/kg Specific energy consumption for hot water connection in I/kg Specific energy consumption for hot water connection in kWh/kg Water consumption with cold water connection in I Energy consumption with cold water connection in kWh Energy consumption for cold water connection in Mops standard 60°C program in kWh Program duration with cold water connection in minutes	• 9.00 0.26 8.80 0.10 216.0 6.24 6.56 60
Tested virucidal efficacy Proven hygiene Specific water consumption for cold water connection in I/ kg Specific energy consumption for cold water connection in kWh/kg Specific water consumption for hot water connection in I/kg Specific energy consumption for hot water connection in kWh/kg Water consumption with cold water connection in I Energy consumption with cold water connection in kWh Energy consumption for cold water connection in Mops standard 60°C program in kWh Program duration with cold water connection in minutes Water consumption with hot water connection in I	• 9.00 0.26 8.80 0.10 216.0 6.24 6.56 60 211.0
Tested virucidal efficacy Proven hygiene Specific water consumption for cold water connection in I/ kg Specific energy consumption for cold water connection in kWh/kg Specific water consumption for hot water connection in I/kg Specific energy consumption for hot water connection in kWh/kg Water consumption with cold water connection in I Energy consumption with cold water connection in kWh Energy consumption for cold water connection in Mops standard 60°C program in kWh Program duration with cold water connection in minutes Water consumption with hot water connection in I Water consumption for hot water connection in I	• 9.00 0.26 8.80 0.10 216.0 6.24 6.56 60 211.0
Tested virucidal efficacy Proven hygiene Specific water consumption for cold water connection in I/ kg Specific energy consumption for cold water connection in kWh/kg Specific energy consumption for hot water connection in I/kg Specific energy consumption for hot water connection in I/kg Specific energy consumption for hot water connection in I kWh/kg Water consumption with cold water connection in I Energy consumption with cold water connection in KWh Energy consumption for cold water connection in Mops standard 60°C program in kWh Program duration with cold water connection in minutes Water consumption with hot water connection in I Water consumption for hot water connection in Mops standard 60°C program in I	• 9.00 0.26 8.80 0.10 216.0 6.24 6.56 60 211.0 276.1
Tested virucidal efficacy Proven hygiene Specific water consumption for cold water connection in I/ kg Specific energy consumption for cold water connection in kWh/kg Specific energy consumption for hot water connection in I/kg Specific energy consumption for hot water connection in kWh/kg Water consumption with cold water connection in I Energy consumption with cold water connection in KWh Energy consumption for cold water connection in Mops standard 60°C program in kWh Program duration with hot water connection in I Water consumption for hot water connection in Mops standard 60°C program in I Water consumption for hot water connection in Mops standard 60°C program in I Energy consumption with hot water connection in KWh Energy consumption with hot water connection in KWh	
Tested virucidal efficacy Proven hygiene Specific water consumption for cold water connection in I/ kg Specific energy consumption for cold water connection in kWh/kg Specific energy consumption for hot water connection in I/kg Specific energy consumption for hot water connection in kWh/kg Water consumption with cold water connection in I Energy consumption for cold water connection in KWh Energy consumption for cold water connection in Mops standard 60°C program in kWh Program duration with hot water connection in Mops standard 60°C program in I Energy consumption for hot water connection in Mops standard 60°C program in I Energy consumption with hot water connection in kWh Energy consumption for hot water connection in Mops standard 60°C program in I Energy consumption for hot water connection in Mops standard 60°C program in KWh	
Tested virucidal efficacy Proven hygiene Specific water consumption for cold water connection in I/ kg Specific energy consumption for cold water connection in kWh/kg Specific energy consumption for hot water connection in I/kg Specific energy consumption for hot water connection in kWh/kg Water consumption with cold water connection in I Energy consumption for cold water connection in kWh Energy consumption for cold water connection in Mops standard 60°C program in kWh Program duration with cold water connection in minutes Water consumption with hot water connection in Mops standard 60°C program in I Energy consumption with hot water connection in kWh Energy consumption for hot water connection in Mops standard 60°C program in I Energy consumption for hot water connection in Mops standard 60°C program in KWh Energy consumption for hot water connection in Mops standard 60°C program in kWh Energy consumption for hot water connection in Mops standard 60°C program in kWh	• 9.00 0.26 8.80 0.10 216.0 6.24 6.56 60 211.0 276.1 2.40 1.66 49
Tested virucidal efficacy Proven hygiene Specific water consumption for cold water connection in I/ kg Specific energy consumption for cold water connection in kWh/kg Specific energy consumption for hot water connection in I/kg Specific energy consumption for hot water connection in kWh/kg Water consumption with cold water connection in I Energy consumption for cold water connection in KWh Energy consumption for cold water connection in Mops standard 60°C program in kWh Program duration with cold water connection in minutes Water consumption for hot water connection in Mops standard 60°C program in I Energy consumption with hot water connection in Mops standard 60°C program in I Energy consumption for hot water connection in Mops standard 60°C program in KWh Energy consumption for hot water connection in Mops standard 60°C program in KWh Energy consumption for hot water connection in Mops standard 60°C program in KWh Energy consumption for hot water connection in Mops standard 60°C program in KWh Program duration with hot water connection in Mops standard 60°C program in KWh	• 9.00 0.26 8.80 0.10 216.0 6.24 6.56 60 211.0 276.1 2.40 1.66 49
Tested virucidal efficacy Proven hygiene Specific water consumption for cold water connection in I/ kg Specific energy consumption for cold water connection in kWh/kg Specific energy consumption for hot water connection in I/kg Specific energy consumption for hot water connection in kWh/kg Water consumption with cold water connection in I Energy consumption for cold water connection in KWh Energy consumption for cold water connection in Mops standard 60°C program in kWh Program duration with cold water connection in minutes Water consumption for hot water connection in Mops standard 60°C program in I Energy consumption with hot water connection in Mops standard 60°C program in I Energy consumption for hot water connection in Mops standard 60°C program in KWh Energy consumption for hot water connection in Mops standard 60°C program in KWh Energy consumption for hot water connection in Mops standard 60°C program in KWh Energy consumption for hot water connection in Mops standard 60°C program in kWh Program duration with hot water connection in Mops standard 60°C program in kWh Program duration with hot water connection in Mops standard 60°C program in kWh	• 9.00 0.26 8.80 0.10 216.0 6.24 6.56 60 211.0 276.1 2.40 1.66 49 212.3





Program duration with cold water connection in Economy program in minutes	46
Water consumption in Economy program with hot water connection in I	212.5
Energy consumption in Economy program with hot water connection in kWh	1.44
Program duration with hot water connection in Economy program in minutes	36
Program cycle time in minutes for Mops standard 60°C program with cold water connection	74
Program cycle time in minutes for Mops standard 60°C program with hot water connection	57
Residual moisture with cold rinse in %	46
Residual moisture with hot rinse in %	43
Residual moisture when reprocessing wiping cloths in %	25
Spin speed in rpm	1100
g-factor	541
Tested operating hours	30000
Controls	
Control type	Profitronic M
Programmability	Freely programmable
Max. delay start in h	Can be selected freely
Time left display	•
Program sequence indicator	•
Choice of display language	•
Standard / target grp programs	
Basic programs	•
Programs for hotels and restaurants	•
Programs for retirement and care homes	•
Programs for facility management	•
Programs for dry cleaners	•
Programs for small businesses	•
Programs for fire departments and rescue services	•
Programs for stud farms / riding schools / stables	•
Programs for hospitals	•
Programs for sports clubs	•
Programs for salons, spas, and fitness centres	•
Dispensing	
Detergent drawer	3 compartments
Maximum number of connections for liquid dispenser	12
pumps [number]	
Empty sensing	•
Standard electrical connection	
Heating type	Electric
Electrical connection	208/240 V 60 HZ 3 PH
Heater rating in kW	24.60
Total rated load in kW	26.20
Fuse rating in A	70
Water connection/drainage	
Water connection/drainage	



Hot water [number]	1x 1/2" hose w/ 3/4" th.	
	union	
Drain valve	DN 70	
Dimensions and weight		
External dimensions, net height in in. (mm)	64 13/16 (1646)	
External dimensions, net width in in. (mm)	42 7/8 (1089)	
External dimensions, net depth in in. (mm)	51 9/16 (1309)	
External dimensions, gross height in in. (mm)	67 3/8 (1710)	
External dimensions, gross width in in. (mm)	49 11/16 (1262)	
External dimensions, gross depth in in. (mm)	58 (1472)	
Net weight in lbs. (kg)	1517 (688.0)	
Gross weight in lbs. (kg)	1630 (739)	
Maximum floor load in N/m ²	9324	
Emission values		
Emission sound pressure level in the workplace	73 dB(A) re 20 µPa	
Heat dissipation into the room in MJ/h	4.70	
Features		
Patented pre-spin	•	
Cloths treatment	•	
Imbalance monitoring	•	
Temperature monitoring	•	
Special heater element	•	
Automatic load recognition+	•	
Volumetric flow meter (optional)	•	
Communication slot	•	
Emergency shut-off	•	
Machine-independent accessories	•	
Efficiency and sustainability		
Recycling rate in %	96	
Connection options		
Payment system (optional)	•	
Optical interface for service access	•	
Serial interface module RS 232 (optional)	•	
Peak-load negotiation / energy management (optional)	•	
Operating data logging	•	
Water recovery (optional)	•	
Capacities		
Breathing masks [number]	20	
Helmets [number]	6	
Protective suits [number]	4	
Protective coats [number]	6	
Chemical protection suits [number]	2	
Synthetic duvets [number]	2	
Synthetic pillows [number]	4	
Down comforters [number]	2	
	4	
Down pillows [number]		
Cleaning cloths, 22 g [number]	578	
Cotton mops, 40 cm / 190 g [number]	126	
Cotton mops, 50 cm / 220 g [number]		
Microfibre mops, 40 cm / 120 g [number]	223	
Microfibre mops, 50 cm / 170 g [number]	146	





Mops, office, 100 g [number]	233
Mops, stairway, 150 g [number]	155
Horse summer blankets [number]	4
Standards / certs / symbols	
Splash protection IPX4	•
c ETL US	•
Complies with Machinery Directive 2006/42/EC	•