

PT 8407 [PTM EL BSS ARP]

Vented dryer, electrically heated

With individually programmable controls for the maximum in flexibility.



- Drum volume 400.00 l, load size 16.0-20.0 kg
- Unique, gentle fabric care – honeycomb drum
- Excellent energy efficiency thanks to Air Recycling Plus
- Precision drying of all fabrics – PerfectDry
- Simple operation – easy to clean large fluff filter

EAN: 4002515480892 / Material number: 09906720 / Old Material Number: 52840705USA

Construction type and version	
Construction type	Front loader
Range	Professional
Front	Stainless steel
Load in kg	16,0-20,0
Load ratio	1:25-1:20
Drum volume in l	400,00
Drying system	Exhaust air
Door opening [Ø] in mm	520
Door opening angle in degrees	180
Door hinge	left
Convertible door hinging	•
Stainless steel honeycomb drum	Yes
Application	
Suitable for the hotel and catering industry	•
Suitable for retirement and care homes	•
Suitable for facility management	•
Suitable for dry cleaners	•
Suitable for commercial laundries	•
Suitable for fire brigades and rescue services	•
Suitable for studs, riding schools and stables	•
Suitable for universities, nurseries, and schools	•
Suitable for hospitals	•
Suitable for sports clubs	•
Suitable for beauty salons, spas, and fitness centres	•
Performance data	
Maximum evaporation capacity in l/hour	22,10
Programme duration in min.	24
Tested operating hours	20000
Control system	
Control system	Profitronic M
Programmability	Freely programmable
User interface	Residual moisture controlled
Max. delay start in h	Freely selectable
Time left display	•
Programme sequence indicator	•
Selectable display languages	•
Standard/target grp programmes	
Basic programmes	•
Programmes for the hotel and catering industry	•
Programmes for retirement and care homes	•
Programmes for facility management	•
Programmes for dry cleaners	•
Programmes for fire brigades and rescue services	•
Programmes for studs, riding schools, and stables	•
Standard electrical connection	
Heating type	Electric
Electrical connection	3 AC 208V 60HZ
Electric heater rating in kW	18,40

PT 8407 [PTM EL BSS ARP]

Vented dryer, electrically heated

With individually programmable controls for the maximum in flexibility.



EAN: 4002515480892 / Material number: 09906720 / Old Material Number: 52840705USA

Total connected load in kW	19,70
Fuse rating in A	65
Possible voltage variant 1	
Electrical connection	3 AC 220-240V 60HZ
Heater rating in kW	20,60-24,50
Total connected load in kW	21,90-25,80
Fuse rating in A	65
Dimensions and weight	
External dimensions, height in mm	1400
External dimensions, width in mm	906
External dimensions, depth in mm	1164
External dimensions, gross height in mm	1526
External dimensions, gross width in mm	1090
External dimensions, gross depth in mm	1254
Net weight in kg	191,5
Gross weight in kg	215
Maximum floor load in N/m ²	2163
Emissions data	
Emission sound pressure level in the workplace	<70 dB(A) re 20 µPa
Heat dissipation into the room in MJ/h	2,64
Features	
Intelligent drum reversal	•
Axial airflow	•
Large-surface fluff filter	•
PerfectDry	•
SoftLift drum ribs	•
AirRecyclingPlus	•
Low temperature function	•
Communication slot	•
Emergency switch-off	•
Machine-independent accessories	•
Connection options	
Payment system (optional)	•
Serial interface RS 232 (optional)	•
Optical interface for service access	•
Peak load cut-out/energy management	•
Operating data acquisition	•
Capacities	
Respirator masks [number]	16
Overalls [number]	3
Over jackets [number]	4
Synthetic duvets [number]	2
Synthetic pillows [number]	4
Down duvets [number]	2
Down pillows [number]	4
Cloths, 22 g [number]	370
Cotton mops, 40 cm [number]	84
Cotton mops, 50 cm [number]	73
Microfibre mops, 40 cm [number]	133
Microfibre mops, 50 cm [number]	94
Summer horse blankets [number]	2-3
Standards, test certificates and symbols	
CE	•

PT 8407 [PTM EL BSS ARP]

Vented dryer, electrically heated

With individually programmable controls for the maximum in flexibility.