

## K 31222 Ui Built-under refrigerator Compactly designed with a practical interior layout.




- Optimum and maintenance-free LED lighting in compartment
- Door shelves can be cleaned in the dishwasher ComfortClean


EAN: 4002515952573 / Material number: 10799710 / Old Material Number: 36312220AUS

| Appliance category   |  |
|--|--|
| Refrigerator   | •  |
| Construction type  |  |
| Built-in appliance   |  |
| Undercounter appliance   | •  |
| Door hinge   | right  |
| Convertible door hinging   | •  |
| Design   |  |
| Refrigeration section lighting   | LED  |
| User convenience   |  |
| ComfortClean   | •  |
| Controls   |  |
| Operating concept  | PicTronic  |
| Independent temperature regulation of fridge and freezer zones   | No   |
| Automatic SuperCool  | •  |
| No. of temperature zones   | 1  |
| Fridge/Fridge section  | ·  |
| No. of shelves   | 4  |
| Number of inner door racks for tinned food   | 1  |
| Door rack for bottles  | 1  |
| Safety   | _  |
| Lock function  | •  |
| Acoustic door alarm  | •  |
| Technical data   |  |
| Niche width in mm min.   | 600  |
| Niche width in mm max.   | 600  |
| Niche widin in min max.  | - 600  |
| Nicha baight in mm min   | 000  |
| Niche height in mm min.  | 820  |
| Niche height in mm max.  | 880  |
| Niche height in mm max. Niche depth in mm  | 880<br>550   |
| Niche height in mm max.  Niche depth in mm  Appliance width in mm  | 880<br>550<br>597  |
| Niche height in mm max.  Niche depth in mm  Appliance width in mm  Appliance height in mm  | 880<br>550<br>597<br>820   |
| Niche height in mm max.  Niche depth in mm  Appliance width in mm  Appliance height in mm  Appliance depth in mm   | 880<br>550<br>597<br>820<br>550  |
| Niche height in mm max.  Niche depth in mm  Appliance width in mm  Appliance height in mm  Appliance depth in mm  Weight in kg   | 880<br>550<br>597<br>820<br>550<br>33,5  |
| Niche height in mm max.  Niche depth in mm  Appliance width in mm  Appliance height in mm  Appliance depth in mm  Weight in kg  Door hinge technology  | 880<br>550<br>597<br>820<br>550<br>33,5<br>Fixed door  |
| Niche height in mm max.  Niche depth in mm  Appliance width in mm  Appliance height in mm  Appliance depth in mm  Weight in kg  Door hinge technology  Max. door front weight – refrigerator, in kg  | 880<br>550<br>597<br>820<br>550<br>33,5<br>Fixed door<br>10  |
| Niche height in mm max.  Niche depth in mm  Appliance width in mm  Appliance height in mm  Appliance depth in mm  Weight in kg  Door hinge technology  Max. door front weight – refrigerator, in kg  Climate class   | 880<br>550<br>597<br>820<br>550<br>33,5<br>Fixed door<br>10<br>SN-T                                      |
| Niche height in mm max.  Niche depth in mm  Appliance width in mm  Appliance height in mm  Appliance depth in mm  Weight in kg  Door hinge technology  Max. door front weight – refrigerator, in kg  Climate class  Total usable capacity in I   | 880<br>550<br>597<br>820<br>550<br>33,5<br>Fixed door<br>10<br>SN-T<br>136                               |
| Niche height in mm max.  Niche depth in mm  Appliance width in mm  Appliance height in mm  Appliance depth in mm  Weight in kg  Door hinge technology  Max. door front weight – refrigerator, in kg  Climate class  Total usable capacity in I  Current consumption (mA)   | 880<br>550<br>597<br>820<br>550<br>33,5<br>Fixed door<br>10<br>SN-T<br>136<br>1200                       |
| Niche height in mm max.  Niche depth in mm  Appliance width in mm  Appliance height in mm  Appliance depth in mm  Weight in kg  Door hinge technology  Max. door front weight – refrigerator, in kg  Climate class  Total usable capacity in I  Current consumption (mA)  Voltage in V   | 880<br>550<br>597<br>820<br>550<br>33,5<br>Fixed door<br>10<br>SN-T<br>136<br>1200<br>220-240            |
| Niche height in mm max.  Niche depth in mm  Appliance width in mm  Appliance height in mm  Appliance depth in mm  Weight in kg  Door hinge technology  Max. door front weight – refrigerator, in kg  Climate class  Total usable capacity in I  Current consumption (mA)  Voltage in V  Fuse rating in A   | 880<br>550<br>597<br>820<br>550<br>33,5<br>Fixed door<br>10<br>SN-T<br>136<br>1200<br>220-240<br>10      |
| Niche height in mm max.  Niche depth in mm  Appliance width in mm  Appliance height in mm  Appliance depth in mm  Weight in kg  Door hinge technology  Max. door front weight – refrigerator, in kg  Climate class  Total usable capacity in I  Current consumption (mA)  Voltage in V  Fuse rating in A  Number of phases   | 880<br>550<br>597<br>820<br>550<br>33,5<br>Fixed door<br>10<br>SN-T<br>136<br>1200<br>220-240<br>10      |
| Niche height in mm max.  Niche depth in mm  Appliance width in mm  Appliance height in mm  Appliance depth in mm  Weight in kg  Door hinge technology  Max. door front weight – refrigerator, in kg  Climate class  Total usable capacity in I  Current consumption (mA)  Voltage in V  Fuse rating in A  Number of phases  Frequency in Hz  | 880<br>550<br>597<br>820<br>550<br>33,5<br>Fixed door<br>10<br>SN-T<br>136<br>1200<br>220-240<br>10<br>1 |
| Niche height in mm max.  Niche depth in mm  Appliance width in mm  Appliance height in mm  Appliance depth in mm  Weight in kg  Door hinge technology  Max. door front weight – refrigerator, in kg  Climate class  Total usable capacity in I  Current consumption (mA)  Voltage in V  Fuse rating in A  Number of phases  Frequency in Hz  Length of supply lead in m                  | 880<br>550<br>597<br>820<br>550<br>33,5<br>Fixed door<br>10<br>SN-T<br>136<br>1200<br>220-240<br>10      |
| Niche height in mm max.  Niche depth in mm  Appliance width in mm  Appliance height in mm  Appliance depth in mm  Weight in kg  Door hinge technology  Max. door front weight – refrigerator, in kg  Climate class  Total usable capacity in I  Current consumption (mA)  Voltage in V  Fuse rating in A  Number of phases  Frequency in Hz  Length of supply lead in m  Replacing lamps | 880<br>550<br>597<br>820<br>550<br>33,5<br>Fixed door<br>10<br>SN-T<br>136<br>1200<br>220-240<br>10<br>1 |
| Niche height in mm max.  Niche depth in mm  Appliance width in mm  Appliance height in mm  Appliance depth in mm  Weight in kg  Door hinge technology  Max. door front weight – refrigerator, in kg  Climate class  Total usable capacity in I  Current consumption (mA)  Voltage in V  Fuse rating in A  Number of phases  Frequency in Hz  Length of supply lead in m                  | 880 550 597 820 550 33,5 Fixed door 10 SN-T 136 1200 220-240 10 1 50                                     |




## K 31222 Ui Built-under refrigerator Compactly designed with a practical interior layout.





K31222Ui, K31222Ui-1, K31225Ui, K31252Ui, K31252Ui-1, K31242UiF, K31242UiF-1, F31202Ui (installation drawings) K31222Ui, K31222Ui-1, K31225Ui, K31252Ui, K31252Ui-1, K31242UiF, K31242UiF-1, F31202Ui, side view (installation draw)



K31222Ui, K31222Ui-1, K31225Ui, K31252Ui, K31252Ui-1, K31242UiF, K31242UiF-1 F31202Ui (installation drawings)