

ESW 7020 29 cm high handleless Gourmet warming drawer for preheating crockery, keeping food warm and low temperature cooking.



- The ultimate in enjoyment low temperature cooking
- Always at the right temperature 4 functions
- Convenient and easy Touch control
- Opening the drawer couldn't be easier Push2open
- Better safe than sorry timer function with automatic switch-off

EAN: 4002516169475 / Material number: 11093300 / Old Material Number: 30702030GB

ourmet warming drawer	•
itroLine	•
rtLine	•
andleless	•
olour	Graphite grey
perating modes	
up warming	•
late warming	•
eeping food warm	•
ow temperature cooking	•
ser convenience	
liele@home	•
apacity	12 place settings
ush2open mechanism	•
ully telescopic runners for easy loading and unloading of	•
ne warming drawer	
ontrol panel with sensor controls	•
ontrol panel with symbols	•
top programming	•
imer function	•
abbath programme	•
fficiency and sustainability	
ower rating in off mode in W	0,5
ower rating in standby mode in W	1,0
ower rating in networked standby in W	2,0
ime until automatic switch to off mode in min	20
me until automatic switch to standby in min	20
me until automatic switch to networked standby in min	20
leaning and care	20
ush control panel	•
afety	
ool front	•
nti-slip mat	•
afety switch-off	•
echnical data	
emperatures min. in °C	40
	85
emperatures max. in °C	<u>85</u>
ppliance width in mm	
ppliance height in mm	289
ppliance depth in mm	570
seable interior height in mm	230
otal rated load in kW	0,70
oltage in V	
requency in Hz	50-60
use rating in A	
umber of phases	
lains cable with plug	•



ESW 7020 29 cm high handleless Gourmet warming drawer for preheating crockery, keeping food warm and low temperature cooking.



EAN: 4002516169475 / Material number: 11093300 / Old Material Number: 30702030GB


Accessories included	
Anti-slip mat	1
Rack for increased capacity	1




ESW 7020

29 cm high handleless Gourmet warming drawer


for preheating crockery, keeping food warm and low temperature cooking.






ESW7x20, DGC7x4xHCPro, DGC7x4xHCXPro installation drawings


ESW7x20, DG7xxx, DGM7xxx installation drawings



ESW7x20, DGM7x4x installation drawings


1) Front view, 2) Mains connection cable, L=2.000 mm, 3) Ventilation cut min. 180 cm², 4) No connection in this area





ESW7x20, DGC7x6xHCPro, DGC7x6xHCXPro installation drawings

side view ESW7x20, installation drawing, GB, AU



Installation ESW7x20, installation drawing, GB, AU

1) Front view, 2) Mains connection cable, L=2,000 mm, 3) ventilation cut-out min. 180 $\rm cm^2,$ 4) no connection in this area