

PWM 908 [EL DP MAR 3 AC 400-480V 50-60Hz]

Professional washing machine, Little Giants, electric heating, drain pump Lloyd's Register approved, load size 8.0 kg.



- Drum volume 73 l, load size 8.0 kg
- 22 % less water consumption and 28 % less energy consumption*
- Tested for intensive use unparalleled Miele quality
- Max. user convenience w. fulltouch colour display –M Touch Flex
- Thorough cleaning with professional wash programmes

Based on the Coloured items 60 °C programme with a warm water connection, compared to predecessor.

EAN: 4002516223504 / Material number: 11251290 / Old Material Number: 51908387MAR

ange F ront S control panel colour S oad in kg E rum volume in I 7 oor opening [Ø] in mm 3 oor opening angle in degrees 1 oor hinge r laintenance-free synchronous motor • oneycomb drum with perforated drum rear panel • pplication • uitable for offshore use • erformance data • ested virucidal efficacy • roven hygiene •	Front loader Performance Plus Stainless steel 3,0 73 300 167 right
ront S control panel colour S control panel colour S coad in kg S rum volume in I 7 cor opening [Ø] in mm S cor opening angle in degrees 1 oor hinge 1 diaintenance-free synchronous motor 1 laintenance free synchronous motor 1 uitable for offshore use 1 uitable for marine use 1 erformance data 1 ested virucidal efficacy 1 roven hygiene 1 pecific water consumption for cold water connection in I/	Stainless steel Stainless steel 8,0 73 300 167 right •
control panel colour 5 poad in kg 6 rum volume in l 7 poor opening [Ø] in mm 6 poor opening angle in degrees 1 poor opening angle in degrees 1 poor hinge r daintenance-free synchronous motor 1 loneycomb drum with perforated drum rear panel 1 pplication 1 uitable for offshore use 1 uitable for marine use 1 ested virucidal efficacy 1 roven hygiene 1 pecific water consumption for cold water connection in I/ 6	Stainless steel 8,0 73 300 167 right
back in kg 8 rum volume in I 7 oor opening [Ø] in mm 7 oor opening angle in degrees 1 oor hinge r aintenance-free synchronous motor 9 laintenance-free synchronous motor 9 oplication 9 uitable for offshore use 9 uitable for marine use 9 erformance data 9 ested virucidal efficacy 9 roven hygiene 9 pecific water consumption for cold water connection in I/ 6	8,0 73 300 167 •
rum volume in I 7 ioor opening [Ø] in mm 3 ioor opening angle in degrees 1 ioor hinge r daintenance-free synchronous motor 9 loneycomb drum with perforated drum rear panel 9 pplication 9 uitable for offshore use 9 erformance data 9 ested virucidal efficacy 9 roven hygiene 9 pecific water consumption for cold water connection in I/ 6	73 300 167 •
oor opening [Ø] in mm 3 oor opening angle in degrees 1 oor hinge r laintenance-free synchronous motor 1 loneycomb drum with perforated drum rear panel 1 pplication 1 uitable for offshore use 1 erformance data 1 ested virucidal efficacy 1 roven hygiene 1 pecific water consumption for cold water connection in I/ 1	300 167 •
oor opening angle in degrees 1 oor hinge r laintenance-free synchronous motor • oneycomb drum with perforated drum rear panel • pplication • uitable for offshore use • uitable for marine use • ested virucidal efficacy • roven hygiene • pecific water consumption for cold water connection in I/ •	167 right •
oor hinge r laintenance-free synchronous motor • loneycomb drum with perforated drum rear panel • pplication • uitable for offshore use • uitable for marine use • ested virucidal efficacy • roven hygiene • pecific water consumption for cold water connection in I/ •	right •
Iaintenance-free synchronous motor • Ioneycomb drum with perforated drum rear panel • pplication • uitable for offshore use • uitable for marine use • erformance data • ested virucidal efficacy • roven hygiene • pecific water consumption for cold water connection in I/ •	•
oneycomb drum with perforated drum rear panel • pplication • uitable for offshore use • uitable for marine use • erformance data • ested virucidal efficacy • roven hygiene • pecific water consumption for cold water connection in I/ •	•
pplication • uitable for offshore use • uitable for marine use • erformance data • ested virucidal efficacy • roven hygiene • pecific water consumption for cold water connection in I/ •	•
uitable for offshore use • uitable for marine use • erformance data • ested virucidal efficacy • roven hygiene • pecific water consumption for cold water connection in I/ •	•
uitable for marine use • erformance data • ested virucidal efficacy • roven hygiene • pecific water consumption for cold water connection in I/ •	•
erformance data ested virucidal efficacy roven hygiene pecific water consumption for cold water connection in I/	•
ested virucidal efficacy roven hygiene pecific water consumption for cold water connection in I/	-
roven hygiene pecific water consumption for cold water connection in I/	
roven hygiene pecific water consumption for cold water connection in I/	•
pecific water consumption for cold water connection in I/	•
	6,40
pecific energy consumption for cold water connection in 0 Wh/kg	0,13
pecific water consumption for hot water connection in I/kg	6,00
pecific energy consumption for hot water connection in 0 Wh/kg	0,06
/ater consumption with cold water connection in I	51,0
	1,05
	59
	48,0
	0,50
	49
esidual moisture with cold rinse in %	48
	45
	1600
· · · · · · · · · · · · · · · · · · ·	704
	30000
control system	
•	M Touch Flex
,	orogrammable
	96
ime left display	
· · ·	•
	•
angaago oan oo oolootoa oaoliy at any timo	-
ispensing	
	3 compartments
• • • • • • • • • • • • • • • • • • •	•
	•
	6



PWM 908 [EL DP MAR 3 AC 400-480V 50-60Hz]

Professional washing machine, Little Giants, electric heating, drain pump Lloyd's Register approved, load size 8.0 kg.



Electric 3~ 440V
3~ 440V
4,00
4.20
10
3~ 400V
3,40
3,60
10
3~ 480V 50/60HZ
4,80
5,00
10
1x 1/0" bc==/ 0/4" !!
1x 1/2" hose w/ 3/4" th. union
1x 1/2" hose w/ 3/4" th.
union
DN 22
DNZZ
850
<u>850</u>
714
940
660
768
108,0
112
2820
<70 dB(A) re 20 µPa
1,00
•
•
•
•
•
•
•
•
•
•
•
•
•
•

EAN: 4002516223504 / Material number: 11251290 / Old Material Number: 51908387MAR



PWM 908 [EL DP MAR 3 AC 400-480V 50-60Hz]

Professional washing machine, Little Giants, electric heating, drain pump Lloyd's Register approved, load size 8.0 kg.



EAN: 4002516223504 / Material number: 11251290 / Old Material Number: 51908387MAR

Efficiency and sustainability	
Recycling rate in %	95
Connection options	
Payment system (optional)	•
Optical interface for service access	•
Peak load cut-out/energy management (optional)	•
LAN/WiFi module (optional)	•
WiFiConn@ct	•
Standards, test certificates and symbols	
WEEE	•
Lloyd's Register	•
Complies with Machinery Directive 2006/42/EC	•