

PWM 908 [EL DP MAR 2 NAC 400V 50-60Hz]

Professional washing machine, Little Giants, electric heating, drain pump Lloyd's Register approved, load size 8.0 kg.



- Drum volume 73 I, load size 8.0 kg
- 22 % less water consumption and 28 % less energy consumption
- Tested for intensive use unparalleled Miele quality
- Max. user convenience w. fulltouch colour display –M Touch Flex
- Thorough cleaning with professional wash programmes

EAN: 4002516218470 / Material number: 11252200 / Old Material Number: 51908181MAR

Construction type and version	E a al la a da .
Construction type	Front loader
Range	Performance Plus
Front	Lotus white
Control panel colour	Stainless steel
Load in kg	8,0
Drum volume in I	73
Door opening [Ø] in mm	300
Door opening angle in degrees	167
Door hinge	right
Maintenance-free synchronous motor	•
Honeycomb drum with perforated drum rear panel	•
Application	
Suitable for offshore use	•
Suitable for marine use	•
Performance data	
Tested virucidal efficacy	•
Proven hygiene	•
Specific water consumption for cold water connection in I/	6,40
kg	0.10
Specific energy consumption for cold water connection in kWh/kg	0,13
Specific water consumption for hot water connection in I/kg	6,00
Specific energy consumption for hot water connection in kWh/kg	0,06
Water consumption with cold water connection in I	51,0
Energy consumption with cold water connection in kW	1,05
Programme duration in minutes with cold water connection	59
Water consumption with hot water connection in I	48,0
Energy consumption with hot water connection in kW	0,50
Programme duration in minutes with cold water and hot water connection	49
Residual moisture with cold rinse in %	48
Residual moisture with hot rinse in %	45
Spin speed in rpm	1600
g factor	704
Tested operating hours	30000
Control system	
Control system	M Touch Flex
Programmability	programmable
Max. delay start in h	96
Time left display	•
Programme sequence indicator	•
Language can be selected easily at any time	•
Dispensing	
Detergent drawer	3 compartments
CapDosing	•
Flexible dispensing adapter (optional)	•
Maximum number of connections for liquid dispenser	6
pumps [number]	
Empty sensor	•

^{*}Based on the Coloured items 60 °C programme with a warm water connection, compared to predecessor.



PWM 908 [EL DP MAR 2 NAC 400V 50-60Hz]

Professional washing machine, Little Giants, electric heating, drain pump Lloyd's Register approved, load size 8.0 kg.



EAN: 4002516218470 / Material number: 11252200 / Old Material Number: 51908181MAR

Heating type	Standard electrical connection	
Electrical connection	Heating type	Electric
Total connected load in kW 5,50 Fuse rating in A 16 Possible voltage variant 1 Electrical connection 230V~ Heater rating in kW 2,65 Total connected load in kW 2,85 Fuse rating in A 16 Water connection/drainage		2N~ 400V 50-60 HZ
Total connected load in kW 5,50 Fuse rating in A 16 Possible voltage variant 1 Electrical connection 230V~ Heater rating in kW 2,65 Total connected load in kW 2,85 Fuse rating in A 16 Water connection/drainage	Heater rating in kW	5,30
Fuse rating in A 16		5,50
Possible voltage variant 1 Electrical connection 230V~ Heater rating in kW 2,65 Total connected load in kW 2,85 Fuse rating in A 16 Water connection/drainage 1x 1/2* hose w/ 3/4* th. union Cold water [number] 1x 1/2* hose w/ 3/4* th. union Drain pump DN 22 Dimensions and weight 2 External dimensions, height in mm 850 External dimensions, syeight in mm 596 External dimensions, gross height in mm 940 External dimensions, gross width in mm 660 External dimensions, gross depth in mm 768 Net weight in kg 104,0 Gross weight in kg 104,0 Maximum floor load in N/m² 2820 Emissions data 280 Emissions ound pressure level in the workplace <70 dB(A) re 20 μPa		
Electrical connection		
Total connected load in kW Fuse rating in A Water connection/drainage Cold water [number] Ix 1/2" hose w/ 3/4" th. union Hot water [number] Drain pump Dox 22 Dimensions and weight External dimensions, height in mm External dimensions, width in mm External dimensions, gepth in mm External dimensions, gross height in mm External dimensions, gross height in mm External dimensions, gross height in mm External dimensions, gross width in mm External dimensions, gross depth in mm Fexternal dimensions, gross depth in mm External dimensions External dimensions, depth in mm External dimensions External dimen	•	230V~
Total connected load in kW Fuse rating in A Water connection/drainage Cold water [number] Ix 1/2" hose w/ 3/4" th. union Hot water [number] Drain pump Dox 22 Dimensions and weight External dimensions, height in mm External dimensions, width in mm External dimensions, gepth in mm External dimensions, gross height in mm External dimensions, gross height in mm External dimensions, gross height in mm External dimensions, gross width in mm External dimensions, gross depth in mm Fexternal dimensions, gross depth in mm External dimensions External dimensions, depth in mm External dimensions External dimen	Heater rating in kW	2,65
Fuse rating in A Water connection/drainage Cold water [number]		·
Water connection/drainage 1x 1/2" hose w/ 3/4" th. union Hot water [number] 1x 1/2" hose w/ 3/4" th. union Drain pump DN 22 Dimensions and weight External dimensions, height in mm External dimensions, width in mm 596 External dimensions, gross height in mm 714 External dimensions, gross height in mm 940 External dimensions, gross depth in mm 768 Net weight in kg 104,0 Gross weight in kg 108 Maximum floor load in N/m² 2820 Emissions data Emissions data Emission sound pressure level in the workplace Heat dissipation into the room in MJ/h 1,00 Features 3-dimensional imbalance monitoring • Commercial shock absorbers • Hard-wearing stainless-steel flange • Disinfection rinse • EcoSpeed • Pre-ironing • Efficient drum rib technology • Temperature monitoring • Special heater element • Automatic load control • Flow mete		16
Cold water [number]		
Hot water [number]	-	1x 1/2" hose w/ 3/4" th.
Drain pump Dimensions and weight External dimensions, height in mm External dimensions, width in mm External dimensions, width in mm External dimensions, depth in mm External dimensions, gross height in mm External dimensions, gross height in mm External dimensions, gross width in mm External dimensions, gross width in mm External dimensions, gross width in mm External dimensions, gross depth in mm Formal dimension		union
Drain pump Drimensions and weight External dimensions, height in mm External dimensions, width in mm External dimensions, width in mm External dimensions, gross height in mm External dimensions, gross height in mm External dimensions, gross height in mm External dimensions, gross width in mm External dimensions, gross width in mm External dimensions, gross width in mm External dimensions, gross depth in mm Formal dimensions, gross weight in kg Formal dimensions, gross depth in mm Formal dimensions, gross height in mm Formal dimensions, great dime	Hot water [number]	1x 1/2" hose w/ 3/4" th.
Dimensions and weight External dimensions, height in mm External dimensions, width in mm External dimensions, depth in mm External dimensions, gross height in mm External dimensions, gross height in mm External dimensions, gross width in mm External dimensions, gross width in mm External dimensions, gross width in mm External dimensions, gross depth in mm Freaturel dimensions, gross depth in mm Tobal Maximum floor load in N/m² External dimensions data Emission sound pressure level in the workplace Heat dissipation into the room in MJ/h Freatures 3-dimensional imbalance monitoring Commercial shock absorbers Hard-wearing stainless-steel flange Disinfection rinse EcoSpeed Pre-ironing Efficient drum rib technology Fremperature monitoring Special heater element Automatic load control Flow meter LED drum lighting, class 1 Communication slot Add laundry Machine-independent accessories Efficiency and sustainability Recycling rate in % Special ray and sustainability Recycling rate in % Sconnection options Payment system (optional)		union
External dimensions, height in mm External dimensions, width in mm External dimensions, depth in mm External dimensions, gross height in mm External dimensions, gross height in mm External dimensions, gross width in mm External dimensions, gross width in mm External dimensions, gross depth in mm External dimensions, gross depth in mm T68 Net weight in kg I04,0 Gross weight in kg I08 Maximum floor load in N/m² Exact Remission sound pressure level in the workplace Emission sound pressure level in the workplace Heat dissipation into the room in MJ/h Features S-dimensional imbalance monitoring Commercial shock absorbers Hard-wearing stainless-steel flange Disinfection rinse EcoSpeed Pre-ironing Efficient drum rib technology Femperature monitoring Special heater element Automatic load control Flow meter LED drum lighting, class 1 Communication slot Add laundry Machine-independent accessories Efficiency and sustainability Recycling rate in % Specman Special system (optional) • Connection options Payment system (optional)	Drain pump	DN 22
External dimensions, width in mm External dimensions, depth in mm External dimensions, gross height in mm External dimensions, gross height in mm External dimensions, gross width in mm External dimensions, gross width in mm External dimensions, gross depth in mm External dimensions, gross depth in mm Features Emission sweight in kg Emissions data Emission sound pressure level in the workplace Emission sound pressure level in the workplace Emission sound pressure level in the workplace Emission sound pressure level in the workplace Emission sound pressure level in the workplace Emission sound pressure level in the workplace -70 dB(A) re 20 μPa 1,00 Features 3-dimensional imbalance monitoring • Commercial shock absorbers • EcoSpeed Pre-ironing Efficient drum rib technology Efficient drum rib technology Temperature monitoring Special heater element Automatic load control Flow meter LED drum lighting, class 1 Communication slot Add laundry Machine-independent accessories Efficiency and sustainability Recycling rate in % Connection options Payment system (optional)	Dimensions and weight	
External dimensions, depth in mm External dimensions, gross height in mm 940 External dimensions, gross width in mm 660 External dimensions, gross depth in mm 768 Net weight in kg 104,0 Gross weight in kg 108 Maximum floor load in N/m² 2820 Emissions data Emission sound pressure level in the workplace Heat dissipation into the room in MJ/h 1,00 Features 3-dimensional imbalance monitoring Commercial shock absorbers Hard-wearing stainless-steel flange Disinfection rinse EcoSpeed Pre-ironing Efficient drum rib technology Temperature monitoring Special heater element Automatic load control Flow meter LED drum lighting, class 1 Communication slot Add laundry Machine-independent accessories Efficiency and sustainability Recycling rate in % Connection options Payment system (optional)	External dimensions, height in mm	850
External dimensions, gross height in mm External dimensions, gross width in mm External dimensions, gross width in mm External dimensions, gross depth in mm 768 Net weight in kg 104,0 Gross weight in kg 108 Maximum floor load in N/m² 2820 Emissions data Emission sound pressure level in the workplace Heat dissipation into the room in MJ/h Features 3-dimensional imbalance monitoring Commercial shock absorbers Hard-wearing stainless-steel flange Disinfection rinse EcoSpeed Pre-ironing Efficient drum rib technology Temperature monitoring Special heater element Automatic load control Flow meter LED drum lighting, class 1 Communication slot Add laundry Machine-independent accessories Efficiency and sustainability Recycling rate in % Connection options Payment system (optional)	External dimensions, width in mm	596
External dimensions, gross width in mm External dimensions, gross depth in mm 768 Net weight in kg 104,0 Gross weight in kg 108 Maximum floor load in N/m² 2820 Emissions data Emission sound pressure level in the workplace Heat dissipation into the room in MJ/h Features 3-dimensional imbalance monitoring Commercial shock absorbers Hard-wearing stainless-steel flange Disinfection rinse EcoSpeed Pre-ironing Efficient drum rib technology Temperature monitoring Special heater element Automatic load control Flow meter LED drum lighting, class 1 Communication slot Add laundry Machine-independent accessories Efficiency and sustainability Recycling rate in % Special heater (optional) Payment system (optional)	External dimensions, depth in mm	714
External dimensions, gross depth in mm Net weight in kg Gross weight in kg 104,0 Gross weight in kg 108 Maximum floor load in N/m² Emissions data Emission sound pressure level in the workplace Heat dissipation into the room in MJ/h Features 3-dimensional imbalance monitoring Commercial shock absorbers Hard-wearing stainless-steel flange Disinfection rinse EcoSpeed Pre-ironing Efficient drum rib technology Temperature monitoring Special heater element Automatic load control Flow meter LED drum lighting, class 1 Communication slot Add laundry Machine-independent accessories Efficiency and sustainability Recycling rate in % Connection options Payment system (optional)	External dimensions, gross height in mm	940
Net weight in kg Gross weight in kg Haximum floor load in N/m² Emissions data Emission sound pressure level in the workplace Heat dissipation into the room in MJ/h Heat dissipation into the room in MJ/h Features 3-dimensional imbalance monitoring Commercial shock absorbers Hard-wearing stainless-steel flange Disinfection rinse EcoSpeed Pre-ironing Efficient drum rib technology Temperature monitoring Special heater element Automatic load control Flow meter LED drum lighting, class 1 Communication slot Add laundry Machine-independent accessories Efficiency and sustainability Recycling rate in % Connection options Payment system (optional)	External dimensions, gross width in mm	660
Gross weight in kg Maximum floor load in N/m² Emissions data Emission sound pressure level in the workplace Heat dissipation into the room in MJ/h Features 3-dimensional imbalance monitoring Commercial shock absorbers Hard-wearing stainless-steel flange Disinfection rinse EcoSpeed Pre-ironing Efficient drum rib technology Temperature monitoring Special heater element Automatic load control Flow meter LED drum lighting, class 1 Communication slot Add laundry Machine-independent accessories Efficiency and sustainability Recycling rate in % Connection options Payment system (optional)	External dimensions, gross depth in mm	768
Maximum floor load in N/m² 2820 Emissions data Emission sound pressure level in the workplace <70 dB(A) re 20 μPa	Net weight in kg	104,0
Emissions data Emission sound pressure level in the workplace Heat dissipation into the room in MJ/h 1,00 Features 3-dimensional imbalance monitoring - Commercial shock absorbers Hard-wearing stainless-steel flange Disinfection rinse EcoSpeed Pre-ironing Efficient drum rib technology Temperature monitoring Special heater element Automatic load control Flow meter LED drum lighting, class 1 Communication slot Add laundry Machine-independent accessories Efficiency and sustainability Recycling rate in % Connection options Payment system (optional)	Gross weight in kg	108
Emission sound pressure level in the workplace Heat dissipation into the room in MJ/h Features 3-dimensional imbalance monitoring Commercial shock absorbers Hard-wearing stainless-steel flange Disinfection rinse EcoSpeed Pre-ironing Efficient drum rib technology Temperature monitoring Special heater element Automatic load control Flow meter LED drum lighting, class 1 Communication slot Add laundry Machine-independent accessories Efficiency and sustainability Recycling rate in % Payment system (optional)	Maximum floor load in N/m ²	2820
Heat dissipation into the room in MJ/h Features 3-dimensional imbalance monitoring Commercial shock absorbers Hard-wearing stainless-steel flange Disinfection rinse EcoSpeed Pre-ironing Efficient drum rib technology Temperature monitoring Special heater element Automatic load control Flow meter LED drum lighting, class 1 Communication slot Add laundry Machine-independent accessories Efficiency and sustainability Recycling rate in % Payment system (optional) •	Emissions data	
Features 3-dimensional imbalance monitoring Commercial shock absorbers Hard-wearing stainless-steel flange Disinfection rinse EcoSpeed Pre-ironing Efficient drum rib technology Temperature monitoring Special heater element Automatic load control Flow meter LED drum lighting, class 1 Communication slot Add laundry Machine-independent accessories Efficiency and sustainability Recycling rate in % Payment system (optional)	Emission sound pressure level in the workplace	<70 dB(A) re 20 μPa
3-dimensional imbalance monitoring Commercial shock absorbers Hard-wearing stainless-steel flange Disinfection rinse EcoSpeed Pre-ironing Efficient drum rib technology Temperature monitoring Special heater element Automatic load control Flow meter LED drum lighting, class 1 Communication slot Add laundry Machine-independent accessories Efficiency and sustainability Recycling rate in % Payment system (optional)	Heat dissipation into the room in MJ/h	1,00
Commercial shock absorbers Hard-wearing stainless-steel flange Disinfection rinse EcoSpeed Pre-ironing Efficient drum rib technology Temperature monitoring Special heater element Automatic load control Flow meter LED drum lighting, class 1 Communication slot Add laundry Machine-independent accessories Efficiency and sustainability Recycling rate in % Payment system (optional)	Features	
Hard-wearing stainless-steel flange Disinfection rinse EcoSpeed Pre-ironing Efficient drum rib technology Temperature monitoring Special heater element Automatic load control Flow meter LED drum lighting, class 1 Communication slot Add laundry Machine-independent accessories Efficiency and sustainability Recycling rate in % Payment system (optional)	3-dimensional imbalance monitoring	•
Disinfection rinse EcoSpeed Pre-ironing Efficient drum rib technology Temperature monitoring Special heater element Automatic load control Flow meter LED drum lighting, class 1 Communication slot Add laundry Machine-independent accessories Efficiency and sustainability Recycling rate in % Payment system (optional)	Commercial shock absorbers	•
EcoSpeed Pre-ironing Efficient drum rib technology Temperature monitoring Special heater element Automatic load control Flow meter LED drum lighting, class 1 Communication slot Add laundry Machine-independent accessories Efficiency and sustainability Recycling rate in % Payment system (optional) •	Hard-wearing stainless-steel flange	•
Pre-ironing Efficient drum rib technology Temperature monitoring Special heater element Automatic load control Flow meter LED drum lighting, class 1 Communication slot Add laundry Machine-independent accessories Efficiency and sustainability Recycling rate in % Payment system (optional)	Disinfection rinse	•
Efficient drum rib technology Temperature monitoring Special heater element Automatic load control Flow meter LED drum lighting, class 1 Communication slot Add laundry Machine-independent accessories Efficiency and sustainability Recycling rate in % Payment system (optional)	EcoSpeed	•
Temperature monitoring Special heater element Automatic load control Flow meter LED drum lighting, class 1 Communication slot Add laundry Machine-independent accessories Efficiency and sustainability Recycling rate in % Connection options Payment system (optional)	Pre-ironing	•
Special heater element Automatic load control Flow meter LED drum lighting, class 1 Communication slot Add laundry Machine-independent accessories Efficiency and sustainability Recycling rate in % Connection options Payment system (optional)		•
Automatic load control Flow meter LED drum lighting, class 1 Communication slot Add laundry Machine-independent accessories Efficiency and sustainability Recycling rate in % Connection options Payment system (optional)		•
Flow meter LED drum lighting, class 1 Communication slot Add laundry Machine-independent accessories Efficiency and sustainability Recycling rate in % Connection options Payment system (optional)	Special heater element	•
LED drum lighting, class 1 Communication slot Add laundry Machine-independent accessories Efficiency and sustainability Recycling rate in % Connection options Payment system (optional)	Automatic load control	•
Communication slot Add laundry Machine-independent accessories Efficiency and sustainability Recycling rate in % Connection options Payment system (optional)	Flow meter	•
Add laundry Machine-independent accessories Efficiency and sustainability Recycling rate in % Connection options Payment system (optional) •	LED drum lighting, class 1	•
Machine-independent accessories Efficiency and sustainability Recycling rate in % Connection options Payment system (optional) •	Communication slot	•
Efficiency and sustainability Recycling rate in % 95 Connection options Payment system (optional) •		•
Recycling rate in % 95 Connection options Payment system (optional) •	Machine-independent accessories	•
Connection options Payment system (optional) •		
Payment system (optional) •		95
Optical interface for service access •	Payment system (optional)	•
<u> </u>	Ontical interface for service access	•



PWM 908 [EL DP MAR 2 NAC 400V 50-60Hz]

Professional washing machine, Little Giants, electric heating, drain pump Lloyd's Register approved, load size 8.0 kg.



EAN: 4002516218470 / Material number: 11252200 / Old Material Number: 51908181MAR

Peak load cut-out/energy management (optional)	•
LAN/WiFi module (optional)	•
WiFiConn@ct	•
Standards, test certificates and symbols	
WEEE	•
Lloyd's Register	•
Complies with Machinery Directive 2006/42/FC	•