

HM 16-80 D [EL SOM] Rotary ironer, electrically heated with steam function for maximum convenience for marine applications.



- Performance 13.0 kg/h^{*}, roller diameter 160 mm, working width 830 mm
- Iron comfortably while seated
- Work at your own pace thanks to variable roller speed
- Durable roller padding aramid needle felt cloth
- Easy to store fold-away function

With 20% residual moisture – performance data according to DIN 11 902:
br>The achievable ironing capacity depends on overall conditions such as, for example, the type of laundry and the experience of the operator. EAN: 4002516276326 / Material number: 11419390 / Old Material Number: 53168001SOM

Construction typeLaundry infeed and outfied at the frontCan be set up against a wall•RangeProfessionalOuter casingLotus whiteRoller diameter in mm160Working width in mm830Heater plate materialAluminiumPaddingPolyester needle-felt clothIroner coverARAMID needle-felt clothApplication•Suitable for offshore use•Suitable for marine use•Performance data•Max. ironing performance at 20 % residual moisture in kg/h13.0Tested operating hours2500Control system•Control system•Touch display (optional)DrehwahlschalterMinimum ironing speed, controlled in m/min4.5Adjustable temperatureIn temperature stagesStandard electrical connectionAC 220-240V 50-60HZElectric heater rating in KW3,10-3,70Boiler heater rating in kW3,20-3,80Fuser rating in A16Dimensions and weight•External dimensions, height in mm959External dimensions, gross depth in mm380External dimensions, gross depth in mm450Net weight in kg39Gross wight in kg39Gross wight in kg39Statemal dimensions, gross depth in mm450Net weight in kg39Staternal dimensions, gross depth in mm450Net weight in kg39Gross wight in kg45 </th <th>Construction type and version</th> <th></th>	Construction type and version	
Att the frontCan be set up against a wall•RangeProfessionalOuter casingLotus whiteRoller diameter in mm180Working width in mm830Heater plate materialAluminiumPaddingPolyester needle-felt clothApplication•Suitable for offshore use•Suitable for marine use•Performance data•Max. ironing performance at 20 % residual moisture in kg/h13,0Tested operating hours2500Control system•Control system•Touch display (optional)DrehwahlschalterMinimum ironing speed, controlled in m/min4,5Adjustable themperatureIn temperature stagesStandard electrical connectionAC 220-240V 50-60HZElectrical connectionAC 220-240V 50-60HZElectrical connection865Totard ding in kW3,10-3,70Boiler heater rating in kW3,20-3,80Totard dingensions, width in mm959External dimensions, height in mm959External dimensions, gross height in mm382External dimensions, gross width in mm382Staan function•External dimensions, gross width in mm450Maximum fior loading in N382Staan function•Free roller end•Fold-away function•Automatic finger guard•Automatic finger guard•Foot switch•Aut		Laundry infood and outfood
Can be set up against a wall • Range Professional Outer casing Lotus white Roller diameter in mm 160 Working width in mm 830 Heater plate material Alumínium Padding Polyester needle-felt cloth Ironer cover ARAMID needle-felt cloth Application • Suitable for marine use • Performance data 13.0 Tested operating hours 2500 Control system Rotary control Touch display (optional) Drehwahlschalter Minimum ironing speed, controlled in m/min 4,5 Adjustable temperature In temperature stages Standard electrical connection AC 220-240V 50-60HZ Electric Electric Electric local connection AC 220-240V 50-60HZ Electric in connection (AC 220-240V 50-60HZ Electric in connection (AC 220-240V 50-60HZ Electric connection (AC 220-240V 50-60HZ Electric in connect	Construction type	2
Outer casing Lotus white Roler diameter in mm 160 Working width in mm 830 Heater plate material Aluminium Padding Polyester needle-felt cloth Application - Suitable for offshore use • Suitable for marine use • Performance data - Max. ironing performance at 20 % residual moisture in kg/h 13,0 Tested operating hours 2500 Control system Rotary control Touch display (optional) Drehwahlschalter Minimum ironing speed, controlled in m/min 2,0 Maximum ironing speed, controlled in m/min 4,5 Adjustable temperature In temperature stages Standard electrical connection AC 220-240V 50-60HZ Electric Electric Electric heater rating in kW 3,10-3,70 Boiler heater rating in kW 3,20-3,80 Fuse rating in A 16 Dimensions and weight External dimensions, gross height in mm External dimensions, gross height in mm 380 E	Can be set up against a wall	•
Roller diameter in mm 160 Working width in mm 830 Heater plate material Aluminium Padding Polyester needle-felt cloth Ironer cover ARAMID needle-felt cloth Application • Suitable for marine use • Performance data • Max. ironing performance at 20 % residual moisture in kg/h 13,0 Tested operating hours 2500 Control system Control system Control system Pady control Touch display (optional) Drehwahlschalter Minimum ironing speed, controlled in m/min 4,5 Adjustable temperature In temperature stages Standard electrical connection AC 220-240V 50-60HZ Electric la connection AC 220-240V 50-60HZ Electric heater rating in kW 3,10-3,70 Boiler heater rating in kW 3,20-3,80 Fuse rating in A 16 Dimensions and weight E External dimensions, kight in mm 959 External dimensions, gross width in mm 120 External dimensions, gross widpt in mm 120 Ext	Range	Professional
Working width in mm 830 Heater plate material Aluminium Padding Polyester needle-felt cloth Inoner cover ARAMID needle-felt cloth Application • Suitable for offshore use • Suitable for offshore use • Performance data 13,0 Tested operating hours 2500 Control system Rotary control Touch display (optional) Drehwahlschalter Minimum ironing speed, controlled in m/min 2,0 Maximum ironing speed, controlled in m/min 4,5 Adjustable temperature In temperature stages Standard electrical connection AC 220-240V 50-60HZ Electric heater rating in KW 3,10-3,70 Boiler heater rating in KW 0,85 Total connected load in kW 3,20-3,80 Fuserating in A 16 Dimensions and weight External dimensions, width in mm External dimensions, depth in mm 570 External dimensions, gross width in mm 1120 External dimensions, gross width in mm 450 Net weight in kg 39 G	Outer casing	Lotus white
Heater plate material Aluminium Padding Polyester needle-felt cloth Application Suitable for offshore use • Suitable for offshore use • Suitable for marine use • Performance data 13,0 Tested operating hours 25000 Control system Rotary control Touch display (optional) Drehwahlschalter Minimum ironing speed, controlled in m/min 2,0 Maximum ironing speed, controlled in m/min 4,5 Adjustable temperature In temperature stages Standard electrical connection AC 220-240V 50-60HZ Electric Electric Electrical connection AC 220-240V 50-60HZ Electrical connection AC 250-240V 50-60HZ El	Roller diameter in mm	160
Padding Polyester neecle-felt cloth Ironer cover ARAMID needle-felt cloth Application • Suitable for offshore use • Suitable for marine use • Performance data • Max. ironing performance at 20 % residual moisture in kg/h 13,0 Tested operating hours 2500 Control system Rotary control Touch display (optional) Drehwahlschalter Minimum ironing speed, controlled in m/min 2,0 Maximum ironing speed, controlled in m/min 4,5 Adjustable temperature In temperature stages Standard electrical connection AC 220-240V 50-60HZ Electrica connection AC 220-240V 50-60HZ Electrica connecton AC 220-240V 50-60HZ Electrica locannecton AC 220-240V 50-60HZ Electrica locannecton AC 220-240V 50-60HZ Electrica locannecton AC 220-240V 50-60HZ Electr	Working width in mm	830
Ironer cover ARAMID needle-feit cloth Application • Suitable for offshore use • Suitable for marine use • Performance data 13,0 Tested operating hours 2500 Control system Rotary control Touch display (optional) Drehwahlschalter Minimum ironing speed, controlled in m/min 2,0 Maximum ironing speed, controlled in m/min 4,5 Adjustable temperature In temperature stages Standard electrical connection AC 220-240V 50-60HZ Electric heater rating in kW 3,10-3,70 Boiler heater rating in kW 0,85 Total connected load in kW 3,20-3,80 Fuse rating in A 16 Dimensions and weight 570 External dimensions, height in mm 959 External dimensions, gorss width in mm 1120 External dimensions, gross width in mm 450 Maximum floor loading in N 382 Features 5 Maximum floor loading in N 382 Features 5 Maximum floor loading in N 382 <td>Heater plate material</td> <td>Aluminium</td>	Heater plate material	Aluminium
ApplicationSuitable for offshore use•Suitable for marine use•Performance data•Max. ironing performance at 20 % residual moisture in kg/n13,0Tested operating hours2500Control systemRotary controlTouch display (optional)DrehwahlschalterMinimum ironing speed, controlled in m/min2,0Maximum ironing speed, controlled in m/min4,5Adjustable temperatureIn temperature stagesStandard electrical connectionAC 220-240V 50-60HZElectric lonnectionAC 220-240V 50-60HZElectric heater rating in kW3,10-3,70Boiler heater rating in kW0,85Total connected load in kW3,20-3,80Fuse rating in A16Dimensions and weightExternal dimensions, height in mmExternal dimensions, kieght in mm959External dimensions, gross weight in mm570External dimensions, gross depth in mm450Net weight in kg39Gross weight in kg45Maximum floor loading in N382Features-Steam function-Free roller end-Foot switch-Automatic finger guard-Foot switch-Airing bar-4 castors gentle on the floor-Feed-in board-Feed-in board-	Padding	Polyester needle-felt cloth
Suitable for offshore use • Suitable for marine use • Performance data 13,0 Max. ironing performance at 20 % residual moisture in kg/h 13,0 Tested operating hours 2500 Control system Rotary control Control system Rotary control Touch display (optional) Drehwahlschalter Minimum ironing speed, controlled in m/min 2,0 Maximum ironing speed, controlled in m/min 4,5 Adjustable temperature In temperature stages Standard electrical connection AC 220-240V 50-60HZ Electric Electric Electric heater rating in kW 3,10-3,70 Boiler heater rating in kW 0,85 Total connected load in kW 3,20-3,80 Fuse rating in A 16 Dimensions and weight External dimensions, width in mm External dimensions, keight in mm 959 External dimensions, gross weight in mm 570 External dimensions, gross weight in mm 120 External dimensions, gross depth in mm 520 External dimensions, gross weight in mm 382 Features	Ironer cover	ARAMID needle-felt cloth
Suitable for marine use • Performance data 13,0 Tested operating hours 2500 Control system Rotary control Touch display (optional) Drehwahlschalter Minimum ironing speed, controlled in m/min 2,0 Maximum ironing speed, controlled in m/min 4,5 Adjustable temperature In temperature stages Standard electrical connection AC 220-240V 50-60HZ Electric Electric Electric heater rating in kW 3,10-3,70 Boiler heater rating in kW 0,85 Total connected load in kW 3,20-3,80 Fuse rating in A 16 Dimensions and weight 959 External dimensions, height in mm 959 External dimensions, gross height in mm 370 External dimensions, gross depth in mm 450 Net weight in kg 39 Gross weight in kg 45 Maximum floor loading in N 382 Features Steam function Free roller end • Foot switch • Automatic finger guard • F	Application	
Performance dataI3,0Max. ironing performance at 20 % residual moisture in kg/h13,0Tested operating hours2500Control systemRotary controlTouch display (optional)DrehwahlschalterMinimum ironing speed, controlled in m/min2,0Maximum ironing speed, controlled in m/min4,5Adjustable temperatureIn temperature stagesStandard electrical connectionAC 220-240V 50-60HZElectric connectionAC 220-240V 50-60HZElectric heater rating in kW3,10-3,70Boiler heater rating in kW0,85Total connected load in kW3,20-3,80Fuse rating in A16Dimensions and weightEExternal dimensions, height in mm959External dimensions, depth in mm380External dimensions, gross height in mm570External dimensions, gross width in mm1120External dimensions, gross weight in mm399Gross weight in kg45Maximum floor loading in N382FeaturesESteam function•Free roller end•Foot switch•Automatic finger guard•Automatic finger guard•Ac astors gentle on the floor•Feed-in board•	Suitable for offshore use	•
Max. ironing performance at 20 % residual moisture in kg/h13,0Tested operating hours2500Control systemRotary controlTouch display (optional)DrehwahlschalterMinimum ironing speed, controlled in m/min4,5Adjustable temperatureIn temperature stagesStandard electrical connectionAC 220-240V 50-60HZElectricElectricElectric heater rating in kW3,10-3,70Boiler heater rating in kW3,20-3,80Fuse rating in A16Dimensions and weight16External dimensions, height in mm959External dimensions, depth in mm380External dimensions, gross height in mm570External dimensions, gross stepth in mm450Net weight in kg39Gross weight in kg45Maximum floor loading in N382FeaturesIntervesSteam function•Free roller end•Foot switch•Foot switch•Automatic finger guard•Foot switch•Automatic finger guard•Feed-in board•	Suitable for marine use	•
Tested operating hours2500Control systemRotary controlTouch display (optional)DrehwahlschalterMinimum ironing speed, controlled in m/min2,0Maximum ironing speed, controlled in m/min4,5Adjustable temperatureIn temperature stagesStandard electrical connectionAC 220-240V 50-60HZElectric heater rating in kW3,10-3,70Boiler heater rating in kW0,85Total connected load in kW3,20-3,80Fuse rating in A16Dimensions and weightExternal dimensions, height in mmExternal dimensions, height in mm959External dimensions, gross height in mm570External dimensions, gross height in mm450Net weight in kg39Gross weight in kg45Maximum floor loading in N382FeaturesSteam functionSteam function•Free roller end•Automatic finger guard•Foot switch•Automatic finger guard•Feed-in board•Feed-in board•	Performance data	
Control systemRotary controlControl systemRotary controlTouch display (optional)DrehwahlschalterMinimum ironing speed, controlled in m/min2,0Maximum ironing speed, controlled in m/min4,5Adjustable temperatureIn temperature stagesStandard electrical connectionAC 220-240V 50-60HZElectric heater rating in kW3,10-3,70Boiler heater rating in kW0,85Total connected load in kW3,20-3,80Fuse rating in A16Dimensions and weightExternal dimensions, height in mmExternal dimensions, kight in mm959External dimensions, gross height in mm570External dimensions, gross width in mm1120External dimensions, gross width in mm450Net weight in kg45Maximum floor loading in N382FeaturesSteam functionSteam function•Free roller end•Fold -away function•Automatic finger guard•Automatic finger guard•Automatic finger guard•Automatic finger guard•Automatic finger guard•Feed-in board•Feed-in board•	Max. ironing performance at 20 % residual moisture in kg/h	13,0
Control systemRotary controlTouch display (optional)DrehwahlschalterMinimum ironing speed, controlled in m/min2,0Maximum ironing speed, controlled in m/min4,5Adjustable temperatureIn temperature stagesStandard electrical connectionElectricElectric connectionAC 220-240V 50-60HZElectric heater rating in kW3,10-3,70Boiler heater rating in kW0,85Total connected load in kW3,20-3,80Fuse rating in A16Dimensions and weight16External dimensions, height in mm959External dimensions, keight in mm959External dimensions, gross height in mm570External dimensions, gross beight in mm1120External dimensions, gross weight in mm450Net weight in kg39Gross weight in kg39Gross weight in kg45Maximum floor loading in N382Features1Steam function•Free roller end•Fold-away function•Automatic finger guard•Foot switch•Airing bar•4 castors gentle on the floor•Feed-in board•	Tested operating hours	2500
Touch display (optional)DrefwahlschalterMinimum ironing speed, controlled in m/min2,0Maximum ironing speed, controlled in m/min4,5Adjustable temperatureIn temperature stagesStandard electrical connectionAC 220-240V 50-60HZElectric connectionAC 220-240V 50-60HZElectric heater rating in kW3,10-3,70Boiler heater rating in kW0,85Total connected load in kW3,20-3,80Fuse rating in A16Dimensions and weight16External dimensions, height in mm959External dimensions, gross height in mm380External dimensions, gross width in mm1120External dimensions, gross weight in mm450Net weight in kg39Gross weight in kg39Gross weight in kg45Maximum floor loading in N382Features5Steam function•Free roller end•Fold-away function•Automatic finger guard•Foat switch•Airing bar•4 castors gentle on the floor•Feed-in board•	Control system	
Minimum ironing speed, controlled in m/min2,0Maximum ironing speed, controlled in m/min4,5Adjustable temperatureIn temperature stagesStandard electrical connectionAC 220-240V 50-60HZElectric classElectricElectric heater rating in kW3,10-3,70Boiler heater rating in kW0,85Total connected load in kW3,20-3,80Fuse rating in A16Dimensions and weightExternal dimensions, height in mmExternal dimensions, height in mm959External dimensions, gross height in mm570External dimensions, gross height in mm1120External dimensions, gross beight in mm450Net weight in kg39Gross weight in kg45Maximum floor loading in N382FeaturesImage: steam of the ste	Control system	Rotary control
Maximum ironing speed, controlled in m/min4,5Adjustable temperatureIn temperature stagesStandard electrical connectionAC 220-240V 50-60HZElectric connectionAC 220-240V 50-60HZElectric heater rating in kW3,10-3,70Boiler heater rating in kW0,85Total connected load in kW3,20-3,80Fuse rating in A16Dimensions and weight959External dimensions, height in mm959External dimensions, depth in mm380External dimensions, gross height in mm570External dimensions, gross height in mm1120External dimensions, gross beight in mm450Net weight in kg39Gross weight in kg39Features52Steam function•Free roller end•Fold-away function•Automatic finger guard•Foot switch•Airing bar•4 castors gentle on the floor•Feed-in board•	Touch display (optional)	Drehwahlschalter
Adjustable temperatureIn temperature stagesStandard electrical connectionElectricHeating typeElectricElectrical connectionAC 220-240V 50-60HZElectric heater rating in kW3,10-3,70Boiler heater rating in kW0,85Total connected load in kW3,20-3,80Fuse rating in A16Dimensions and weightExternal dimensions, height in mmExternal dimensions, height in mm959External dimensions, gross height in mm380External dimensions, gross height in mm570External dimensions, gross width in mm1120External dimensions, gross depth in mm450Net weight in kg39Gross weight in kg45Maximum floor loading in N382FeaturesSteam functionSteam function•Free roller end•Foot switch•Automatic finger guard•Automatic finger guard•Features gentle on the floor•Feed-in board•	Minimum ironing speed, controlled in m/min	2,0
Standard electrical connectionElectricHeating typeElectricElectrical connectionAC 220-240V 50-60HZElectric heater rating in kW3,10-3,70Boiler heater rating in kW0,85Total connected load in kW3,20-3,80Fuse rating in A16Dimensions and weight16External dimensions, height in mm959External dimensions, width in mm985External dimensions, gross height in mm570External dimensions, gross height in mm1120External dimensions, gross width in mm450Net weight in kg39Gross weight in kg45Maximum floor loading in N382Features5Steam function•Free roller end•Fold-away function•Automatic finger guard•Automatic finger guard•Acastors gentle on the floor•Feed-in board•	Maximum ironing speed, controlled in m/min	4,5
Heating typeElectricElectrical connectionAC 220-240V 50-60HZElectric heater rating in kW3,10-3,70Boiler heater rating in kW0,85Total connected load in kW3,20-3,80Fuse rating in A16Dimensions and weight16External dimensions, height in mm959External dimensions, width in mm985External dimensions, depth in mm380External dimensions, gross height in mm570External dimensions, gross height in mm1120External dimensions, gross width in mm450Net weight in kg39Gross weight in kg45Maximum floor loading in N382Features16Steam function•Free roller end•Foot switch•Automatic finger guard•Automatic finger guard•Airing bar•4 castors gentle on the floor•Feed-in board•	Adjustable temperature	In temperature stages
Electrical connectionAC 220-240V 50-60HZElectric heater rating in kW3,10-3,70Boiler heater rating in kW0,85Total connected load in kW3,20-3,80Fuse rating in A16Dimensions and weight16External dimensions, height in mm959External dimensions, width in mm985External dimensions, depth in mm570External dimensions, gross height in mm570External dimensions, gross width in mm1120External dimensions, gross width in mm450Net weight in kg39Gross weight in kg45Maximum floor loading in N382Features9Steam function•Free roller end•Fold-away function•Automatic finger guard•Automatic finger guard•Automatic finger guard•Ac astors gentle on the floor•Feed-in board•	Standard electrical connection	
Electric heater rating in kW3,10-3,70Boiler heater rating in kW0,85Total connected load in kW3,20-3,80Fuse rating in A16Dimensions and weight16External dimensions, height in mm959External dimensions, width in mm985External dimensions, depth in mm380External dimensions, gross height in mm570External dimensions, gross height in mm1120External dimensions, gross width in mm450Net weight in kg39Gross weight in kg45Maximum floor loading in N382Features9Steam function•Free roller end•Fold-away function•Automatic finger guard•Foot switch•Airing bar•4 castors gentle on the floor•Feed-in board•	Heating type	Electric
Boiler heater rating in kW0,85Total connected load in kW3,20-3,80Fuse rating in A16Dimensions and weightExternal dimensions, height in mmExternal dimensions, height in mm959External dimensions, width in mm985External dimensions, depth in mm380External dimensions, gross height in mm570External dimensions, gross width in mm1120External dimensions, gross width in mm450Net weight in kg39Gross weight in kg45Maximum floor loading in N382Features5Steam function•Free roller end•Fold-away function•Automatic finger guard•Automatic finger guard•Airing bar•4 castors gentle on the floor•Feed-in board•	Electrical connection	AC 220-240V 50-60HZ
Total connected load in kW3,20-3,80Fuse rating in A16Dimensions and weight16External dimensions, height in mm959External dimensions, width in mm985External dimensions, depth in mm380External dimensions, gross height in mm570External dimensions, gross height in mm570External dimensions, gross width in mm1120External dimensions, gross depth in mm450Net weight in kg39Gross weight in kg45Maximum floor loading in N382Features5Steam function•Free roller end•Fold-away function•Automatic finger guard•Automatic finger guard•Airing bar•4 castors gentle on the floor•Feed-in board•	Electric heater rating in kW	3,10-3,70
Fuse rating in A16Dimensions and weight16External dimensions, height in mm959External dimensions, width in mm985External dimensions, depth in mm380External dimensions, gross height in mm570External dimensions, gross width in mm1120External dimensions, gross weight in mm450Net weight in kg39Gross weight in kg45Maximum floor loading in N382Features9Steam function•Free roller end•Fold-away function•Automatic finger guard•Automatic finger guard•Airing bar•4 castors gentle on the floor•Feed-in board•	Boiler heater rating in kW	0,85
Dimensions and weight959External dimensions, height in mm959External dimensions, width in mm985External dimensions, depth in mm380External dimensions, gross height in mm570External dimensions, gross width in mm1120External dimensions, gross weight in mm450Net weight in kg39Gross weight in kg45Maximum floor loading in N382Features9Steam function•Free roller end•Fold-away function•Automatic finger guard•Airing bar•4 castors gentle on the floor•Feed-in board•	Total connected load in kW	3,20-3,80
External dimensions, height in mm959External dimensions, width in mm985External dimensions, depth in mm380External dimensions, gross height in mm570External dimensions, gross width in mm1120External dimensions, gross width in mm450Net weight in kg39Gross weight in kg45Maximum floor loading in N382Features9Steam function•Free roller end•Fold-away function•Automatic finger guard•Automatic finger guard•Airing bar•4 castors gentle on the floor•Feed-in board•	Fuse rating in A	16
External dimensions, width in mm985External dimensions, depth in mm380External dimensions, gross height in mm570External dimensions, gross width in mm1120External dimensions, gross depth in mm450Net weight in kg39Gross weight in kg45Maximum floor loading in N382FeaturesSteam function•Free roller end•Fold-away function•Automatic finger guard•Airing bar•4 castors gentle on the floor•Feed-in board•	-	
External dimensions, depth in mm380External dimensions, gross height in mm570External dimensions, gross width in mm1120External dimensions, gross depth in mm450Net weight in kg39Gross weight in kg45Maximum floor loading in N382FeaturesSteam function•Free roller end•Fold-away function•Automatic finger guard•Foot switch•Airing bar•4 castors gentle on the floor•Feed-in board•	External dimensions, height in mm	959
External dimensions, gross height in mm570External dimensions, gross width in mm1120External dimensions, gross depth in mm450Net weight in kg39Gross weight in kg45Maximum floor loading in N382FeaturesSteam function•Free roller end•Fold-away function•Automatic finger guard•Foot switch•Airing bar•4 castors gentle on the floor•Feed-in board•	External dimensions, width in mm	985
External dimensions, gross width in mm1120External dimensions, gross depth in mm450Net weight in kg39Gross weight in kg45Maximum floor loading in N382FeaturesSteam function•Free roller end•Fold-away function•Automatic finger guard•Foot switch•Airing bar•4 castors gentle on the floor•Feed-in board•	External dimensions, depth in mm	380
External dimensions, gross depth in mm450Net weight in kg39Gross weight in kg45Maximum floor loading in N382Features9Steam function•Free roller end•Fold-away function•Automatic finger guard•Foot switch•Airing bar•4 castors gentle on the floor•Feed-in board•	External dimensions, gross height in mm	570
Net weight in kg39Gross weight in kg45Maximum floor loading in N382Features9Steam function•Free roller end•Fold-away function•Automatic finger guard•Foot switch•Airing bar•4 castors gentle on the floor•Feed-in board•	External dimensions, gross width in mm	1120
Gross weight in kg45Maximum floor loading in N382Features382Steam function•Free roller end•Fold-away function•Automatic finger guard•Foot switch•Airing bar•4 castors gentle on the floor•Feed-in board•	External dimensions, gross depth in mm	450
Maximum floor loading in N382Features382Steam function•Free roller end•Fold-away function•Automatic finger guard•Foot switch•Airing bar•4 castors gentle on the floor•Feed-in board•	Net weight in kg	39
FeaturesSteam function•Free roller end•Fold-away function•Automatic finger guard•Foot switch•Airing bar•4 castors gentle on the floor•Feed-in board•		45
Steam function•Free roller end•Fold-away function•Automatic finger guard•Foot switch•Airing bar•4 castors gentle on the floor•Feed-in board•	Maximum floor loading in N	382
Free roller end•Fold-away function•Automatic finger guard•Foot switch•Airing bar•4 castors gentle on the floor•Feed-in board•	Features	
Fold-away function•Automatic finger guard•Foot switch•Airing bar•4 castors gentle on the floor•Feed-in board•	Steam function	•
Automatic finger guard • Foot switch • Airing bar • 4 castors gentle on the floor • Feed-in board •	Free roller end	•
Foot switch•Airing bar•4 castors gentle on the floor•Feed-in board•		•
Airing bar • 4 castors gentle on the floor • Feed-in board •	Automatic finger guard	•
4 castors gentle on the floor • Feed-in board •		•
Feed-in board •	Airing bar	•
	4 castors gentle on the floor	•
Laundry return feed •		•
	Laundry return feed	•



HM 16-80 D [EL SOM] Rotary ironer, electrically heated with steam function for maximum convenience for marine applications.



EAN: 4002516276326 / Material number: 11419390 / Old Material Number: 53168001SOM

Option of ironing when seated	•
Machine-independent accessories	•
Standards, test certificates and symbols	
VDE	•
CE	•
WEEE	•
VDE-EMC	•
UKCA	•