

G 5050 SCVi Active Fully integrated dishwashers in tried-and-tested Miele quality at an affordable entry-level price.



- Perfect results in less than one hour – QuickPowerWash
- Save up to 50 % more electricity hot water connection
- Versatile and secure comfort basket design
- Very easy door opening and closing – ComfortClose
- Maximum versatility Heightadjustable upper basket

EAN: 4002516316312 / Material number: 11495870 / Old Material Number: 21505062GB

Model	
Fully integrated dishwasher	•
60 cm dishwasher	•
Design	
Control panel colour	Stainless Steel.
Control panel version	Fully integrated fascia
Control type	Programme selector button
Display	3-digit 7-segment display
Display colour	Yellow
Convenience	
Door closing aid	ComfortClose
Time left display	·
Delay start up to 24 hours	•
In-operation indicator light	acoustic
Efficiency and sustainability	
Energy efficiency class (A-G)	_ <u>E</u>
Water consumption in the Automatic programme in I from	6,0
Water consumption of the ECO programme in litres per	8,9
programme cycle	
Electricity consumption in the ECO programme in kWh	0,95
Energy consumption of the ECO programme in kWh after	95
100 programme cycles	
Consumption value in kWh in the ECO programme with hot water connection	0,65
Duration of ECO programme in minutes	234
Noise emission class	С
Noise emissions in dB(A)	45
EcoPower Technology	•
Proven hygiene	•
Hot water connection	•
Quality of results	
Fresh water dishwasher	•
Wash programmes	
QuickPowerWash	•
ECO ECO	•
Automatic	•
Intensive 75 °C	•
Gentle	•
Dishwashing options	
Express	•
Extra Clean	•
Extra dry	•
Basket design	O. Han due.
Cutlery loading	Cutlery tray
FlexCare cup rack	1
Basket design	Comfort
Number of place settings	14
Safety	
Waterproof system	•
Technical data	
Niche width minimal in mm	600



G 5050 SCVi Active Fully integrated dishwashers in tried-and-tested Miele quality at an affordable entry-level price.




EAN: 4002516316312 / Material number: 11495870 / Old Material Number: 21505062GB

Niche width max in mm	600
Niche height minimal in mm	805
Niche height maximal in mm	870
Niche depth in mm	550
Appliance width in mm	598
Appliance height in mm	805
Appliance depth in mm	550
Depth with door open in cm	116,5
Net weight in kg	44,0
Total rated load in kW	2,00
Voltage in V	230
Fuse rating in A	10
Number of phases	1
Electrical frequency standard	50
Length of water inlet hose in cm	1,50
Length of water drain hose in cm	1,50
Length of supply lead in m	1,80
Min. front panel weight in kg	4,0
Max. front panel weight in kg	11,0
[can be retrofitted by Service to min.]	8,0
[can be retrofitted by Service to max.]	16,0
Accessories included	
1 x UltraTabs box (20 tabs)	•

Voucher for 1 x box of UltraTabs (20 tabs) or 9 boxes at a reduced price



G 5050 SCVi Active Fully integrated dishwashers in tried-and-tested Miele quality at an affordable entry-level price.



1) Plinth height 35-155 mm, 2) Plinth height 100-220 mm, 3) Appliance height max. 930 mm with plinth height conversion kit (Mat.-Nr. 6.394.761),