Miele

PWM 912 [EL DV DD SOM]

Professional washing machine, electrically heated, with drain valve and detergent drawer, M Touch Pro Plus freely programmable, for marine use.



- Drum volume 110 I, maximum load size 12.0 kg
- Top cleaning & consumption values – innovative Miele technology
- Ideal operation thanks to colour touch display M Touch Pro Plus
- Simple and safe operation thanks to automatic door lock
- Connected for the future using LAN and WiFi

EAN: 4002516391586 / Material number: 11682920 / Old Material Number: 51912001SOM

Construction type and version	
Construction type and version Construction type	Front loader
Range	Performance Plus
Front	Stainless steel
Control panel colour	Stainless steel
Maximum load with a load ratio of 1:9 in kg	12,0
Load ratio	1:9
Load in kg	12,0
Drum volume in I	110
Door opening [Ø] in mm	415
Door opening angle in degrees	180
Door hinge	right
Automatic door lock	•
Innovative suds container	•
Maintenance-free motor with frequency converter	•
Patented honeycomb drum 2.0	•
Application	
Suitable for offshore use	•
Suitable for marine use	•
Performance data	
Tested virucidal efficacy	•
Proven hygiene	•
Specific water consumption for cold water connection in I/kg	6,20
Specific energy consumption for cold water connection in kWh/kg	0,14
Specific water consumption for hot water connection in I/kg	5,90
Specific energy consumption for hot water connection in kWh/kg	0,06
Water consumption with cold water connection in I	74,4
Water consumption for cold water connection in Mops standard 60 °C programme in I	142,2
Energy consumption with cold water connection in kW	1,68
Energy consumption for cold water connection in Mops standard 60 °C programme in kWh	2,50
Programme duration in minutes with cold water connection	49
Water consumption with hot water connection in I	70,8
Water consumption for hot water connection in Mops standard 60 °C programme in I	139,9
Energy consumption with hot water connection in kW	0,72
Energy consumption for hot water connection in Mops standard 60 °C programme in kWh	1,00
Programme duration in minutes with cold water and hot water connection	42
Water consumption in ECO programme with cold water connection in I	69,6
Energy consumption in ECO programme with cold water	1,20
Programme duration in minutes with cold water connection in ECO programme	34
Water consumption in ECO programme with hot water connection in I	68,4
Energy consumption in ECO programme with hot water	0,36



PWM 912 [EL DV DD SOM]

Professional washing machine, electrically heated, with drain valve and detergent drawer, M Touch Pro Plus freely programmable, for marine use.



EAN: 4002516391586 / Material number: 11682920 / Old Material Number: 51912001SOM

Programme running time in minutes for Mops standard 60 °C programme with cold water connection Programme running time in minutes for Mops standard 60 °C programme with hot water connection Residual moisture with hot mater connection Residual moisture with hot rinse in % 48 Residual moisture when processing cleaning cloths in % 5pin speed in rpm 1150 g factor 458 Tested operating hours 30000 Control system Control system Control system Programmability Freely programmable Programmability Freely programmable Programmability Freely selectable Time left display Programme sequence indicator • Selectable display languages Option to enter weight prior to start of programme Standard/target grp programmes Basic programmes Dispensing Detergent drawer Maximum number of connections for liquid dispenser pumps [number] Empty sensor Standard electrical connection Heating type Electrical connection Heater rating in kW 9,00 Total connected load in kW 9,80 Fuse rating in A 16 Water connection A 172° hose w/ 3/4° th. union Dump valve DN 70 Dimmsions and weight External dimensions, height in mm 799 External dimensions, gross height in mm 1480 External dimensions, gross height in mm 1994 External dimensions, gross depth in mm 1990	Programme duration in minutes with cold water and hot water connection in ECO programme	31
Programme running time in minutes for Mops standard 60 °C programme with hot water connection Residual moisture with cold rinse in % 48 Residual moisture with cold rinse in % 44 Residual moisture when processing cleaning cloths in % 25 Spin speed in rpm g factor 458 Spin speed in rpm g 30000 Tested operating hours 30000 Control system M Touch Pro Plus Programmability Freely programmable Programmability Freely programmable Programmability Freely programmable Programme sequence indicator • • Programme sequence indicator • • Selectable display languages • Option to enter weight prior to start of programme Standard/target grp programmes Basic programmes • • Standard/target grp programmes Basic programmes • • Standard/target grp programmes Dispensing Detergent drawer Maximum number of connections for liquid dispenser pumps [number] Empty sensor • • Standard electrical connection Heating type Electric Electrical connected load in kW 9,60 Fuse rating in kW 9,00 Total connected load in kW 9,60 Fuse rating in A 16 Possible voltage variant 1 Electrical connection 3N AC 400V 50HZ Heater rating in kW 9,00 Total connected load in kW 9,60 Fuse rating in A 16 Possible voltage variant 1 Electrical connection 3x N AC 400V 60HZ Heater rating in kW 9,00 Total connected load in kW 9,60 Fuse rating in A 16 Water connection/drainage Cold water [number] 3x 1/2* hose w/ 3/4* union Hot water [number] 1x 1/2* hose w/ 3/4* union Dump valve Dn 70 Dimensions and weight External dimensions, height in mm 1350 External dimensions, height in mm 1350 External dimensions, gross width in mm 924 External dimensions, gross width in mm 1090 External dimensions, gross depth in mm 1130	Programme running time in minutes for Mops standard	54
Residual moisture with hot rinse in % 44 Residual moisture when processing cleaning cloths in % 25 Spin speed in rpm 1150 g factor 458 Tested operating hours 30000 Control system M Touch Pro Plus Programmability Freely programmable Max. delay start in h Freely selectable Time left display • Programme sequence indicator • Selectable display languages • Option to enter weight prior to start of programme • Standard/target grp programmes • Basic programmes • Dispensing • Detergent drawer 3 compartments Maximum number of connections for liquid dispenser pumps [number] 12 Empty sensor • Standard electrical connection Belectrical connection Heater rating in kW 9,00 Total connected load in kW 9,60 Fuse rating in A 16 Possible voltage variant 1 Electrical connected load in kW Fuse rating in A	Programme running time in minutes for Mops standard	47
Residual moisture when processing cleaning cloths in % 25 Spin speed in rpm 458 g factor 458 Tested operating hours 30000 Control system M Touch Pro Plus Freely programmability Max. delay start in h Freely selectable Selectable display languages Option to enter weight prior to start of programme Standard/target grp programmes		48
Spin speed in rpm		44
Spin speed in rpm	Residual moisture when processing cleaning cloths in %	25
g factor 458 Tested operating hours 30000 Control system M Touch Pro Plus Freely programmability Freely programmable Freely selectable Gisplay languages Gisplay languages Freely Selectable Gisplay languages Freely Selectable Gisplay languages Freely Selectable Gisplay languages Gi		
Tested operating hours Control system Control system Programmability Freely programmable Max. delay start in h Freely selectable Freely s		
Control system Control system Programmability Freely programmable Max. delay start in h Freely selectable Time left display Programme sequence indicator Selectable display languages Option to enter weight prior to start of programme Standard/target grp programmes Basic programmes Basic programmes Basic programmes Basic programmes Basic programmes Dispensing Detergent drawer Maximum number of connections for liquid dispenser pumps [number] Empty sensor Standard electrical connection Heating type Electrical connection Heating type Electrical connection Heater rating in kW 9,00 Total connected load in kW Fuse rating in A 16 Possible voltage variant 1 Electrical connection Bleater rating in kW 9,00 Total connected load in kW Fuse rating in A 16 Vater connected load in kW 9,60 Fuse rating in A 16 Water connection 18 N AC 400V 60HZ Heater rating in kW 9,00 Total connected load in kW Fuse rating in A 16 Vater connection 18 N AC 400V 60HZ Heater rating in A 16 Vater connection Hot water [number] 10 A 172" hose w/ 3/4" union Hot water [number] 10 A 172" hose w/ 3/4" union Hot water (optional) [number] Dump valve Dimensions and weight External dimensions, height in mm 1350 External dimensions, gross height in mm External dimensions, gross width in mm 1090 External dimensions, gross width in mm 1090		
Control system Programmability Programmability Freely programmable Max. delay start in h Freely selectable Time left display Programme sequence indicator Selectable display languages Option to enter weight prior to start of programme Standard/target grp programmes Basic programmes Basic programmes Basic programmes Basic programmes Detergent drawer Maximum number of connections for liquid dispenser pumps [number] Empty sensor Standard electrical connection Heating type Electrical connection Heater rating in kW 9,00 Total connected load in kW 9,60 Fuse rating in A Possible voltage variant 1 Electrical connection Heater rating in kW 9,60 Fuse rating in kW 9,60 Fuse rating in A 16 Water connected load in kW 9,60 Fuse rating in A 16 Water connection/drainage Cold water [number] 1x 1/2" hose w/ 3/4" union Dump valve Dimensions and weight External dimensions, height in mm 1350 External dimensions, gross height in mm External dimensions, gross beight in mm External dimensions, gross beight in mm External dimensions, gross beight in mm External dimensions, gross depth in mm 1130		
Programmability Max. delay start in h Time left display Programme sequence indicator Selectable display languages Option to enter weight prior to start of programme Standard/target grp programmes Basic programmes Dispensing Detergent drawer Maximum number of connections for liquid dispenser pumps [number] Empty sensor Standard electrical connection Heating type Electrical connection Heater rating in kW Total connected load in kW Fuse rating in A Possible voltage variant 1 Electrical connection Heater rating in A 16 Maxer connected load in kW Fuse rating in A Total connected load in kW Fuse rating in A Heater rating in A 16 Possible voltage variant 1 Electrical connection 3 N AC 400V 60HZ Heater rating in A 16 Maxer connection/drainage Cold water [number] 3 x 1/2" hose w/ 3/4" union 1x 1/2" hose w/ 3/4" union Dump valve Dimensions and weight External dimensions, height in mm 799 External dimensions, gross height in mm External dimensions, gross beight in mm External dimensions, gross depth in mm 1130		M Touch Pro Plus
Max. delay start in h Freely selectable Time left display • Programme sequence indicator • Selectable display languages • Option to enter weight prior to start of programme • Standard/target grp programmes • Basic programmes • Dispensing 12 Detergent drawer 3 compartments Maximum number of connections for liquid dispenser pumps [number] 12 Empty sensor • Standard electrical connection 12 Heating type Electrical Electrical connection 3N AC 400V 50HZ Heater rating in kW 9,00 Total connected load in kW 9,60 Fuse rating in A 16 Possible voltage variant 1 Electrical connection Electrical connected load in kW 9,60 Fuse rating in A 16 Water connection/drainage 3 x 1/2" hose w/ 3/4" union Cold water [number] 1 x 1/2" hose w/ 3/4" th. union Hot water (pumber] 1 x 1/2" hose w/ 3/4" union Dump valve DN 70 Dimensions and weight		
Time left display Programme sequence indicator Selectable display languages Option to enter weight prior to start of programme Standard/target grp programmes Basic programmes Basic programmes Dispensing Detergent drawer Maximum number of connections for liquid dispenser pumps [number] Empty sensor Standard electrical connection Heating type Electrical connection Heater rating in kW 9,00 Total connected load in kW 9,60 Fuse rating in A 16 Possible voltage variant 1 Electrical connection Heater rating in kW 9,00 Total connected load in kW 9,60 Fuse rating in kW 9,00 Total connection Heater rating in kW 16 Possible voltage variant 1 Electrical connection Heater rating in kW 10 Total connected load in kW 10 Total connection Total connection Total connection 3x x 1/2" hose w/ 3/4" union 16 Water connection/drainage Cold water [number] 1x 1/2" hose w/ 3/4" union 1x 1/2" hose w/ 3/4" union 1x 1/2" hose w/ 3/4" th. union 1x 1/2" hose w/ 3/4" union 1x 1/2" ho	- ·	
Programme sequence indicator Selectable display languages Option to enter weight prior to start of programme Standard/target grp programmes Basic programmes Detergent drawer Maximum number of connections for liquid dispenser pumps [number] Empty sensor Standard electrical connection Heating type Electrical connection Heater rating in kW 9,00 Total connected load in kW Fuse rating in A Possible voltage variant 1 Electrical connection Heater rating in kW 9,00 Total connected load in kW 9,60 Fuse rating in A 16 Possible voltage variant 1 Electrical connection Heater rating in kW 9,00 Total connected load in kW 9,60 Fuse rating in A 16 Water connection 3N AC 400V 60HZ Heater rating in A 16 Water connection/drainage Cold water [number] 1x 1/2" hose w/ 3/4" union Hard water (optional) [number] 2 x 1/2" w/ 3/4" union Dump valve DN 70 Dimensions and weight External dimensions, height in mm 1350 External dimensions, gross height in mm External dimensions, gross width in mm External dimensions, gross depth in mm 1130		_
Selectable display languages Option to enter weight prior to start of programme Standard/target grp programmes Basic programmes Dispensing Detergent drawer Maximum number of connections for liquid dispenser pumps [number] Empty sensor Standard electrical connection Heating type Electrical connection Heater rating in kW 9,00 Total connected load in kW Fuse rating in A Possible voltage variant 1 Electrical connected load in kW 9,60 Fuse rating in kW 9,00 Total connected load in kW 9,60 Fuse rating in kW 9,00 Total connected load in kW 9,60 Fuse rating in A 16 Water connection 3N AC 400V 60HZ Heater rating in kW 9,60 Fuse rating in A 16 Water (pumber) Fuse rating in A 16 Water connection/drainage Cold water [number] 3 x 1/2" hose w/ 3/4" union Hard water (optional) [number] 2 x 1/2" w/ 3/4" union Dump valve DN 70 Dimensions and weight External dimensions, height in mm 1350 External dimensions, gross height in mm 2924 External dimensions, gross width in mm 1480 External dimensions, gross width in mm External dimensions, gross width in mm 1130		
Option to enter weight prior to start of programme Standard/target grp programmes Basic programmes Dispensing Detergent drawer Maximum number of connections for liquid dispenser pumps [number] Empty sensor Standard electrical connection Heating type Electrical connection Heater rating in kW Total connected load in kW Fuse rating in A Possible voltage variant 1 Electrical connected load in kW Fuse rating in A Total connected load in kW Fuse rating in A Mater connected load in kW Fuse rating in A Total connected load in kW Fuse rating in A Total connected load in kW Fuse rating in A Sax 1/2" hose w/ 3/4" union Hot water [number] Hot water (optional) [number] Dump valve Dimensions and weight External dimensions, height in mm External dimensions, gross height in mm External dimensions, gross width in mm External dimensions, gross width in mm External dimensions, gross width in mm External dimensions, gross depth in mm External dimensions, gross width in mm External dimensions, gross width in mm External dimensions, gross width in mm External dimensions, gross depth in mm		
Standard/target grp programmes Basic programmes Dispensing Detergent drawer Maximum number of connections for liquid dispenser pumps [number] Empty sensor Standard electrical connection Heating type Electric Electrical connection Heater rating in kW Total connected load in kW Fuse rating in A Possible voltage variant 1 Electrical connection Heater rating in kW 7otal connected load in kW 9,60 Fuse rating in A 16 Possible voltage variant 1 Electrical connection 3N AC 400V 60HZ Heater rating in kW 9,60 Fuse rating in A 16 Water connected load in kW 9,60 Fuse rating in A 16 Water connection/drainage Cold water [number] 10 Hot water [number] 11 Lat 1/2" hose w/ 3/4" union Hard water (optional) [number] Dump valve Dimensions and weight External dimensions, height in mm 1350 External dimensions, depth in mm External dimensions, gross height in mm External dimensions, gross width in mm External dimensions, gross depth in mm External dimensions, gross width in mm External dimensions, gross depth in mm External dimensions, gross depth in mm		<u></u>
Basic programmes Dispensing Detergent drawer Maximum number of connections for liquid dispenser pumps [number] Empty sensor Standard electrical connection Heating type Electrical connection Heater rating in kW 9,00 Total connected load in kW Fuse rating in A Possible voltage variant 1 Electrical connection Heater rating in kW 9,00 Total connected load in kW 9,60 Fuse rating in A 16 Possible voltage variant 1 Electrical connection 3N AC 400V 60HZ Heater rating in kW 9,00 Total connected load in kW 9,60 Fuse rating in A 16 Water connection Total connected load in kW 9,60 Fuse rating in A 16 Water (pumber) Cold water [number] 10 Total connection/drainage Cold water [number] 3 x 1/2" hose w/ 3/4" union Hot water (optional) [number] Dump valve DN 70 Dimensions and weight External dimensions, height in mm 1350 External dimensions, deptth in mm 294 External dimensions, gross height in mm External dimensions, gross width in mm External dimensions, gross width in mm External dimensions, gross width in mm External dimensions, gross depth in mm		
Dispensing Detergent drawer Maximum number of connections for liquid dispenser pumps [number] Empty sensor Standard electrical connection Heating type Electrical connection Heater rating in kW Total connected load in kW Fuse rating in A Possible voltage variant 1 Electrical connection Heater rating in kW Total connected load in kW Fuse rating in A Possible voltage variant 1 Electrical connection 3N AC 400V 60HZ Heater rating in kW 9,00 Total connected load in kW 9,60 Fuse rating in A 16 Water connection/drainage Cold water [number] 1x 1/2" hose w/ 3/4" union Hot water [number] 1x 1/2" hose w/ 3/4" union Dump valve Dimensions and weight External dimensions, height in mm External dimensions, gross height in mm External dimensions, gross width in mm External dimensions, gross width in mm External dimensions, gross depth in mm 1130		
Detergent drawer Maximum number of connections for liquid dispenser pumps [number] Empty sensor Standard electrical connection Heating type Electrical connection Heater rating in kW Total connected load in kW 9,00 Total connection Heater rating in kW 7 og.00 Total connected load in kW 9,00 Total connected load in kW 9,60 Fuse rating in A 16 Water connection/drainage Cold water [number] 1 x 1/2" hose w/ 3/4" union Hot water [number] 1 x 1/2" hose w/ 3/4" union Dump valve Dimensions and weight External dimensions, height in mm External dimensions, gross height in mm External dimensions, gross width in mm External dimensions, gross beight in mm External dimensions, gross depth in mm External dimensions, gross depth in mm External dimensions, gross depth in mm 1130		•
Maximum number of connections for liquid dispenser pumps [number] 12 Empty sensor ● Standard electrical connection Electric Heating type Electric Electrical connection 3N AC 400V 50HZ Heater rating in kW 9,00 Total connected load in kW 9,60 Fuse rating in A 16 Possible voltage variant 1 Electrical connection Electrical connection 3N AC 400V 60HZ Heater rating in kW 9,00 Total connected load in kW 9,60 Fuse rating in A 16 Water connection/drainage 16 Cold water [number] 3 x 1/2" hose w/ 3/4" union Hot water [number] 1x 1/2" hose w/ 3/4" union Hard water (optional) [number] 2 x 1/2" w/ 3/4" union Dump valve DN 70 Dimensions and weight External dimensions, height in mm 1350 External dimensions, gross height in mm 1480 External dimensions, gross width in mm 1090 External dimensions, gross depth in mm 1130		
Empty sensor Standard electrical connection Heating type Electrical connection Heater rating in kW 9,00 Total connected load in kW 9,60 Fuse rating in A 16 Possible voltage variant 1 Electrical connection 3N AC 400V 60HZ Heater rating in kW 9,00 Total connected load in kW 9,60 Fuse rating in A 16 Possible voltage variant 1 Electrical connection 3N AC 400V 60HZ Heater rating in kW 9,00 Total connected load in kW 9,60 Fuse rating in A 16 Water connection/drainage Cold water [number] 3 x 1/2" hose w/ 3/4" union Hot water [number] 1x 1/2" hose w/ 3/4" th. union Hard water (optional) [number] 2 x x 1/2" w/ 3/4" union Dump valve DN 70 Dimensions and weight External dimensions, height in mm 1350 External dimensions, depth in mm 224 External dimensions, gross height in mm 1480 External dimensions, gross width in mm External dimensions, gross depth in mm 1130		_ -
Standard electrical connectionHeating typeElectricElectrical connection3N AC 400V 50HZHeater rating in kW9,00Total connected load in kW9,60Fuse rating in A16Possible voltage variant 1Electrical connectionElectrical connection3N AC 400V 60HZHeater rating in kW9,00Total connected load in kW9,60Fuse rating in A16Water connection/drainage3 x 1/2" hose w/ 3/4" unionCold water [number]3 x 1/2" hose w/ 3/4" unionHot water (optional) [number]2 x 1/2" w/ 3/4" unionDump valveDN 70Dimensions and weightDN 70External dimensions, height in mm1350External dimensions, width in mm799External dimensions, gross height in mm1480External dimensions, gross width in mm1090External dimensions, gross depth in mm1130		12
Heating type Electrical connection 3N AC 400V 50HZ Heater rating in kW 9,00 Total connected load in kW Fuse rating in A Possible voltage variant 1 Electrical connection 3N AC 400V 60HZ Heater rating in kW 9,00 Total connected load in kW 9,00 Total connection 16 Water cannected load in kW 9,60 Fuse rating in A 16 Water connection/drainage Cold water [number] 3 x 1/2" hose w/ 3/4" union Hot water [number] 1x 1/2" hose w/ 3/4" th. union Hard water (optional) [number] 2 x 1/2" w/ 3/4" union Dump valve Dimensions and weight External dimensions, height in mm 1350 External dimensions, gross height in mm 224 External dimensions, gross height in mm External dimensions, gross width in mm 1090 External dimensions, gross depth in mm External dimensions, gross depth in mm External dimensions, gross depth in mm 1130	Empty sensor	•
Electrical connection Heater rating in kW 9,00 Total connected load in kW Fuse rating in A Possible voltage variant 1 Electrical connection Heater rating in kW 9,00 Total connected load in kW 9,00 Total connected load in kW 9,00 Total connected load in kW 9,60 Fuse rating in A 16 Water connection/drainage Cold water [number] 3 x 1/2" hose w/ 3/4" union Hot water [number] 1x 1/2" hose w/ 3/4" th. union Hard water (optional) [number] 2 x 1/2" w/ 3/4" union Dump valve Dimensions and weight External dimensions, height in mm 1350 External dimensions, depth in mm 924 External dimensions, gross height in mm External dimensions, gross width in mm External dimensions, gross width in mm External dimensions, gross width in mm External dimensions, gross depth in mm 1130	Standard electrical connection	
Heater rating in kW Total connected load in kW Fuse rating in A Fossible voltage variant 1 Electrical connection Heater rating in kW Total connected load in kW Fuse rating in kW Fuse rating in kW Fuse rating in A Fuse rating in	Heating type	Electric
Total connected load in kW 9,60 Fuse rating in A 16 Possible voltage variant 1 3N AC 400V 60HZ Electrical connection 3N AC 400V 60HZ Heater rating in kW 9,00 Total connected load in kW 9,60 Fuse rating in A 16 Water connection/drainage 20 Cold water [number] 3 x 1/2" hose w/ 3/4" union Hot water [number] 1x 1/2" hose w/ 3/4" th. union Hard water (optional) [number] 2 x 1/2" w/ 3/4" union Dump valve DN 70 Dimensions and weight External dimensions, height in mm 1350 External dimensions, width in mm 799 External dimensions, gross height in mm 1480 External dimensions, gross width in mm 1090 External dimensions, gross depth in mm 1130	Electrical connection	3N AC 400V 50HZ
Fuse rating in A Possible voltage variant 1 Electrical connection Heater rating in kW 7otal connected load in kW Fuse rating in A Water connection/drainage Cold water [number] Hot water [number] Hard water (optional) [number] Dump valve Dimensions and weight External dimensions, height in mm External dimensions, gross height in mm External dimensions, gross width in mm External dimensions, gross depth in mm 1130	Heater rating in kW	9,00
Possible voltage variant 1 Electrical connection 3N AC 400V 60HZ Heater rating in kW 9,00 Total connected load in kW 9,60 Fuse rating in A 16 Water connection/drainage Cold water [number] 3 x 1/2" hose w/ 3/4" union Hot water [number] 1x 1/2" hose w/ 3/4" th. union Hard water (optional) [number] 2 x 1/2" w/ 3/4" union Dump valve DN 70 Dimensions and weight External dimensions, height in mm 1350 External dimensions, depth in mm 924 External dimensions, gross height in mm 1480 External dimensions, gross width in mm 1090 External dimensions, gross depth in mm 1130	Total connected load in kW	9,60
Electrical connection 3N AC 400V 60HZ Heater rating in kW 9,00 Total connected load in kW 9,60 Fuse rating in A 16 Water connection/drainage 3 x 1/2" hose w/ 3/4" union Cold water [number] 1x 1/2" hose w/ 3/4" union Hot water (number] 2 x 1/2" w/ 3/4" union Dump valve (potional) [number] 2 x 1/2" w/ 3/4" union Dump valve (pimensions and weight 2 x 1/2" w/ 3/4" union External dimensions, height in mm 1350 External dimensions, width in mm 799 External dimensions, depth in mm 924 External dimensions, gross height in mm 1480 External dimensions, gross width in mm 1090 External dimensions, gross depth in mm 1130	Fuse rating in A	16
Heater rating in kW Total connected load in kW Fuse rating in A Water connection/drainage Cold water [number] 1x 1/2" hose w/ 3/4" union Hot water [number] 1x 1/2" hose w/ 3/4" union Hard water (optional) [number] 2 x 1/2" w/ 3/4" union Dump valve DN 70 Dimensions and weight External dimensions, height in mm 1350 External dimensions, depth in mm External dimensions, gross height in mm 1480 External dimensions, gross width in mm External dimensions, gross depth in mm External dimensions, gross depth in mm External dimensions, gross depth in mm 1130	Possible voltage variant 1	
Total connected load in kW 9,60 Fuse rating in A 16 Water connection/drainage 3 x 1/2" hose w/ 3/4" union Cold water [number] 1x 1/2" hose w/ 3/4" th. union Hot water (number] 2 x 1/2" w/ 3/4" th. union Dump valve DN 70 Dimensions and weight External dimensions, height in mm External dimensions, width in mm 799 External dimensions, depth in mm 924 External dimensions, gross height in mm 1480 External dimensions, gross width in mm 1090 External dimensions, gross depth in mm 1130	Electrical connection	3N AC 400V 60HZ
Fuse rating in A Water connection/drainage Cold water [number] Hot water [number] Hard water (optional) [number] Dump valve Dimensions and weight External dimensions, height in mm External dimensions, gross height in mm External dimensions, gross width in mm External dimensions, gross width in mm External dimensions, gross width in mm External dimensions, gross depth in mm Dump valve DN 70 Dimensions 1350 External dimensions, width in mm 1480 External dimensions, gross depth in mm 1090 External dimensions, gross depth in mm	Heater rating in kW	9,00
Water connection/drainage Cold water [number] 3 x 1/2" hose w/ 3/4" union Hot water [number] 1x 1/2" hose w/ 3/4" th. union Hard water (optional) [number] 2 x 1/2" w/ 3/4" union Dump valve DN 70 Dimensions and weight External dimensions, height in mm 1350 External dimensions, width in mm 799 External dimensions, depth in mm 924 External dimensions, gross height in mm 1480 External dimensions, gross width in mm 1090 External dimensions, gross depth in mm 1130	Total connected load in kW	9,60
Cold water [number] Hot water [number] 1x 1/2" hose w/ 3/4" union 1x 1/2" hose w/ 3/4" th. union Hard water (optional) [number] 2 x 1/2" w/ 3/4" union Dump valve DN 70 Dimensions and weight External dimensions, height in mm 1350 External dimensions, width in mm 799 External dimensions, depth in mm External dimensions, gross height in mm 1480 External dimensions, gross width in mm External dimensions, gross depth in mm 1090 External dimensions, gross depth in mm	Fuse rating in A	16
Hot water [number] Tx 1/2" hose w/ 3/4" th. union Union	Water connection/drainage	
Hard water (optional) [number] 2 x 1/2" w/ 3/4" union Dump valve DN 70 Dimensions and weight External dimensions, height in mm 1350 External dimensions, width in mm 799 External dimensions, depth in mm 924 External dimensions, gross height in mm 1480 External dimensions, gross width in mm 1090 External dimensions, gross depth in mm 1130	Cold water [number]	3 x 1/2" hose w/ 3/4" union
Dump valve Dimensions and weight External dimensions, height in mm External dimensions, width in mm Top9 External dimensions, depth in mm External dimensions, gross height in mm External dimensions, gross width in mm External dimensions, gross width in mm External dimensions, gross width in mm External dimensions, gross depth in mm 1130	Hot water [number]	
Dump valve Dimensions and weight External dimensions, height in mm External dimensions, width in mm Type External dimensions, depth in mm External dimensions, gross height in mm External dimensions, gross width in mm External dimensions, gross width in mm External dimensions, gross depth in mm 1090 External dimensions, gross depth in mm 1130	Hard water (optional) [number]	2 x 1/2" w/ 3/4" union
Dimensions and weightExternal dimensions, height in mm1350External dimensions, width in mm799External dimensions, depth in mm924External dimensions, gross height in mm1480External dimensions, gross width in mm1090External dimensions, gross depth in mm1130		DN 70
External dimensions, height in mm 1350 External dimensions, width in mm 799 External dimensions, depth in mm 924 External dimensions, gross height in mm 1480 External dimensions, gross width in mm 1090 External dimensions, gross depth in mm 1130		
External dimensions, width in mm 799 External dimensions, depth in mm 924 External dimensions, gross height in mm 1480 External dimensions, gross width in mm 1090 External dimensions, gross depth in mm 1130		1350
External dimensions, depth in mm 924 External dimensions, gross height in mm 1480 External dimensions, gross width in mm 1090 External dimensions, gross depth in mm 1130		
External dimensions, gross height in mm 1480 External dimensions, gross width in mm 1090 External dimensions, gross depth in mm 1130		
External dimensions, gross width in mm 1090 External dimensions, gross depth in mm 1130		
External dimensions, gross depth in mm 1130		
THOC WOIGHT IN THE		
	The moight in hig	



PWM 912 [EL DV DD SOM]

Professional washing machine, electrically heated, with drain valve and detergent drawer, M Touch Pro Plus freely programmable, for marine use.

EAN: 4002516391586 / Material number: 11682920 / Old Material Number: 51912001SOM

Gross weight in kg	290
Maximum floor load in N/m ²	4402
Emissions data	
Emission sound pressure level in the workplace	65 dB(A) re 20 µPa
Heat dissipation into the room in MJ/h	6,48
Features	
Patented pre-spin	•
Cloth reprocessing	•
3-dimensional imbalance monitoring	•
Disinfection rinse	•
Efficient scoop-and-ladle ribs	•
EcoSpeed	•
Spring-in-spring system	•
Temperature monitoring	•
Special heater element	•
Automatic load control+	
Volumetric flow meter (optional)	•
Weighing plinth (optional)	•
	•
Add laundry Programme selection via colour frame	•
	`
Emergency switch-off Machine independent appearance	`
Machine-independent accessories	
Efficiency and sustainability	01
Recycling rate in %	91
Connection options	
Payment system (optional)	•
Optical interface for service access	<u>•</u>
Peak load cut-out/energy management (optional)	<u>•</u>
Water recovery (optional)	<u> </u>
LAN	<u>•</u>
WiFi	<u>•</u>
Connector Box	•
Capacities	
Respirator masks [number]	10
Helmets [number]	3
Overalls [number]	2
Over jackets [number]	3
Chemical protection suits [number]	1
Synthetic duvets [number]	1
Synthetic pillows [number]	2
Down duvets [number]	1
Down pillows [number]	2
Cloths, 22 g [number]	
Cotton mops, 40 cm / 190 g [number]	64
Cotton mops, 50 cm / 220 g [number]	56
Microfibre mops, 40 cm / 120 g [number]	100
Microfibre mops, 50 cm / 170 g [number]	72
Mops, office, 100 g [quantity]	120
Mops, stairway, 150 g [quantity]	80
Summer horse blankets [number]	2



PWM 912 [EL DV DD SOM]

Professional washing machine, electrically heated, with drain valve and detergent drawer, M Touch Pro Plus freely programmable, for marine use.



EAN: 4002516391586 / Material number: 11682920 / Old Material Number: 51912001SOM

Standards, test certificates and symbols	
CE	•
VDE-EMC	•
VDE	•
Splash-proof safety rating IPX4	•
UKCA	•
WEEE	•
EAC	•
Complies with Machinery Directive 2006/42/EC	

Complies with Machinery Directive 2006/42/EC