Miele

PW 6243 [EL WEK]

Hygiene washing machine, electrically heated

Barrier machine for retirement and care homes as well as hospitals.



- Drum volume 240 I, load size 24.0 kg
- Wide variety of programmes special disinfection programme
- Gentle laundry care thanks to the Miele honeycomb drum
- Particularly efficient low water and energy consumption
- Perfect spinning results residual moisture 46 %*, g-factor360

EAN: 4002516446996 / Material number: 11812870 / Old Material Number: 51624305ZER

Overlanding Lawrence and America	
Construction type and version	I I aliana a salaha a sasahira
Construction type	Hygiene washing machine
Range	Professional
Front	Iron grey
Load ratio	1:10
Load in kg	24,0
Drum volume in I	240
Door opening [W] in mm clean side	352
Door opening [H] in mm clean side	593
Door opening [W] in mm unclean side	352
Door opening [H] in mm unclean side	593
Door opening angle in degrees	153
Maintenance-free motor with frequency converter	•
Honeycomb drum	•
Application	
Suitable for retirement and care homes	•
Suitable for facility management	•
Suitable for commercial laundries	•
Suitable for fire brigades and rescue services	•
Suitable for hospitals	•
Performance data	
Tested virucidal efficacy	•
Proven hygiene	•
Specific water consumption for hot water connection in I/kg	10,63
Specific energy consumption for hot water connection in	0,09
kWh/kg	
Programme duration in minutes with cold water connection	68
Programme duration in minutes with cold water and hot water connection	53
Residual moisture with cold rinse in %	50
Residual moisture with hot rinse in %	46
Spin speed in rpm	975
g factor	360
Tested operating hours	30000
Control system	
Control system	Profitronic M
Programmability	Freely programmable
Max. delay start in h	Freely selectable
Time left display	•
Programme sequence indicator	•
Selectable display languages	•
Standard/target grp programmes	
Basic programmes	•
Programmes for the hotel and catering industry	•
Programmes for retirement and care homes	•
Programmes for facility management	•
Programmes for dry cleaners	•
Programmes for small businesses	•
Programmes for fire brigades and rescue services	•
Programmes for studs, riding schools, and stables	

^{*}Residual moisture specification relates to a hot rinse during the last rinse cycle.



PW 6243 [EL WEK]

Hygiene washing machine, electrically heated Barrier machine for retirement and care homes as well as hospitals.



EAN: 4002516446996 / Material number: 11812870 / Old Material Number: 51624305ZER

Programmes for beauty clinics, spas, and fitness studios Dispensing Detergent drawer	Programmes for hospitals	•
Detergent drawer Liquid dispensing module (optional) Maximum number of connections for liquid dispenser pumps [number] Empty sensor Standard electrical connection Heating type Electrical connection Heating type Electrical connection Heating in kW 24,00 Total connected load in kW 25,00 Fuse rating in A 50 Water connection/drainage Cold water [number] Lx 1/2" hose w/ 3/4" th. union Dump valve DN 70 Dimensions and weight External dimensions, height in mm 1718 External dimensions, depth in mm 1384 External dimensions, gross height in mm 1570 External dimensions, gross width in mm 1138 Net weight in kg 820,0 Gross weight in kg 838 Maximum floor load in N/m² Emissions data Emission sound pressure level in the workplace Patented pre-spin Cloth reprocessing Imbalance monitoring Temperature monitori	Programmes for beauty clinics, spas, and fitness studios	•
Liquid dispensing module (optional) Maximum number of connections for liquid dispenser pumps [number] Empty sensor Standard electrical connection Heating type Electrical connection Heater rating in kW 24,00 Total connected load in kW 25,00 Fuse rating in A Water connection/drainage Cold water [number] Lix 1/2* hose w/ 3/4* th. union Dump valve DN 70 Dimensions and weight External dimensions, height in mm 1718 External dimensions, width in mm External dimensions, depth in mm 1570 External dimensions, gross width in mm 1138 Net weight in kg Maximum floor load in N/m² Pasus weight in kg Maximum floor load in N/m² Pasus weight in kg Maximum floor load in N/m² Patented pre-spin Cloth reprocessing Imbalance monitoring Temperature monitor	Dispensing	
Maximum number of connections for liquid dispenser pumps [number] Empty sensor Standard electrical connection Heating type Electrical connection Heater rating in kW 24,00 Total connected load in kW 7 25,00 Fuse rating in A Water connection/drainage Cold water [number] Let water [number] Dump valve Dimensions and weight External dimensions, height in mm External dimensions, depth in mm 1718 External dimensions, gross height in mm External dimensions, gross width in mm External dimensions, gross width in mm 1570 External dimensions, gross width in mm 1138 Ret weight in kg Gross weight in kg Brission sound pressure level in the workplace Heat dissipation into the room in MJ/h Peatures Patente or monitoring Temperature moni	Detergent drawer	4 compartments
pumps [number] Empty sensor • Standard electrical connection • Electric 3N AC 400V 50/60HZ Heater rating in kW 24,00 Total connected load in kW 25,00 Fuse rating in A 50 Water connection/drainage 2x 1/2* hose w/ 3/4* th. union Cold water [number] 1x 1/2* hose w/ 3/4* th. union Hot water [number] 1x 1/2* hose w/ 3/4* th. union Dump valve DN 70 Dimensions and weight External dimensions, height in mm External dimensions, height in mm 1718 External dimensions, gross height in mm 1070 External dimensions, gross height in mm 1800 External dimensions, gross height in mm 1570 External dimensions, gross beight in mm 1138 Net weight in kg 820,0 Gross weight in kg 838 Maximum floor load in N/m² 9808 Emission south pressure level in the workplace 71 dB(A) re 20 μPa Heat dissipation into the room in MJ/h 9,00 Features Patented pre-spin • </td <td>Liquid dispensing module (optional)</td> <td>•</td>	Liquid dispensing module (optional)	•
Empty sensor Standard electrical connection Heating type Electrical connection Heating type Electrical connection 3N AC 400V 50/60HZ Heater rating in kW 24,00 Total connected load in kW 25,00 Fuse rating in A Water connection/drainage Cold water [number] Lat 1/2" hose w/ 3/4" th. union Dump valve Dimensions and weight External dimensions, height in mm 1718 External dimensions, width in mm 1884 External dimensions, depth in mm 1070 External dimensions, gross width in mm 11800 External dimensions, gross width in mm 11880 External dimensions, gross width in mm 1570 External dimensions, gross width in mm 1670 External dimensions, gross width in mm 1880 Fishing 820,0 Gross weight in kg 820,0 Gross weight in kg 838 Maximum floor load in N/m² 9808 Emission sound pressure level in the workplace Tidskispiation into the room in MJ/h 9,00 Features Patented pre-spin Cloth reprocessing Imbalance monitioring - Temperature monitoring - Temperature monitorin	Maximum number of connections for liquid dispenser	12
Standard electrical connection Heating type	pumps [number]	
Heating type Electrical connection 3N AC 400V 50/60HZ Heater rating in kW 24,00 Total connected load in kW 25,00 Fuse rating in A 50 Water connection/drainage Cold water [number] 2x 1/2" hose w/ 3/4" th. union Hot water [number] 1x 1/2" hose w/ 3/4" th. union Dump valve DN 70 Dimensions and weight External dimensions, height in mm 1718 External dimensions, width in mm 1384 External dimensions, depth in mm 1070 External dimensions, gross height in mm 1570 External dimensions, gross width in mm 1580 External dimensions, gross width in mm 1570 External dimensions, gross depth in mm 1138 Net weight in kg 820,0 Gross weight in kg 838 Maximum floor load in N/m² 9808 Emissions data Emission sound pressure level in the workplace 71 dB(A) re 20 μPa Heat dissipation into the room in MJ/h 9,00 Features Patented pre-spin • Cloth reprocessing • Imbalance monitoring • Temperature monitoring •		•
Electrical connection 3N AC 400V 50/60HZ Heater rating in kW 24,00 Total connected load in kW 25,00 Fuse rating in A 50 Water connection/drainage 2x 1/2" hose w/ 3/4" th. union Cold water [number] 1x 1/2" hose w/ 3/4" th. union Dump valve DN 70 Dimensions and weight External climensions, height in mm External dimensions, width in mm 1718 External dimensions, depth in mm 1070 External dimensions, gross height in mm 1800 External dimensions, gross width in mm 1570 External dimensions, gross depth in mm 1138 Net weight in kg 820,0 Gross weight in kg 838 Maximum floor load in N/m² 9808 Emission sound pressure level in the workplace 71 dB(A) re 20 μPa Heat dissipation into the room in MJ/h 9,00 Features • Patented pre-spin • Cloth reprocessing • Imbalance monitoring • Temperature monitoring • Temp		
Heater rating in kW Total connected load in kW 25,00 Fuse rating in A So Water connection/drainage Cold water [number] Hot water [number] Dump valve Dimensions and weight External dimensions, height in mm External dimensions, width in mm 1070 External dimensions, gross height in mm 1480 External dimensions, gross height in mm 1570 External dimensions, gross height in mm 1570 External dimensions, gross depth in mm 1580 External dimensions, gross depth in mm 1570 External dimensions, gross depth in mm 1580 External dimensions, gross depth in mm 1580 External dimensions, gross depth in mm 1580 External dimensions, gross depth in mm 1570 External dimensions, gross depth in mm 1138 Net weight in kg 820,0 Gross weight in kg 838 Maximum floor load in N/m² 9808 Emission sound pressure level in the workplace Heat dissipation into the room in MJ/h 9,00 Features Patented pre-spin Cloth reprocessing Imbalance monitoring	Heating type	
Total connected load in kW Fuse rating in A Water connection/drainage Cold water [number] Lex 1/2" hose w/ 3/4" th. union Dump valve Dimensions and weight External dimensions, height in mm External dimensions, depth in mm External dimensions, depth in mm External dimensions, gross height in mm External dimensions, gross width in mm External dimensions, gross depth in mm External dimensions, gross depth in mm External dimensions, gross depth in mm 1138 Net weight in kg Ba20,0 Gross weight in kg Ba38 Maximum floor load in N/m² Benissions data Emissions oaund pressure level in the workplace Heat dissipation into the room in MJ/h Peatures Patented pre-spin Cloth reprocessing Imbalance monitoring Temperature monitoring Temperature monitoring Temperature monitoring Temperature monitoring Temperature monitoring Temperature monitoring Automatic drum positioning and locking Special heater element Automatic drum positioning and locking Special heater element 4 Volumetric flow meter (optional) Communication slot Emergency switch-off Machine-independent accessories Efficiency and sustainability Recycling rate in % Connection options Optical interface for service access		3N AC 400V 50/60HZ
Fuse rating in A Water connection/drainage Cold water [number] Dump valve Dimensions and weight External dimensions, height in mm External dimensions, depth in mm External dimensions, gross height in mm External dimensions, gross height in mm External dimensions, gross height in mm External dimensions, gross beight in mm External dimensions, gross height in mm External dimensions, gross beight in mm External dimensions, gross beight in mm External dimensions, gross depth in mm External dimensions, gross depth in mm 11380 External dimensions, gross depth in mm 1138 Net weight in kg Resistion sound pressure level in the workplace Emission sound pressure level in the workplace Features Patented pre-spin Cloth reprocessing Imbalance monitoring Temperature monitoring Temperature monitoring Temperature monitoring Temperature monitoring Two indicator lights on the clean side Automatic drum positioning and locking Special heater element Automatic load control+ Volumetric flow meter (optional) Communication slot Emergency switch-off Machine-independent accessories Efficiency and sustainability Recycling rate in % Connection options Optical interface for service access	Heater rating in kW	24,00
Water connection/drainage 2x 1/2" hose w/ 3/4" th. union Hot water [number] 2x 1/2" hose w/ 3/4" th. union Dump valve DN 70 Dimensions and weight External dimensions, height in mm External dimensions, width in mm 1718 External dimensions, depth in mm 1070 External dimensions, gross height in mm 1800 External dimensions, gross width in mm 1570 External dimensions, gross depth in mm 1138 Net weight in kg 820,0 Gross weight in kg 838 Maximum floor load in N/m² 9808 Emission sound pressure level in the workplace 71 dB(A) re 20 μPa Heat dissipation into the room in MJ/h 9,00 Features Patented pre-spin • Cloth reprocessing • Imbalance monitoring • Temperature monitoring • Temperature monitoring • Town indicator lights on the clean side • Automatic dum positioning and locking • Special heater element • Automatic load control+ • Volumetric flow meter (optional)		25,00
Cold water [number]	Fuse rating in A	50
Hot water [number] union Dump valve DN 70 Dimensions and weight External dimensions, height in mm External dimensions, width in mm 1718 External dimensions, depth in mm 1384 External dimensions, gross height in mm 1070 External dimensions, gross width in mm 1570 External dimensions, gross width in mm 1138 Net weight in kg 820,0 Gross weight in kg 838 Maximum floor load in N/m² 9808 Emissions data *** Emission sound pressure level in the workplace 71 dB(A) re 20 μPa Heat dissipation into the room in MJ/h 9,00 Features *** Patented pre-spin • Cloth reprocessing • Imbalance monitoring • Temperature monitoring • Two indicator lights on the clean side • Automatic load control+ • Volumetric flow meter (optional) • Communication slot • Emergency switch-off • Machine-independent accessories •	Water connection/drainage	
Hot water [number] Dump valve Dimensions and weight External dimensions, height in mm External dimensions, width in mm External dimensions, gross height in mm External dimensions, gross width in mm External dimensions, gross depth in mm External dimensions, gross height in mm 1570 External dimensions, gross height in mm	Cold water [number]	
Dump valve Dimensions and weight External dimensions, height in mm External dimensions, width in mm External dimensions, width in mm External dimensions, gross height in mm External dimensions, gross height in mm External dimensions, gross height in mm External dimensions, gross width in mm External dimensions, gross width in mm External dimensions, gross width in mm External dimensions, gross depth in mm External dimensions, gross width in mm External dimensions, sports height External dimensions, width in mm External dimensions, profile and to 1570 External dimensions, width in mm External dimensions, profile and to 1570 External dimensions, width in mm External dimensions, profile and 1570 External dimensions, width in mm External dimensions, profile and 1570 External dimensions, width in mm External dimensions, profile and 1570 External dimensions, width in mm External dimensions, profile and 1570 External		
Dump valve Dimensions and weight External dimensions, height in mm External dimensions, width in mm 1384 External dimensions, depth in mm 1070 External dimensions, gross height in mm 1800 External dimensions, gross height in mm 1570 External dimensions, gross width in mm 1138 Net weight in kg Rezo,0 Gross weight in kg Rezo,0 Gr	Hot water [number]	
Dimensions and weight External dimensions, height in mm 1718 External dimensions, width in mm 1384 External dimensions, depth in mm 1070 External dimensions, gross height in mm 1800 External dimensions, gross width in mm 1570 External dimensions, gross depth in mm 1138 Net weight in kg 820,0 Gross weight in kg 838 Maximum floor load in N/m² 9808 Emissions data 71 dB(A) re 20 μPa Heat dissipation into the room in MJ/h 9,00 Features 9,00 Patented pre-spin • Cloth reprocessing • Imbalance monitoring • Temperature monitoring • Two indicator lights on the clean side • Automatic drum positioning and locking • Special heater element • Automatic load control+ • Volumetric flow meter (optional) • Communication slot • Emergency switch-off • Machine-independent accessories • Efficiency and sustainability		-
External dimensions, height in mm External dimensions, width in mm 1384 External dimensions, width in mm 1070 External dimensions, gross height in mm 1800 External dimensions, gross width in mm 1570 External dimensions, gross width in mm 1570 External dimensions, gross depth in mm 1138 Net weight in kg 820,0 Gross weight in kg 838 Maximum floor load in N/m² 9808 Emissions data Emission sound pressure level in the workplace Heat dissipation into the room in MJ/h 9,00 Features Patented pre-spin Cloth reprocessing Imbalance monitoring Temperature monitoring Temperature monitoring Two indicator lights on the clean side Automatic drum positioning and locking Special heater element Automatic load control+ Volumetric flow meter (optional) Communication slot Emergency switch-off Machine-independent accessories Efficiency and sustainability Recycling rate in % Connection options Optical interface for service access		DN 70
External dimensions, width in mm External dimensions, depth in mm External dimensions, gross height in mm External dimensions, gross height in mm External dimensions, gross width in mm External dimensions, gross width in mm External dimensions, gross width in mm External dimensions, gross depth in mm External dimensions, gross width in mm External dimensions, gross height in mm External dimensions, gross width in mm External dimensions, gross height in mm External dimensions, gross width in mm External dimensions, gross width in mm External dimensions, gross height in mm External dimensions, gross width in mm External dimensions, gross depth in mm External dimensions, gross depth in mm External dimensions, gross deferth in mm External dimensions, gross degth in mm External dimensions, gross degth in mm Exte		1710
External dimensions, depth in mm External dimensions, gross height in mm External dimensions, gross width in mm External dimensions, gross width in mm External dimensions, gross width in mm External dimensions, gross depth in mm 1138 Net weight in kg Record of the kg Record o		
External dimensions, gross height in mm External dimensions, gross width in mm External dimensions, gross width in mm External dimensions, gross depth in mm 1138 Net weight in kg B20,0 Gross weight in kg B38 Maximum floor load in N/m² 9808 Emissions data Emission sound pressure level in the workplace Heat dissipation into the room in MJ/h 9,00 Features Patented pre-spin Cloth reprocessing Imbalance monitoring Temperature monitoring Two indicator lights on the clean side Automatic drum positioning and locking Special heater element Automatic load control+ Volumetric flow meter (optional) Communication slot Emergency switch-off Machine-independent accessories Efficiency and sustainability Recycling rate in % Connection options Optical interface for service access	· · · · · · · · · · · · · · · · · · ·	
External dimensions, gross width in mm External dimensions, gross depth in mm 1138 Net weight in kg Reso,0 Gross weight in kg Reso,0 Gross weight in kg Resistant floor load in N/m² Remissions data Emission sound pressure level in the workplace Heat dissipation into the room in MJ/h Reatures Patented pre-spin Cloth reprocessing Imbalance monitoring Temperature monitoring Temperature monitoring Two indicator lights on the clean side Automatic drum positioning and locking Special heater element Automatic load control+ Volumetric flow meter (optional) Communication slot Emergency switch-off Machine-independent accessories Efficiency and sustainability Recycling rate in % Connection options Optical interface for service access		-
External dimensions, gross depth in mm Net weight in kg Record weight		
Net weight in kg 820,0 Gross weight in kg 838 Maximum floor load in N/m² 9808 Emissions data 71 dB(A) re 20 μPa Emission sound pressure level in the workplace 71 dB(A) re 20 μPa Heat dissipation into the room in MJ/h 9,00 Features ** Patented pre-spin • Cloth reprocessing • Imbalance monitoring • Temperature monitoring • Two indicator lights on the clean side • Automatic drum positioning and locking • Special heater element • Automatic load control+ • Volumetric flow meter (optional) • Communication slot • Emergency switch-off • Machine-independent accessories • Efficiency and sustainability Recycling rate in % 95 Connection options • Optical interface for service access •		
Gross weight in kg Maximum floor load in N/m² Emissions data Emission sound pressure level in the workplace Heat dissipation into the room in MJ/h Features Patented pre-spin Cloth reprocessing Imbalance monitoring Temperature monitoring Two indicator lights on the clean side Automatic drum positioning and locking Special heater element Automatic load control+ Volumetric flow meter (optional) Communication slot Emergency switch-off Machine-independent accessories Efficiency and sustainability Recycling rate in % Optical interface for service access •		
Maximum floor load in N/m² 9808 Emissions data 71 dB(A) re 20 μPa Heat dissipation into the room in MJ/h 9,00 Features 9,00 Patented pre-spin • Cloth reprocessing • Imbalance monitoring • Temperature monitoring • Two indicator lights on the clean side • Automatic drum positioning and locking • Special heater element • Automatic load control+ • Volumetric flow meter (optional) • Communication slot • Emergency switch-off • Machine-independent accessories • Efficiency and sustainability 95 Connection options • Optical interface for service access •		
Emissions data Emission sound pressure level in the workplace Heat dissipation into the room in MJ/h Patented pre-spin Cloth reprocessing Imbalance monitoring Temperature monitoring Two indicator lights on the clean side Automatic drum positioning and locking Special heater element Automatic load control+ Volumetric flow meter (optional) Communication slot Emergency switch-off Machine-independent accessories Efficiency and sustainability Recycling rate in % Connection options Optical interface for service access		-
Emission sound pressure level in the workplace Heat dissipation into the room in MJ/h Peatures Patented pre-spin Cloth reprocessing Imbalance monitoring Temperature monitoring Two indicator lights on the clean side Automatic drum positioning and locking Special heater element Automatic load control+ Volumetric flow meter (optional) Communication slot Emergency switch-off Machine-independent accessories Efficiency and sustainability Recycling rate in % Connection options Optical interface for service access		9808
Heat dissipation into the room in MJ/h Features Patented pre-spin Cloth reprocessing Imbalance monitoring Temperature monitoring Two indicator lights on the clean side Automatic drum positioning and locking Special heater element Automatic load control+ Volumetric flow meter (optional) Communication slot Emergency switch-off Machine-independent accessories Efficiency and sustainability Recycling rate in % Optical interface for service access		
Patented pre-spin Cloth reprocessing Imbalance monitoring Temperature monitoring Two indicator lights on the clean side Automatic drum positioning and locking Special heater element Automatic load control+ Volumetric flow meter (optional) Communication slot Emergency switch-off Machine-independent accessories Efficiency and sustainability Recycling rate in % Optical interface for service access		71 dB(A) re 20 μPa
Patented pre-spin Cloth reprocessing Imbalance monitoring Temperature monitoring Two indicator lights on the clean side Automatic drum positioning and locking Special heater element Automatic load control+ Volumetric flow meter (optional) Communication slot Emergency switch-off Machine-independent accessories Efficiency and sustainability Recycling rate in % Optical interface for service access	·	9,00
Cloth reprocessing Imbalance monitoring Temperature monitoring Two indicator lights on the clean side Automatic drum positioning and locking Special heater element Automatic load control+ Volumetric flow meter (optional) Communication slot Emergency switch-off Machine-independent accessories Efficiency and sustainability Recycling rate in % Optical interface for service access		
Imbalance monitoring Temperature monitoring Two indicator lights on the clean side Automatic drum positioning and locking Special heater element Automatic load control+ Volumetric flow meter (optional) Communication slot Emergency switch-off Machine-independent accessories Efficiency and sustainability Recycling rate in % Optical interface for service access		
Temperature monitoring Two indicator lights on the clean side Automatic drum positioning and locking Special heater element Automatic load control+ Volumetric flow meter (optional) Communication slot Emergency switch-off Machine-independent accessories Efficiency and sustainability Recycling rate in % Optical interface for service access		
Two indicator lights on the clean side Automatic drum positioning and locking Special heater element Automatic load control+ Volumetric flow meter (optional) Communication slot Emergency switch-off Machine-independent accessories Efficiency and sustainability Recycling rate in % Connection options Optical interface for service access		•
Automatic drum positioning and locking Special heater element Automatic load control+ Volumetric flow meter (optional) Communication slot Emergency switch-off Machine-independent accessories Efficiency and sustainability Recycling rate in % Connection options Optical interface for service access		<u>•</u>
Special heater element Automatic load control+ Volumetric flow meter (optional) Communication slot Emergency switch-off Machine-independent accessories Efficiency and sustainability Recycling rate in % Connection options Optical interface for service access	Two indicator lights on the clean side	<u>•</u>
Automatic load control+ Volumetric flow meter (optional) Communication slot Emergency switch-off Machine-independent accessories Efficiency and sustainability Recycling rate in % Connection options Optical interface for service access	Automatic drum positioning and locking	•
Volumetric flow meter (optional) Communication slot Emergency switch-off Machine-independent accessories Efficiency and sustainability Recycling rate in % Connection options Optical interface for service access	Special heater element	•
Communication slot Emergency switch-off Machine-independent accessories Efficiency and sustainability Recycling rate in % Connection options Optical interface for service access	Automatic load control+	<u>•</u>
Emergency switch-off Machine-independent accessories Efficiency and sustainability Recycling rate in % 95 Connection options Optical interface for service access	Volumetric flow meter (optional)	•
Machine-independent accessories Efficiency and sustainability Recycling rate in % Connection options Optical interface for service access	Communication slot	•
Efficiency and sustainability Recycling rate in % 95 Connection options Optical interface for service access		•
Recycling rate in % 95 Connection options Optical interface for service access •	Machine-independent accessories	•
Connection options Optical interface for service access •	Efficiency and sustainability	
Optical interface for service access •	Recycling rate in %	95
	Connection options	
Serial interface module RS 232 (optional)	Optical interface for service access	•
	Serial interface module RS 232 (optional)	•



PW 6243 [EL WEK] Hygiene washing machine, electrically heated Barrier machine for retirement and care homes as well as hospitals.



EAN: 4002516446996 / Material number: 11812870 / Old Material Number: 51624305ZER

Peak-load negotiation / energy management (optional)	•
Operating data acquisition	•
Water recovery (optional)	•
Capacities	
Synthetic duvets [number]	3
Synthetic pillows [number]	6
Down duvets [number]	3
Down pillows [number]	6
Cotton mops, 40 cm / 190 g [number]	126
Cotton mops, 50 cm / 220 g [number]	109
Microfibre mops, 40 cm / 120 g [number]	200
Microfibre mops, 50 cm / 170 g [number]	141
Standards, test certificates and symbols	
CE	•
VDE-EMC	•
Splash-proof safety rating IPX4	•
UKCA	•
WEEE	•
Complies with Machinery Directive 2006/42/EC	•