

PW 6321 [EL SOM WEK MF]

Washing machine, electrically heated

For marine requirements, powder detergent dispenser, liquid dispensing module.



- Large programme variety application-specific wash programmes
- Particularly efficient low water and energy consumption
- Perfect spinning results residual moisture 47 %*, g-factor447
- Gentle laundry care thanks to the Miele honeycomb drum
- Drum volume 320 I, load size 32.0 kg

EAN: 4002516447528 / Material number: 11814110 / Old Material Number: 51632118SOM

Construction type and version	
Construction type	Front loader
Range	Professional
Front	Stainless steel
Control panel colour	Stainless steel
Load ratio	1:10
Load in kg	32,0
Drum volume in I	320
Door opening [Ø] in mm	430
Door opening angle in degrees	180
Door hinge	right
Maintenance-free motor with frequency converter	•
Honeycomb drum	•
Application	
Suitable for marine use	•
Performance data	
Tested virucidal efficacy	•
Proven hygiene	•
Specific water consumption for cold water connection in I/	9,00
kg	
Specific energy consumption for cold water connection in kWh/kg	0,25
Specific water consumption for hot water connection in I/kg	8,80
Specific energy consumption for hot water connection in kWh/kg	0,10
Water consumption with cold water connection in I	288,0
Energy consumption with cold water connection in kW	8,00
Programme duration in minutes with cold water connection	61
Water consumption with hot water connection in I	281,6
Energy consumption with hot water connection in kW	3,20
Programme duration in minutes with cold water and hot water connection	49
Water consumption in ECO programme with cold water connection in I	281,6
Energy consumption in ECO programme with cold water	6,20
Programme duration in minutes with cold water connection in ECO programme	47
Water consumption in ECO programme with hot water connection in I	284,8
Energy consumption in ECO programme with hot water	1,60
Programme duration in minutes with cold water and hot	37
water connection in ECO programme	
Residual moisture with cold rinse in %	50
Residual moisture with hot rinse in %	47
Spin speed in rpm	1000
g factor	447
Tested operating hours	30000
Control system	
Control system	Profitronic M
Programmability	Freely programmable
Max. delay start in h	Freely selectable
, ·····	,

Residual moisture specification relates to a hot rinse during the last rinse cycle.



PW 6321 [EL SOM WEK MF]

Washing machine, electrically heated

For marine requirements, powder detergent dispenser, liquid dispensing module.



EAN: 4002516447528 / Material number: 11814110 / Old Material Number: 51632118SOM

Time left display	•
Programme sequence indicator	•
Selectable display languages	•
Standard/target grp programmes	
Basic programmes	•
Programmes for the hotel and catering industry	•
Programmes for retirement and care homes	•
Programmes for facility management	•
Programmes for dry cleaners	•
Programmes for small businesses	•
Programmes for fire brigades and rescue services	•
Programmes for studs, riding schools, and stables	•
Programmes for hospitals	•
Programmes for sports clubs	•
Programmes for beauty clinics, spas, and fitness studios	•
Dispensing	
Detergent drawer	3 compartments
Liquid dispensing module	•
Maximum number of connections for liquid dispenser	12
pumps [number]	
Empty sensor	•
Standard electrical connection	
Heating type	Electric
Electrical connection	3 AC 380-415V 50-60HZ
Heater rating in kW	30,00
Total connected load in kW	31,00
Fuse rating in A	63
Water connection/drainage	
Cold water [number]	2x 1/2" hose w/ 3/4" th. union
Hot water [number]	1x 1/2" hose w/ 3/4" th. union
Dump valve	DN 70
Dump valve Dimensions and weight	DN 70
	DN 70 1643
Dimensions and weight	
Dimensions and weight External dimensions, height in mm	1643
Dimensions and weight External dimensions, height in mm External dimensions, width in mm	1643 1089
Dimensions and weight External dimensions, height in mm External dimensions, width in mm External dimensions, depth in mm	1643 1089 1280
Dimensions and weight External dimensions, height in mm External dimensions, width in mm External dimensions, depth in mm External dimensions, gross height in mm External dimensions, gross width in mm	1643 1089 1280 1710
Dimensions and weight External dimensions, height in mm External dimensions, width in mm External dimensions, depth in mm External dimensions, gross height in mm	1643 1089 1280 1710
Dimensions and weight External dimensions, height in mm External dimensions, width in mm External dimensions, depth in mm External dimensions, gross height in mm External dimensions, gross width in mm External dimensions, gross depth in mm	1643 1089 1280 1710 1336 1530
Dimensions and weight External dimensions, height in mm External dimensions, width in mm External dimensions, depth in mm External dimensions, gross height in mm External dimensions, gross width in mm External dimensions, gross depth in mm Net weight in kg	1643 1089 1280 1710 1336 1530 654,0
Dimensions and weight External dimensions, height in mm External dimensions, width in mm External dimensions, depth in mm External dimensions, gross height in mm External dimensions, gross width in mm External dimensions, gross depth in mm Net weight in kg Gross weight in kg	1643 1089 1280 1710 1336 1530 654,0 705
Dimensions and weight External dimensions, height in mm External dimensions, width in mm External dimensions, depth in mm External dimensions, gross height in mm External dimensions, gross width in mm External dimensions, gross depth in mm Net weight in kg Gross weight in kg Maximum floor load in N/m²	1643 1089 1280 1710 1336 1530 654,0 705
Dimensions and weight External dimensions, height in mm External dimensions, width in mm External dimensions, depth in mm External dimensions, gross height in mm External dimensions, gross width in mm External dimensions, gross depth in mm Net weight in kg Gross weight in kg Maximum floor load in N/m² Emissions data	1643 1089 1280 1710 1336 1530 654,0 705 9265
Dimensions and weight External dimensions, height in mm External dimensions, width in mm External dimensions, depth in mm External dimensions, gross height in mm External dimensions, gross width in mm External dimensions, gross depth in mm Net weight in kg Gross weight in kg Maximum floor load in N/m² Emissions data Emission sound pressure level in the workplace	1643 1089 1280 1710 1336 1530 654,0 705 9265
Dimensions and weight External dimensions, height in mm External dimensions, width in mm External dimensions, depth in mm External dimensions, gross height in mm External dimensions, gross width in mm External dimensions, gross depth in mm Net weight in kg Gross weight in kg Maximum floor load in N/m² Emissions data Emission sound pressure level in the workplace Heat dissipation into the room in MJ/h	1643 1089 1280 1710 1336 1530 654,0 705 9265
Dimensions and weight External dimensions, height in mm External dimensions, width in mm External dimensions, depth in mm External dimensions, gross height in mm External dimensions, gross width in mm External dimensions, gross depth in mm Net weight in kg Gross weight in kg Maximum floor load in N/m² Emissions data Emission sound pressure level in the workplace Heat dissipation into the room in MJ/h Features	1643 1089 1280 1710 1336 1530 654,0 705 9265
Dimensions and weight External dimensions, height in mm External dimensions, width in mm External dimensions, depth in mm External dimensions, gross height in mm External dimensions, gross width in mm External dimensions, gross depth in mm Net weight in kg Gross weight in kg Maximum floor load in N/m² Emissions data Emission sound pressure level in the workplace Heat dissipation into the room in MJ/h Features Patented pre-spin	1643 1089 1280 1710 1336 1530 654,0 705 9265 73 dB(A) re 20 μPa 4,70
Dimensions and weight External dimensions, height in mm External dimensions, width in mm External dimensions, depth in mm External dimensions, gross height in mm External dimensions, gross width in mm External dimensions, gross depth in mm Net weight in kg Gross weight in kg Maximum floor load in N/m² Emissions data Emission sound pressure level in the workplace Heat dissipation into the room in MJ/h Features Patented pre-spin Cloth reprocessing	1643 1089 1280 1710 1336 1530 654,0 705 9265 73 dB(A) re 20 µPa 4,70



PW 6321 [EL SOM WEK MF]

Washing machine, electrically heated

For marine requirements, powder detergent dispenser, liquid dispensing module.



EAN: 4002516447528 / Material number: 11814110 / Old Material Number: 51632118SOM

Special heater element	•
Automatic load control+	•
Volumetric flow meter (optional)	•
Communication slot	•
Emergency switch-off	•
Machine-independent accessories	•
Efficiency and sustainability	
Recycling rate in %	96
Connection options	
Payment system (optional)	•
Optical interface for service access	•
Serial interface module RS 232 (optional)	•
Peak-load negotiation / energy management (optional)	•
Operating data acquisition	•
Water recovery (optional)	•
Capacities	
Respirator masks [number]	26
Overalls [number]	6
Over jackets [number]	9
Chemical protection suits [number]	5
Synthetic duvets [number]	4
Synthetic pillows [number]	8
Down duvets [number]	4
Down pillows [number]	8
Cloths, 22 g [number]	727
Cotton mops, 40 cm / 190 g [number]	168
Cotton mops, 50 cm / 220 g [number]	145
Microfibre mops, 40 cm / 120 g [number]	267
Microfibre mops, 50 cm / 170 g [number]	188
Summer horse blankets [number]	5
Standards, test certificates and symbols	
CE	•
VDE	•
Splash-proof safety rating IPX4	•
UKCA	•
WEEE	•
RCM	•
EAC	•
Complies with Machinery Directive 2006/42/EC	•