

PDW 909 [EL DP DD SOM]

Professional washer-dryer stack, electric heating, with drain pump for washing/drying in the smallest space, with drain pump, for marine use.



EAN: 4002516703099 / Material number: 12341260 / Old Material Number: 51909520SOM

| Construction type and version | |
|--|---------------------------|
| Construction type | Front-loading stack |
| Range | Performance Plus |
| Front | Stainless steel |
| Washer-extractor load capacity in kg | 9,0 |
| Tumble dryer load capacity in kg | 9,0 |
| Washer-extractor fill ratio | 1:9 |
| Tumble dryer fill ratio | 1:20 |
| Washer-extractor drum volume in I | 80 |
| Tumble dryer drum volume in I | 180 |
| Drying system | Exhaust air |
| Washer-extractor door opening [Ø] in mm | 370 |
| Tumble dryer door opening [Ø] in mm | 440 |
| Door opening angle in degrees | 180 |
| Door hinge | Washing right/drying left |
| Automatic door lock | • |
| Honeycomb drum | • |
| Application | |
| Suitable for offshore use | • |
| Suitable for marine use | • |
| Performance data | |
| Specific washer-extractor energy consumption in kW | 0,03 |
| Residual moisture with cold rinse in % | 47 |
| Residual moisture with hot rinse in % | 44 |
| Washer-extractor spin speed in rpm. | 1300 |
| Washer-extractor g-factor | 518 |
| Control system | |
| Control type for washing machine | M Touch Pro Plus |
| Control type for tumble dryer | M Touch Pro |
| Programmability for washing machine | Frei Programmierbar |
| Programmability for tumble dryer | Programmierbar |
| Max. delay start in h for washing machine | Frei wählbar |
| Max. delay start in h for tumble dryer | 24 |
| Time left display | • |
| Programme sequence indicator | • |
| Selectable display languages | • |
| Standard/target grp programmes | |
| Basic programmes | • |
| Programmes for the hotel and catering industry | • |
| Programmes for retirement and care homes | • |
| Programmes for launderettes | • |
| Programmes for residential homes and apartments | • |
| Programmes for dry cleaners | • |
| Programmes for commercial laundries | • |
| Programmes for small businesses | ` |
| Programmes for fire brigades and rescue services | • |
| | ` |
| Programmes for universities, nurseries, and school | • |
| Drogrammae for hospitale | • |
| Programmes for hospitals Programmes for camp sites | • |



PDW 909 [EL DP DD SOM]

Professional washer-dryer stack, electric heating, with drain pump for washing/drying in the smallest space, with drain pump, for marine use.



EAN: 4002516703099 / Material number: 12341260 / Old Material Number: 51909520SOM

| Programmes for beauty clinics, spas, and fitness studios | • |
|---|---|
| Programmes for domestic use | • |
| Programmes for doctors' and dentists' practices | • |
| Washing machine dispensing | |
| Detergent drawer | 3 compartments |
| Maximum number of connections for liquid dispenser | 6 |
| Empty sensor | • |
| Standard electrical connection | |
| Type of heating washing machine | Electric |
| Type of heating tumble dryer | Electric |
| Electrical connection washing machine | 3N AC 400 V 60 Hz |
| Heater rating washing machine in kW | 7,95 |
| Total connected load washing machine in kW | 8,20 |
| Electrical connection tumble dryer | 3N AC 400 V 50/60 Hz |
| Heater rating tumble dryer in kW | 7,94 |
| Total connected load tumble dryer in kW | 8,20 |
| Possible voltage options | |
| Electrical connection washing machine | 3N AC 400 V 60 Hz |
| Heater rating washing machine in kW | 7,95 |
| Total connected load washing machine in kW | 8,20 |
| Fuse rating washing machine in A | 16,0 |
| Electrical connection tumble dryer | 3N AC 400 V 50/60 Hz |
| Water connection/drainage | 011710 100 1 00700 112 |
| Cold water [number] | 1x 1/2" hose w/ 3/4" th. |
| Cold Water [Harrison] | union |
| Hot water [number] | 1x 1/2" hose w/ 3/4" th. |
| riot water frumber | 1X 1/2 1103C W/ 0/4 til. |
| not water [number] | union |
| Grey water (optional) [number] | |
| | union |
| Grey water (optional) [number] | union 1 x 1/2" w/ 3/4" union |
| Grey water (optional) [number] Drain pump | union 1 x 1/2" w/ 3/4" union |
| Grey water (optional) [number] Drain pump Dimensions and weight | union 1 x 1/2" w/ 3/4" union DN 22 |
| Grey water (optional) [number] Drain pump Dimensions and weight External dimensions, net height in mm | union 1 x 1/2" w/ 3/4" union DN 22 1940 |
| Grey water (optional) [number] Drain pump Dimensions and weight External dimensions, net height in mm External dimensions, net width in mm | union 1 x 1/2" w/ 3/4" union DN 22 1940 692 |
| Grey water (optional) [number] Drain pump Dimensions and weight External dimensions, net height in mm External dimensions, net width in mm External dimensions, net depth in mm | union 1 x 1/2" w/ 3/4" union DN 22 1940 692 761 |
| Grey water (optional) [number] Drain pump Dimensions and weight External dimensions, net height in mm External dimensions, net width in mm External dimensions, net depth in mm Net weight in kg | union 1 x 1/2" w/ 3/4" union DN 22 1940 692 761 208,0 |
| Grey water (optional) [number] Drain pump Dimensions and weight External dimensions, net height in mm External dimensions, net width in mm External dimensions, net depth in mm Net weight in kg Gross weight in kg | union 1 x 1/2" w/ 3/4" union DN 22 1940 692 761 208,0 232,0 |
| Grey water (optional) [number] Drain pump Dimensions and weight External dimensions, net height in mm External dimensions, net width in mm External dimensions, net depth in mm Net weight in kg Gross weight in kg Maximum floor load in N/m² | union 1 x 1/2" w/ 3/4" union DN 22 1940 692 761 208,0 232,0 3235 |
| Grey water (optional) [number] Drain pump Dimensions and weight External dimensions, net height in mm External dimensions, net width in mm External dimensions, net depth in mm Net weight in kg Gross weight in kg Maximum floor load in N/m² Net weight in kg | union 1 x 1/2" w/ 3/4" union DN 22 1940 692 761 208,0 232,0 3235 |
| Grey water (optional) [number] Drain pump Dimensions and weight External dimensions, net height in mm External dimensions, net width in mm External dimensions, net depth in mm Net weight in kg Gross weight in kg Maximum floor load in N/m² Net weight in kg Emissions data | union 1 x 1/2" w/ 3/4" union DN 22 1940 692 761 208,0 232,0 3235 139,00 |
| Grey water (optional) [number] Drain pump Dimensions and weight External dimensions, net height in mm External dimensions, net width in mm External dimensions, net depth in mm Net weight in kg Gross weight in kg Maximum floor load in N/m² Net weight in kg Emissions data Emission sound pressure level in the workplace | union 1 x 1/2" w/ 3/4" union DN 22 1940 692 761 208,0 232,0 3235 139,00 63 dB(A) re 20 µPa |
| Grey water (optional) [number] Drain pump Dimensions and weight External dimensions, net height in mm External dimensions, net width in mm External dimensions, net depth in mm Net weight in kg Gross weight in kg Maximum floor load in N/m² Net weight in kg Emissions data Emission sound pressure level in the workplace Washer-extractor heat output to the room in Mj/h | union 1 x 1/2" w/ 3/4" union DN 22 1940 692 761 208,0 232,0 3235 139,00 63 dB(A) re 20 μPa 3,00 |
| Grey water (optional) [number] Drain pump Dimensions and weight External dimensions, net height in mm External dimensions, net width in mm External dimensions, net depth in mm Net weight in kg Gross weight in kg Maximum floor load in N/m² Net weight in kg Emissions data Emission sound pressure level in the workplace Washer-extractor heat output to the room in Mj/h Tumble dryer heat output to the room in Mj/h | union 1 x 1/2" w/ 3/4" union DN 22 1940 692 761 208,0 232,0 3235 139,00 63 dB(A) re 20 μPa 3,00 |
| Grey water (optional) [number] Drain pump Dimensions and weight External dimensions, net height in mm External dimensions, net width in mm External dimensions, net depth in mm Net weight in kg Gross weight in kg Maximum floor load in N/m² Net weight in kg Emissions data Emission sound pressure level in the workplace Washer-extractor heat output to the room in Mj/h Tumble dryer heat output to the room in Mj/h Features | union 1 x 1/2" w/ 3/4" union DN 22 1940 692 761 208,0 232,0 3235 139,00 63 dB(A) re 20 µPa 3,00 1,62 |
| Grey water (optional) [number] Drain pump Dimensions and weight External dimensions, net height in mm External dimensions, net width in mm External dimensions, net depth in mm Net weight in kg Gross weight in kg Maximum floor load in N/m² Net weight in kg Emissions data Emission sound pressure level in the workplace Washer-extractor heat output to the room in Mj/h Tumble dryer heat output to the room in Mj/h Features Washer-extractor disinfection rinse | union 1 x 1/2" w/ 3/4" union DN 22 1940 692 761 208,0 232,0 3235 139,00 63 dB(A) re 20 µPa 3,00 1,62 |
| Grey water (optional) [number] Drain pump Dimensions and weight External dimensions, net height in mm External dimensions, net width in mm External dimensions, net depth in mm Net weight in kg Gross weight in kg Maximum floor load in N/m² Net weight in kg Emissions data Emission sound pressure level in the workplace Washer-extractor heat output to the room in Mj/h Tumble dryer heat output to the room in Mj/h Features Washer-extractor disinfection rinse Washer-extractor temperature monitoring | union 1 x 1/2" w/ 3/4" union DN 22 1940 692 761 208,0 232,0 3235 139,00 63 dB(A) re 20 µPa 3,00 1,62 |
| Grey water (optional) [number] Drain pump Dimensions and weight External dimensions, net height in mm External dimensions, net width in mm External dimensions, net depth in mm Net weight in kg Gross weight in kg Maximum floor load in N/m² Net weight in kg Emissions data Emission sound pressure level in the workplace Washer-extractor heat output to the room in Mj/h Tumble dryer heat output to the room in Mj/h Features Washer-extractor disinfection rinse Washer-extractor temperature monitoring Volumetric flow meter, washer-extractor | union 1 x 1/2" w/ 3/4" union DN 22 1940 692 761 208,0 232,0 3235 139,00 63 dB(A) re 20 µPa 3,00 1,62 |
| Grey water (optional) [number] Drain pump Dimensions and weight External dimensions, net height in mm External dimensions, net width in mm External dimensions, net depth in mm Net weight in kg Gross weight in kg Maximum floor load in N/m² Net weight in kg Emissions data Emission sound pressure level in the workplace Washer-extractor heat output to the room in Mj/h Tumble dryer heat output to the room in Mj/h Features Washer-extractor disinfection rinse Washer-extractor temperature monitoring Volumetric flow meter, washer-extractor Special heater element washing machine | union 1 x 1/2" w/ 3/4" union DN 22 1940 692 761 208,0 232,0 3235 139,00 63 dB(A) re 20 µPa 3,00 1,62 |
| Grey water (optional) [number] Drain pump Dimensions and weight External dimensions, net height in mm External dimensions, net width in mm External dimensions, net depth in mm Net weight in kg Gross weight in kg Maximum floor load in N/m² Net weight in kg Emissions data Emission sound pressure level in the workplace Washer-extractor heat output to the room in Mj/h Tumble dryer heat output to the room in Mj/h Features Washer-extractor disinfection rinse Washer-extractor temperature monitoring Volumetric flow meter, washer-extractor Special heater element washing machine Intelligent tumble dryer drum reversal | union 1 x 1/2" w/ 3/4" union DN 22 1940 692 761 208,0 232,0 3235 139,00 63 dB(A) re 20 µPa 3,00 1,62 • • • • |
| Grey water (optional) [number] Drain pump Dimensions and weight External dimensions, net height in mm External dimensions, net width in mm External dimensions, net depth in mm Net weight in kg Gross weight in kg Maximum floor load in N/m² Net weight in kg Emissions data Emission sound pressure level in the workplace Washer-extractor heat output to the room in Mj/h Tumble dryer heat output to the room in Mj/h Features Washer-extractor disinfection rinse Washer-extractor temperature monitoring Volumetric flow meter, washer-extractor Special heater element washing machine Intelligent tumble dryer filter | union 1 x 1/2" w/ 3/4" union DN 22 1940 692 761 208,0 232,0 3235 139,00 63 dB(A) re 20 µPa 3,00 1,62 • • • • |
| Grey water (optional) [number] Drain pump Dimensions and weight External dimensions, net height in mm External dimensions, net width in mm External dimensions, net depth in mm Net weight in kg Gross weight in kg Maximum floor load in N/m² Net weight in kg Emissions data Emission sound pressure level in the workplace Washer-extractor heat output to the room in Mj/h Tumble dryer heat output to the room in Mj/h Features Washer-extractor disinfection rinse Washer-extractor temperature monitoring Volumetric flow meter, washer-extractor Special heater element washing machine Intelligent tumble dryer drum reversal Axial air flow dryer | union 1 x 1/2" w/ 3/4" union DN 22 1940 692 761 208,0 232,0 3235 139,00 63 dB(A) re 20 μPa 3,00 1,62 • • • • |



PDW 909 [EL DP DD SOM]

Professional washer-dryer stack, electric heating, with drain pump for washing/drying in the smallest space, with drain pump, for marine use.



EAN: 4002516703099 / Material number: 12341260 / Old Material Number: 51909520SOM

| Low temperature tumble dryer function | • |
|--|-----|
| Drying basket (optional) | • |
| Machine-independent accessories | • |
| Connection options | |
| Payment system (optional) | • |
| Optical interface for service access | • |
| Peak load cut-out/energy management (optional) | • |
| LAN for washing machine | • |
| WiFi | • |
| Connector Box | • |
| Capacities | |
| Respirator masks [number] | 13 |
| Protective suits [number] | 1 |
| Over jackets [number] | 2 |
| Synthetic duvets [number] | 1 |
| Synthetic pillows [number] | 2 |
| Down duvets [number] | 1 |
| Down pillows [number] | _2 |
| Cloths, 22 g [number] | 204 |
| Cotton mops, 40 cm [number] | 42 |
| Cotton mops, 50 cm [number] | 33 |
| Microfibre mops, 50 cm [number] | 47 |
| Summer horse blankets [number] | 2 |
| Standards, test certificates and symbols | |
| CE | • |
| VDE-EMC | • |
| VDE | • |
| Splash-proof safety rating IPX4 | • |
| WEEE | • |
| Complies with Machinery Directive 2006/42/EC | • |