

PFD 409 [WB Offshore] Freestanding fresh water dishwasher with baskets, for offshore locations such as drilling platforms.



- Max. cleaning performance*: 190 plates/h or 10 baskets/h
- First-class results thanks to freshwater wash system
- Special electrical connection for specific site conditions
- Extremely hygienic results final rinse temperature of 85 $^{\circ}\text{C}$
- Maximum convenience with M Touch Flex full-touch colour display

EAN: 4002516745648 / Material number: 12441910 / Old Material Number: 61040910SOM

Old Material Number: 61040910SOM	
Construction type and version	
Construction type	Freestanding dishwasher, front loader
Range	MasterLine
Model	Offshore
Wash system	Fresh water front loader
Number of levels	2
Front	Stainless steel
Lid	Stainless Steel
Side panels	Stainless steel
Rear panel	Galvanised
Application	
Suitable for offshore and marine services	
Performance data	
Tested virucidal efficacy	•
Proven hygiene	•
Circulation pump Qmax in I/min.	390
Shortest programme duration in min.	12
Maximum final rinse temperature in °C	 85
Cleaning performance, plates/h	190
Cleaning performance, baskets/h	10
Possible to wash plastic baskets on 2 levels	•
Service life in wash cycles	28000
Miele MOVE	20000
Network-enabled with Miele MOVE	•
Control system	
Control system	M Touch Flex
Max. delay start in h	24
	•
Time left display Dishwashing programmes [number]	7
	*
Adjustable temperature holding time	<u>`</u>
Adjustable final rinse temperature	`
Programme sequence indicator	•
Choice of display language	
Language-neutral operation	·
Standard electrical connection	2 4 6 4 4 0 1/ 6 0 1/7
Electrical connection	3 AC 440V 60HZ
Heater rating in kW	9,00
Total connected load in kW	9,00
Fuse rating in A	16
Length of mains connection cable in m	1,70
Possible voltage variant 1	40.0001/001/7
Electrical connection	AC 220V 60HZ
Total connected load in kW	0,70
Fuse rating in A	4
Water connection/drainage	
Cold water [number]	1
Hot water [number]	1

^{*} Depending on site conditions (temperature of incoming water / power connection) values given may vary.



PFD 409 [WB Offshore] Freestanding fresh water dishwasher with baskets, for offshore locations such as drilling platforms.



EAN: 4002516745648 / Material number: 12441910 / Old Material Number: 61040910SOM Required flow pressure in bar 1,00-10,00 Drain pump [DN] 22 Drain pump head height from floor level, max. in c 100 Integrated water softener Maximum water hardness in mmol/l 10,70 Water protection system Waterproof system Water consumption per wash cycle in I 17,50 Length of water inlet hose in cm 150 Length of water drain hose in cm 150 Dimensions and weight External dimensions, height in mm 820 External dimensions with lid, height in mm 835 598 External dimensions, net width in mm 598 External dimensions, net depth in mm External dimensions, gross height in mm 920 External dimensions, gross width in mm 670 External dimensions, gross depth in mm 740 520 Usable space in wash cabinet, height in mm Usable space in wash cabinet, width in mm 530 Usable space in wash cabinet, depth of upper baske Usable space in wash cabinet, depth of lower basket in mm 505 In-feed height above floor in mm 216 Required niche width in mm 600 Net weight [kg] 78 Gross weight in kg 88 **Emissions data** Emissions – sound pressure at workplace 45 dB(A) re 20 μPa Sound power (LwA) in dB(A) re 1 pW 57,0 Heat dissipation into the room in MJ/h 1,08 **Programmes** Universal Short Cold/Pre-wash Glasses Cutlery Plastics Intensive Reactivation Drainage Basket design 2 x E 816 inserts for plates 2 x E 165 inserts for cutlery 1 x APFD 215 upper basket 1 x APFD 220 lower basket for inserts Height-adjustable upper basket Combinable with APFD 210 bottle basket **Features** Drying AutoOpen assisted drying



PFD 409 [WB Offshore] Freestanding fresh water dishwasher with baskets, for offshore locations such as drilling platforms.

DIN EN 17735



EAN: 4002516745648 / Material number: 12441910 / Old Material Number: 61040910SOM AutoClose 1 combi dispenser in the door for powder cleaning agent and rinsing agent In-door salt container Door lock, protected by code Perfect GlassCare Highly effective filter system with filter monitoring Aerosol steam condenser Wash cabinet made from high-quality stai Optical interface A wide range of accessories (optional) Connection options External dispensing module for liquid cleaning agent External dispensing module for rinse aid WiFi ٠ Standards, test certificates and symbols Complies with Machinery Directive 2006/42/EC Interference suppression Splash-protection IPX1 DIN 10512