

PG 8060 [OFFSHORE]

Freestanding fresh water dishwasher

with baskets, for offshore locations such as drilling platforms.



- Max. cleaning performance*: 76 plates/h
- First-class results thanks to freshwater wash system
- Special electrical connection for specific site conditions
- Extremely hygienic results – final rinse temperature of 85 °C
- Versatile processing of 2 wire baskets per cycle

* Depending on site conditions (temperature of incoming water / power connection) values given may vary.

EAN: 4002515524428 / Material number: 09736630 / Old Material Number: 61806005N

| Construction type and version | |
|--|---------------------------------------|
| Construction type | Freestanding dishwasher, front loader |
| Range | Professional |
| Wash system | Fresh water front loader |
| Number of levels | 2 |
| Front | Stainless steel |
| Lid | Stainless Steel |
| Side panels | Stainless steel |
| Application | |
| Suitable for offshore and marine services | • |
| Performance data | |
| Circulation pump Qmax in l/min. | 390 |
| Shortest programme duration in min. | 28 |
| Maximum final rinse temperature in °C | 85 |
| Cleaning performance, plates/h | 76 |
| Cleaning performance, baskets/h | 4 |
| Service life in wash cycles | 15000 |
| Control system | |
| Control system | TouchControl |
| Programme selection | Touch on MSetal |
| Max. delay start in h | 24 |
| Time left display | • |
| Programme sequence indicator | • |
| Choice of display language | • |
| Language-neutral operation | • |
| Standard electrical connection | |
| Electrical connection | 3 AC 220V 60HZ |
| Heater rating in kW | 6.10 |
| Total connected load in kW | 6.50 |
| Fuse rating in A | 20 |
| Length of mains connection cable in m | 1.70 |
| Possible voltage variant 1 | |
| Electrical connection | AC 220V 60HZ |
| Heater rating in kW | 2.30 |
| Total connected load in kW | 2.70 |
| Fuse rating in A | 16 |
| Water connection/drainage | |
| Cold water [number] | 1 |
| Hot water [number] | 1 |
| Required flow pressure in bar | 1.00-10.00 |
| Drain pump [DN] | 22 |
| Drain pump head height from floor level, max. in c | 100 |
| Integrated water softener | • |
| Maximum water hardness in mmol/l | 10.70 |
| Water protection system | Waterproof system |
| Water consumption per wash cycle in l | 8.00 |
| Dimensions and weight | |
| External dimensions, height in mm | 820 |
| External dimensions with lid, height in mm | 835 |

PG 8060 [OFFSHORE]

Freestanding fresh water dishwasher

with baskets, for offshore locations such as drilling platforms.



EAN: 4002515524428 / Material number: 09736630 / Old Material Number: 61806005N

| | |
|---|--------------------------|
| External dimensions, net width in mm | 600 |
| External dimensions, net depth in mm | 600 |
| External dimensions, gross height in mm | 950 |
| External dimensions, gross width in mm | 670 |
| External dimensions, gross depth in mm | 690 |
| Usable space in wash cabinet, height in mm | 520 |
| Usable space in wash cabinet, width in mm | 530 |
| Usable space in wash cabinet, depth of upper basket | 474 |
| Usable space in wash cabinet, depth of lower basket in mm | 505 |
| In-feed height above floor in mm | 216 |
| Net weight [kg] | 72 |
| Gross weight in kg | 84 |
| Maximum floor load in N/m ² | 1200 |
| Emissions data | |
| Emissions – sound pressure at workplace | 45 dB(A) re 20 µPa |
| Sound power (LwA) in dB(A) re 1 pW | 57.0 |
| Heat dissipation into the room in MJ/h | 1.08 |
| Programmes | |
| Universal | • |
| Short | • |
| Cold/Pre-wash | • |
| Glasses | • |
| Cutlery | • |
| Intensive | • |
| Reactivation | • |
| Drainage | • |
| Basket design | |
| 1 x O 891 upper basket for cups | • |
| 1 x U 890 lower basket for inserts | • |
| 1 x E 810 insert for dessert plates | • |
| 2 x E 816 inserts for plates | • |
| 2 x E 165 inserts for cutlery | • |
| Height-adjustable upper basket | • |
| Features | |
| Drying | AutoOpen assisted drying |
| 1 combi dispenser in the door for powder cleaning agent and rinsing agent | • |
| Wash cabinet made from high-quality stainless steel | • |
| In-door salt container | • |
| AutoClose | • |
| Perfect GlassCare | • |
| Aerosol steam condenser | • |
| Adjustable temperature holding time | • |
| Adjustable final rinse temperature | • |
| Adjustable wash temperature | • |
| Adjustable rinse time | • |
| Optical interface | • |
| A wide range of accessories (optional) | • |
| Connection options | |
| External dispensing module for liquid detergent | • |
| External dispensing module for rinse aid | • |

PG 8060 [OFFSHORE]
Freestanding fresh water dishwasher
with baskets, for offshore locations such as drilling platforms.



EAN: 4002515524428 / Material number: 09736630 / Old Material Number: 61806005N

| Standards, test certificates and symbols | |
|--|---|
| CE | • |
| Complies with Machinery Directive 2006/42/EC | • |
| EMC | • |
| Interference suppression | • |
| VDE | • |
| DIN 10512 | • |
| EN 1717 | • |