

PG 8060 [OFFSHORE]

Freestanding fresh water dishwasher

with baskets, for offshore locations such as drilling platforms.



- Max. cleaning performance*: 76 plates/h
- First-class results thanks to freshwater wash system
- Special electrical connection for specific site conditions
- Extremely hygienic results – final rinse temperature of 85 °C
- Versatile processing of 2 wire baskets per cycle

* Depending on site conditions (temperature of incoming water / power connection) values given may vary.

EAN: 4002515524428 / Material number: 09736630 /
Old Material Number: 61806005N

Construction type and version	
Construction type	Freestanding dishwasher, front loader
Range	Professional
Wash system	Fresh water front loader
Number of levels	2
Front	Stainless steel
Lid	Stainless Steel
Side panels	Stainless steel
Application	
Suitable for offshore and marine services	•
Performance data	
Circulation pump Qmax in l/min.	390
Shortest programme duration in min.	28
Maximum final rinse temperature in °C	85
Cleaning performance, plates/h	76
Cleaning performance, baskets/h	4
Service life in wash cycles	15000
Control system	
Control system	TouchControl
Programme selection	Touch on MSetal
Max. delay start in h	24
Time left display	•
Adjustable temperature holding time	•
Programme sequence indicator	•
Choice of display language	•
Language-neutral operation	•
Standard electrical connection	
Electrical connection	3 AC 220V 60HZ
Heater rating in kW	6.10
Total connected load in kW	6.50
Fuse rating in A	20
Length of mains connection cable in m	1.70
Possible voltage variant 1	
Electrical connection	AC 220V 60HZ
Heater rating in kW	2.30
Total connected load in kW	2.70
Fuse rating in A	16
Water connection/drainage	
Cold water [number]	1
Hot water [number]	1
Required flow pressure in bar	1.00-10.00
Drain pump [DN]	22
Drain pump head height from floor level, max. in c	100
Integrated water softener	•
Maximum water hardness in mmol/l	10.70
Water protection system	Waterproof system
Water consumption per wash cycle in l	8.00

PG 8060 [OFFSHORE]

Freestanding fresh water dishwasher

with baskets, for offshore locations such as drilling platforms.



EAN: 4002515524428 / Material number: 09736630 /

Old Material Number: 61806005N

Dimensions and weight

External dimensions, height in mm	820
External dimensions with lid, height in mm	835
External dimensions, net width in mm	600
External dimensions, net depth in mm	600
External dimensions, gross height in mm	950
External dimensions, gross width in mm	670
External dimensions, gross depth in mm	690
Usable space in wash cabinet, height in mm	520
Usable space in wash cabinet, width in mm	530
Usable space in wash cabinet, depth of upper basket	474
Usable space in wash cabinet, depth of lower basket in mm	505
In-feed height above floor in mm	216
Net weight [kg]	72
Gross weight in kg	84
Maximum floor load in N/m ²	1200

Emissions data

Emissions – sound pressure at workplace	45 dB(A) re 20 µPa
Sound power (LwA) in dB(A) re 1 pW	57.0
Heat dissipation into the room in MJ/h	1.08

Programmes

Universal	•
Short	•
Cold/Pre-wash	•
Glasses	•
Cutlery	•
Intensive	•
Reactivation	•
Drainage	•

Basket design

1 x O 891 upper basket for cups	•
1 x U 890 lower basket for inserts	•
1 x E 810 insert for dessert plates	•
2 x E 816 inserts for plates	•
2 x E 165 inserts for cutlery	•
Height-adjustable upper basket	•

Features

Drying	AutoOpen assisted drying
1 combi dispenser in the door for powder cleaning agent and rinsing agent	•
Wash cabinet made from high-quality stainless steel	•
In-door salt container	•
AutoClose	•
Perfect GlassCare	•
Aerosol steam condenser	•
Adjustable final rinse temperature	•
Adjustable wash temperature	•
Adjustable rinse time	•
Optical interface	•

PG 8060 [OFFSHORE]

Freestanding fresh water dishwasher

with baskets, for offshore locations such as drilling platforms.



EAN: 4002515524428 / Material number: 09736630 /

Old Material Number: 61806005N

A wide range of accessories (optional)

Connection options

External dispensing module for liquid detergent

External dispensing module for rinse aid

Standards, test certificates and symbols

CE

Complies with Machinery Directive 2006/42/EC

EMC

Interference suppression

VDE

DIN 10512

EN 1717