

A 204
Mobile unit
for the optimum loading of Micro instruments.



- Level 1: suitable for inserts
- Level 2 right: 22 connections for hollow instruments
- Level 2 left: 11 Luer lock adapters, male, horizontal Hose
- With integrated spray arm
- Tubular filter A 800 can be used in both injector manifolds

EAN: 4002515460733 / Material number: 09862460 / Old Material Number: 69620400D

Product category	
Washer-disinfectors, medical	•
Machine affiliation	
PG 8562	•
PG 8582	•
PG 8582 CD	•
PG 8592	•
Product category	
Mobile unit for ophthalmology instruments	•
Product properties	
Material	Stainless steel
Colour	Stainless Steel
Option to use a central filter	•
Area of application	
Reprocessing of ophthalmology instruments	•
Capacity	
Theatre sets for micro instruments [number]	2-4
Standard electrical connection	
Number of phases	0
Voltage in V	0-0
Frequency in Hz	0-0
Total rated load in kW	0.00-0.00
Fuse rating in A	0-0
Dimensions and weight	
External dimensions, net height in mm	365
External dimensions, net width in mm	529
External dimensions, net depth in mm	535
External dimensions, gross height in mm	530
External dimensions, gross width in mm	560
External dimensions, gross depth in mm	540
Net weight in kg	11.50
Gross weight in kg	12.50
Companion pack	
E 476 holder [number]	1
E 477 stopper [number]	1