


ProCare Lab 30 C - 5 I Neutralising agent, acidic, 5 I

For optimum neutralisation with citric acid based neutralising agent.





- Free from surfactants, phosphorus compounds and oxidation agents
- Specially developed for Miele Professional
- Suitable for all types of materials
- pH value 2.6-3.0
- To be used as neutralising agent or acid pre-cleaner

Product classification	
Washer-disinfectors, laboratory	•
Applications	
Removal of tarnishing, limescale, urine scale and other	Good
acid-soluble impurities	Good
Dispensing recommendation	
Dispensing recommendation per wash cycle	1-4 ml/l (0.1-0.4%)
pH value of solution	2.6-3.0
Main applications	2.0 0.0
Medical laboratories	•
Biological laboratories	•
Microbiological laboratories	•
Chemical laboratories	•
Water laboratories	•
Laboratories for the food industry	
Laboratories for the cosmetics industry	•
Industrial laboratories	•
Phosphate industry	_ <del>`</del>
Laboratories for the pharmaceutical industry	•
Product properties	A sidia nautralisina agent
Medium type	Acidic neutralising agent
Aggregate form	Liquid
Composition	Organic acids
Suitable for plastic items	
Suitable for stainless steel	<u>•</u>
Suitable for laboratory glassware	<u>•</u>
Suitable for ceramic items	
Not suitable for anodised aluminium	
Does not contain phosphates	
Does not contain surfactants	
Very gentle on materials	
Acidic pre-cleaning	
Suitable for sensitive materials	
Neutralisation of carried-over alkali residues	<del>•</del>
Not suitable for chrome-plated parts	<u>•</u>
Not suitable for nickel-plated parts	<u>•</u>
Not suitable for acidic pre-cleaning of non-anodised	•
aluminium	
Not suitable for light and non-ferrous metals	
Suitable for neutralisation of non-anodised aluminium	•
Dimensions and weight	0.1=
External dimensions, net height in mm	217
External dimensions, net width in mm	142
External dimensions, net depth in mm	248
External dimensions, gross height in mm	250
External dimensions, gross width in mm	190
External dimensions, gross depth in mm	150
Gross weight in kg	6
Fill volume in ml	5000
Compliance, certs/symbols	
GHS/CLP compliant	•