

PDR 908 [EL MAR 2 AC 208-240V 60Hz]
Vented dryer, electrically heated
Lloyd's Register approved, load size 8.0 kg.



- Drum volume 130.00 l, load size 8.0 kg
- Tested for intensive use – unparalleled Miele quality
- Max. user convenience, full-touch colour display – M Touch Flex
- Precision drying of all fabrics – PerfectDry

EAN: 4002516216896 / Material number: 11251140 / Old Material Number: 52908489MAR

| Construction type and version | |
|--|------------------------------|
| Construction type | Front loader |
| Range | Performance Plus |
| Front | Stainless steel |
| Fascia color | Stainless steel |
| Load in kg | 8.0 |
| Drum volume in l | 130.00 |
| Drying system | Exhaust air |
| Door opening [Ø] in mm | 370 |
| Door opening angle in degrees | 167 |
| Door hinge | left |
| Stainless steel honeycomb drum | Yes |
| Application | |
| Suitable for offshore use | • |
| Suitable for marine use | • |
| Performance data | |
| Maximum evaporation capacity in l/hour | 3.70 |
| Specific energy consumption in kWh/kg | 0.49 |
| Specific energy consumption for Cottons/Normal drying programme with residual moisture at 48 % in kW | 0.49 |
| Specific energy consumption for mixed fibre fabrics/Normal drying programme with residual moisture a | 0.41 |
| Programme duration in min. | 62 |
| Programme duration for Cottons/Normal drying programme with residual moisture at 48 % in minutes | 62 |
| Programme duration for mixed fibre fabrics/Normal drying programme with residual moisture at 40 % in | 57 |
| Control system | |
| Control system | M Touch Flex |
| Programmability | programmable |
| User interface | Residual moisture controlled |
| Max. delay start in h | 24 |
| Time left display | • |
| Programme sequence indicator | • |
| Language can be selected easily at any time | • |
| Standard electrical connection | |
| Heating type | Electric |
| Electrical connection | 2~ 208-240V 60HZ |
| Electric heater rating in kW | 3.03-4.04 |
| Total connected load in kW | 3.40-4.30 |
| Fuse rating in A | 30 |
| Dimensions and weight of dryer | |
| External dimensions, height in mm | 850 |
| External dimensions, width in mm | 606 |
| External dimensions, depth in mm | 717 |
| External dimensions, gross height in mm | 940 |
| External dimensions, gross width in mm | 660 |
| External dimensions, gross depth in mm | 820 |
| Net weight in kg | 72.0 |
| Gross weight in kg | 78 |

PDR 908 [EL MAR 2 AC 208-240V 60Hz]
 Vented dryer, electrically heated
 Lloyd's Register approved, load size 8.0 kg.



EAN: 4002516216896 / Material number: 11251140 / Old Material Number: 52908489MAR

| | |
|---|---------------------|
| Maximum floor load in N/m ² | 920 |
| Emissions data | |
| Emission sound pressure level in the workplace | <70 dB(A) re 20 µPa |
| Heat dissipation into the room in MJ/h | 0.76 |
| Features | |
| Intelligent drum reversal | • |
| Axial airflow | • |
| Large-surface filter | • |
| PerfectDry | • |
| SoftLift drum ribs | • |
| Low temperature function | • |
| Communication slot | • |
| Drying basket (optional) | • |
| Drum lighting | • |
| Machine-independent accessories | • |
| Connection options | |
| Payment system (optional) | • |
| Optical interface for service access | • |
| Peak load cut-out/energy management (optional) | • |
| LAN/WiFi module (optional) | • |
| WiFiConn@ct | • |
| Standards, test certificates and symbols | |
| WEEE | • |
| Lloyd's Register | • |
| Complies with Machinery Directive 2006/42/EC | • |