

## PRI 418 [EL SOM LAM IB RF] Rotary ironer, electrically heated with leaf-spring padding, feed-in belts and return feed for marine applications.



- Performance 104.0 kg/h<sup>\*</sup>, roller diameter 365 mm, working width 1750 mm
- Fast cooling of textiles EasyFold feed table
- State-of-the-art controls Touch display
- Selection of the most important settings favourite programmes
- Perfect rotary ironing performance flexibly positioned heater plate

EAN: 4002516367772 / Material number: 11606890 / Old Material Number: 53418107SOM

Laundry infeed at the front, laundry outfeed at the back  Professional Iron grey
laundry outfeed at the back  Professional
Iron arev
non groy
365
1750
Aluminium
Leaf-spring padding
ARAMID needle-felt cloth
•
•
104.0
63.0
20000
Touch display
Touch-Display PRI
Setting of defined
programme parameters
1.5
5.4
Infinitely variable
Electric
3 AC 450V 50-60HZ
22.40
23.00
50
3 AC 440V 50-60HZ
21.40
22.00
50
1110
2469
1441
1388
2576
1096
444
521
4356
56 dB(A) re 20 μPa

With 25 % residual moisture – performance data according to DIN 11902: the achievable ironing performance depends on overall conditions such as, for example, the type of laundry and the experience of the operator.



## PRI 418 [EL SOM LAM IB RF] Rotary ironer, electrically heated with leaf-spring padding, feed-in belts and return feed for marine applications.



EAN: 4002516367772 / Material number: 11606890 / Old Material Number: 53418107SOM

Features	
Patented EasyFold out-feed table	•
Outfeed table extension (optional)	•
HPC heater plate	•
Automatic finger guard	•
FlexControl footswitch	•
In-feed table with feed-in bands	•
Pick-off bands	•
Laundry box	•
Laundry return feed	•
Cover (optional)	•
Favourite programme	•
Incorrect feed recognition	•
Air suspension	•
Pause function	•
High contact pressure	•
Clean and wax heater plate indicator (op	•
Emergency switch-off	•
APRI 319 care set for the heater plate included in the scope of delivery	•
Machine-independent accessories	•
Connection options	
Peak load cut-out/energy management (optional)	•
Standards, test certificates and symbols	
VDE	•
CE	•
WEEE	•
VDE-EMC	•
Splash-proof IPX0	•
UKCA	•
Complies with Machinery Directive 2006/42/EC	•