

PDR 922 [HW] Professional vented dryer, heated with hot water with programmable M Touch Pro controls for the maximum in flexibility.



- Drum volume 400.00 l, load size29 (13.0) lb (kg) kg–16.0 kg
- Unique, gentle fabric care honeycomb drum
- Excellent energy efficiency thanks to Air Recycling Plus
- Precision drying of all fabrics –
 PerfectDry
- Connected for the future using LAN and WiFi

EAN: 4002516409137 / Material number: 11718230 / Old Material Number: 52922005EU

Construction type and version	
Construction type and version	Front loador
Construction type	Front loader Performance Plus
Range Front	
Load size with a load ratio of 1:32	29 (13.0) lb (kg)
Load size with a load ratio of 1:25	
Drum volume in I	400.00
Drying system	Hot water
Door opening [Ø] in mm	
Door opening angle in degrees	
Door hinge	left
Convertible door hinging	•
Stainless steel honeycomb drum	Yes
Application	
Suitable for the hotel and catering industry	•
Suitable for retirement and care homes	•
Suitable for facility management	•
Suitable for dry cleaners	•
Suitable for commercial laundries	•
Suitable for fire brigades and rescue services	•
Suitable for studs, riding schools and stables	
Suitable for universities, nurseries, and schools	•
Suitable for hospitals	•
Suitable for sports clubs	•
Suitable for beauty salons, spas, and fitness centres	•
Suitable for doctors' and dentists' practices	•
Suitable for the petrochemicals industry	•
Suitable for the food-processing industry	•
Suitable for amusement parks & holiday complexes	•
Suitable for state/community care facilities	•
Performance data	
Specific energy consumption in kWh/kg	0.56
Programme duration in min.	60
Service life in drying cycles	40000
Control system	
Control system	M Touch Pro
Programmability	programmable
User interface	Residual moisture
	controlled
Max. delay start in h	24
Time left display	•
Programme sequence indicator	•
Selectable display languages	•
Standard electrical connection	
Heating type	Hot water
Electrical connection	1N AC 230V 50/60HZ
Electric heater rating in kW	0.00
Heater rating, hot water in kW	9.80
Total connected load in kW	1.00
Fuse rating in A	10
5	



PDR 922 [HW] Professional vented dryer, heated with hot water with programmable M Touch Pro controls for the maximum in flexibility.



EAN: 4002516409137 / Material number: 11718230 / Old Material Number: 52922005EU

Marine and a factorial and a second second	00
Maximum water intake temperature in °C	90
Dimensions and weight of dryer	
External dimensions, height in mm	1400
External dimensions, width in mm	906
External dimensions, depth in mm	1162
External dimensions, gross height in mm	1526
External dimensions, gross width in mm	1090
External dimensions, gross depth in mm	1254
Net weight in kg	231.9
Gross weight in kg	246
Maximum floor load in N/m ²	2600
Emissions data	
Emission sound pressure level in the workplace	62 dB(A) re 20 µPa
Heat dissipation into the room in MJ/h	2.60
Features	
Intelligent drum reversal	•
Axial airflow	•
Large-surface fluff filter	•
PerfectDry	•
SoftLift drum ribs	•
AirRecyclingPlus	•
Communication slot	•
Emergency switch-off	•
Machine-independent accessories	•
Connection options	
Payment system (optional)	•
Optical interface for service access	•
Peak load cut-out/energy management (optional)	•
WiFi tumble dryer	•
Connector Box	•
LAN module (optional)	•
Capacities	
Respirator masks [number]	16
Overalls [number]	2
Over jackets [number]	3
Synthetic duvets [number]	1
Synthetic pillows [number]	3
Down duvets [number]	2
Down pillows [number]	2
Cloths, 22 g [number]	364
Cotton mops, 40 cm [number]	58
Cotton mops, 50 cm [number]	51
Microfibre mops, 40 cm [number]	93
Microfibre mops, 50 cm [number]	65
Summer horse blankets [number]	3
Standards, test certificates and symbols	
CE	•
VDE	•
VDE-EMC	•
Splash-proof safety rating IPX4	•
WEEE	•



PDR 922 [HW] Professional vented dryer, heated with hot water with programmable M Touch Pro controls for the maximum in flexibility.



EAN: 4002516409137 / Material number: 11718230 / Old Material Number: 52922005EU

•

•

UKCA

Complies with Machinery Directive 2006/42/EC