

PDR 928 [HW] Professional vented dryer, heated with hot water with programmable M Touch Pro controls for the maximum in flexibility.



- Drum volume 500.00 l, load size36 (16.0) lb (kg) kg–20.0 kg
- Unique, gentle fabric care honeycomb drum
- Excellent energy efficiency thanks to Air Recycling Plus
- Precision drying of all fabrics PerfectDry
- Connected for the future using LAN and WiFi

EAN: 4002516409175 / Material number: 11718270 / Old Material Number: 52928007EU

Construction type and version	
Construction type	Front loader
Range	Performance Plus
Front	Iron grey
Load size with a load ratio of 1:32	36 (16.0) lb (kg)
Load size with a load ratio of 1:25	20.0
Drum volume in I	500.00
Drying system	Hot water
Door opening [Ø] in mm	520
Door opening angle in degrees	180
Door hinge	left
Convertible door hinging	•
Stainless steel honeycomb drum	Yes
Application	
Suitable for the hotel and catering industry	•
Suitable for retirement and care homes	•
Suitable for facility management	•
Suitable for dry cleaners	•
Suitable for commercial laundries	•
Suitable for fire brigades and rescue services	•
Suitable for studs, riding schools and stables	•
Suitable for universities, nurseries, and schools	•
Suitable for hospitals	•
Suitable for sports clubs	•
Suitable for beauty salons, spas, and fitness centres	
Suitable for doctors' and dentists' practices	
Suitable for the petrochemicals industry	•
Suitable for the food-processing industry	•
Suitable for amusement parks & holiday complexes	•
Suitable for state/community care facilities	
Performance data	
	0.49
Specific energy consumption in kWh/kg Programme duration in min.	55
Service life in drying cycles	40000
Control system	40000
•	M Touch Dro
Control system	M Touch Pro programmable
Programmability Llagr interface	
User interface	Residual moisture controlled
Max. delay start in h	24
Time left display	•
Programme sequence indicator	•
Selectable display languages	•
Standard electrical connection	
	Hot water
Heating type	Hot water
Electrical connection	1N AC 230V 50/60HZ
Electric heater rating in kW	0.00
Heater rating, hot water in kW	10.00
Total connected load in kW	1.20
Fuse rating in A	10



PDR 928 [HW] Professional vented dryer, heated with hot water with programmable M Touch Pro controls for the maximum in flexibility.



EAN: 4002516409175 / Material number: 11718270 / Old Material Number: 52928007EU

Maximum water intake temperature in °C	90
Dimensions and weight of dryer	
External dimensions, height in mm	1640
External dimensions, width in mm	1206
External dimensions, depth in mm	1019
External dimensions, gross height in mm	1766
External dimensions, gross width in mm	1390
External dimensions, gross depth in mm	1108
Net weight in kg	281.3
Gross weight in kg	296
Maximum floor load in N/m ²	3171
Emissions data	
Emission sound pressure level in the workplace	60 dB(A) re 20 µPa
Heat dissipation into the room in MJ/h	3.30
Features	0.00
Intelligent drum reversal	•
Axial airflow	•
Large-surface fluff filter	•
PerfectDry	-
SoftLift drum ribs	•
	•
AirRecyclingPlus	`
Communication slot	
Emergency switch-off	•
Machine-independent accessories	•
Connection options	
Payment system (optional)	<u> </u>
Optical interface for service access	<u> </u>
Peak load cut-out/energy management (optional)	<u> </u>
WiFi tumble dryer	<u> </u>
Connector Box	<u> </u>
LAN module (optional)	•
Capacities	
Respirator masks [number]	12
Overalls [number]	2
Over jackets [number]	3
Synthetic duvets [number]	1
Synthetic pillows [number]	3
Down duvets [number]	2
Down pillows [number]	5
Cloths, 22 g [number]	545
Cotton mops, 40 cm [number]	75
Cotton mops, 50 cm [number]	63
Microfibre mops, 40 cm [number]	116
Microfibre mops, 50 cm [number]	83
Summer horse blankets [number]	2
Standards, test certificates and symbols	
CE	•
VDE	•
VDE_ VDE-EMC	•
	•



PDR 928 [HW] Professional vented dryer, heated with hot water with programmable M Touch Pro controls for the maximum in flexibility.



EAN: 4002516409175 / Material number: 11718270 / Old Material Number: 52928007EU

UKCA • • Complies with Machinery Directive 2006/42/EC • • •